



Features

- Low forward voltage drop
- High current capability
- High reliability
- High surge current capability

Mechanical Data

Cases	: Moulded plastic DO-41
Lead	: Axial leads, solderable per MIL-STD-202, Method 208 guaranteed
Polarity	: Colour band denotes cathode end
High temperature soldering guaranteed	: 260°C/10 seconds/0.375", (9.5mm) lead lengths at 5lbs., (2.3kg) tension
Weight	: 0.34g

Maximum Ratings and Electrical Characteristics:

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.


Type Number	Symbol	Value	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	1,000	V
Maximum RMS Voltage	V_{RMS}	700	
Maximum DC Blocking Voltage	V_{DC}	1,000	
Maximum Average Forward Rectified Current 0.375" (9.5mm) Lead Length at $T_A = 60^\circ\text{C}$	$I_{(AV)}$	1.5	A
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	50	
Maximum Instantaneous Forward Voltage at 1.5A	V_F	1	V
Maximum DC Reverse Current at $T_A = 25^\circ\text{C}$ at Rated DC Blocking Voltage at $T_A = 125^\circ\text{C}$	I_R	5 100	μA μA
Typical Junction Capacitance (Note 1)	C_J	15	pF
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	65	$^\circ\text{C/W}$
Operating Temperature Range	T_J	-65 to +175	$^\circ\text{C}$
Storage Temperature Range	T_{STG}		

Note 1: Measured at 1MHz and Applied Reverse Voltage of 4V DC.


Note 2: Mount on Cu-Pad Size 5mm × 5mm on PCB.

Ratings and Characteristic Curves


Typical Forward Characteristics




Maximum Non-Repetitive Forward Surge Current




Maximum Forward Current Derating Curve



Typical Junction Capacitance



Dimensions:



Dimensions : Inches (Millimetres)

Part Number Table

Description	Part Number
Standard Diode, 1.5A, 1,000V	1N5399G+

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.