



Features:

- Low power loss, high efficiency
- Low forward voltage drop
- Low reverse leakage current
- High surge current capability
- Plastic material has UL flammability classification 94V-0

Mechanical Data:

Case	: TO-220AC molded plastic
Lead	: MIL-STD-202E method 208C guaranteed
Weight	: 2.24 grams
Mounting Position	: Any
Reverse Voltage	: 200 to 600 Volts
Forward Current	: 8 Amperes

Maximum Ratings and Electrical Characteristics:

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.




For capacitive load, derate current by 20%.

Characteristics	Symbol	MUR820+	MUR840+	MUR860+	Unit
Max. Recurrent Peak Reverse Voltage	V _{RRM}	200	400	600	V
Max. RMS Voltage	V _{RMS}	200	400	600	
Max. DC Blocking Voltage	V _{DC}	140	280	420	
Max. Average Forward Rectified Current @ T _L = 95°C	I _o	8			A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load (JEDEC Method)	I _{FSM}	100			
Typical Thermal Resistance (Note 2)	R _{θJC}	3	2		
Peak Forward Voltage at 20A DC	V _F	0.95	1.3	1.5	V
Max. DC Reverse Current at T _A = 25°C Rated DC Blocking Voltage at T _A = 100°C	I _R	5 250			μA
Maximum Reverse Recovery Time (Note 1)	T _{RR}	35	50		nS
Operating Temperature Range	T _J	-55 to +150			°C
Storage Temperature Range	T _{STG}				


Notes:

1. Measured with $I_F = 0.5\text{A}$, $I_R = 1\text{A}$, $I_{RR} = 0.25\text{A}$.
2. Thermal resistance junction to case mounted on heatsink.
3. The typical data above is for reference only

Ratings and Characteristic Curves



Dimensions:



Dimensions : Inches (Millimetres)

Part Number Table

Description	Part Number
Super Fast Rectifiers	MUR820+
	MUR840+
	MUR860+

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.