



**RoHS
Compliant**

Feature

- Hermetically sealed, glass silicon diodes.

Absolute Maximum Ratings (T_A = 25°C)

Description	Symbol	Values	Unit
Average Forward Current (averaged Over any 20ms period)	I _{F(av)}	250	mA
Repetitive Peak Forward Current	I _{FRM}	250	
Total Power Dissipation up to T _{flange} = 50°C	P _{tot}	500	mW
Up to Ta = 50°C and Mounted on a Ceramic Substrate of 10mm × 10mm × 0.6mm	P _{tot}	400	
Non-Repetitive Peak Reverse Power Dissipation t = 100μs, T _J = 150°C	P _{ZSM}	30	W
Storage Temperature	T _{STG}	- 65 to +200	°C
Junction Temperature	T _J	200	
Thermal Resistance			
From Junction to tie-point (flanges)	R _{th (j-tp)}	0.3	K/mW
From Junction to Ambient when Mounted on a Ceramic Substrate of 10mm × 10mm × 0.6mm	R _{th (j-a)}	0.38	

Electrical Characteristics (T_A = 25°C unless specified otherwise)

Working Voltage* ±5% V _Z (V) at I _{Ztest} = 5mA		Differential * Resistance r _{diff} (Ω) at I _{Ztest} = 5mA	Temperature Coefficient Sz(mV/K) at I _{Ztest} = 5mA		Differential Resistance r _{diff} (Ω) at I _{Ztest} = 1mA	I _R T _A 25°C (μA)	V _R V	Part Number
Minimum	Maximum	Maximum	Minimum	Maximum	Maximum	Maximum		
9.4	10.6	20	4.5	8	150	0.2	7	BZV55C10
10.4	11.6	20	5.4	9	150	0.1	8	BZV55C11
11.4	12.7	25	6	10	150	0.1	8	BZV55C12
12.4	14.1	30	7	11	170	0.1	8	BZV55C13
13.8	15.6	30	9.2	13	200	0.05	10.5	BZV55C15
15.3	17.1	40	10.4	14	200	0.05	11.2	BZV55C16
16.8	19.1	45	12.4	16	225	0.05	12.6	BZV55C18
18.8	21.2	55	14.4	18	225	0.05	14	BZV55C20
20.8	23.3	55	16.4	20	250	0.05	15.4	BZV55C22
22.8	25.6	70	18.4	22	250	0.05	16.8	BZV55C24

Working Voltage* ±5% Vz (V) at I _{Ztest} = 5mA		Differential * Resistance r _{diff} (Ω) at I _{Ztest} = 5mA	Temperature Coefficient Sz(mV/K) at I _{Ztest} = 5mA		Differential Resistance r _{diff} (Ω) at I _{Ztest} = 1mA	I _R T _A 25°C (μA)	V _R V	Part Number
Minimum	Maximum	Maximum	Minimum	Maximum	Maximum	Maximum		
at I _{Ztest} = 2mA		at I _{Ztest} = 2mA	at I _{Ztest} = 2mA		at I _{Ztest} = 0.5mA			
25.1	28.9	80	21.4	25.3	300	0.05	18.9	BZV55C27
28	32	80	24.4	29.4	300	0.05	21	BZV55C30
31	35	80	27.4	33.4	325	0.05	23.1	BZV55C33
34	38	90	30.4	37.4	350	0.05	25.2	BZV55C36
3.4	3.8	90	-3.5	0	600	5	1	BZV55C3V6
3.7	4.1	90	-3.5	0	600	3	1	BZV55C3V9
40	46	150	37.6	46.6	375	0.05	30.1	BZV55C43
44	50	170	42	51.8	375	0.05	32.9	BZV55C47
4	4.6	90	-3.5	0	600	3	1	BZV55C4V3
4.4	5	80	-3.5	0.2	500	3	2	BZV55C 4V7
48	54	180	46.6	57.2	400	0.05	35.7	BZV55C51
4.8	5.4	60	-2.7	1.2	480	2	2	BZV55C 5V1
5.2	6	40	-2	2.5	400	1	2	BZV55C 5V6
5.8	6.6	10	0.4	3.7	150	3	4	BZV55C 6V2
7	7.9	15	2.5	5.3	80	1	5	BZV55C 7V5
7.7	8.7	15	3.2	6.2	80	0.7	5	BZV55C 8V2
8.5	9.6	15	3.8	7	100	0.5	6	BZV55C 9V1

*Pulse test: 20ms < t_p < 50ms

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.