


XX :01~03Meters
01 :01Meter
03 :03Meters

Cable Length(L):01~03Meters

Note:

- * **QC** Important Dimension.
- * Waterproof Rate: IP67
- * Connector: USB3.0—A Male, Black
- * Gasket: Silicone, Gray
- * Cable:USB 3.0,(1P*28#+D+Al/My)*2+1P*28#+2C*28#+F+Al+B, Black, PVC Jacket, UV Resistant,OD=5.5mm
- * Cable Length Tolerance:01M:±40mm
02M~03M:±60mm
- * All of Drain twisted together.

Shield	Braid	編織	Shield		
9	Orange	28AWG	橙	9	Twist
8	Purple	28AWG	紫	8	
7	Drain	28AWG		7	Twist
6	Yellow	28AWG	黃	6	
5	Blue	28AWG	藍	5	
	Drain	28AWG			
4	Black	28AWG	黑	4	Twist
3	Green	28AWG	綠	3	
2	White	28AWG	白	2	
1	Red	28AWG	紅	1	
Conn.1	Wire Color			Conn.2	
Pin Out					



Pin Assignments

Front View

UNIT:mm	
TOLERANCE	
$\pm 0.5\text{mm}$	

TITLE			USB 3.0, Cable Lock F Conn M Pin To M Plug		
SCALE		Free	SHEET		1 OF 1
REV.	A	SIZE	A4 :Inspection Item		

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Kevin Wang	DATE 2012/12/05
DWG NO UA-30AFM-LD7BXX	CHECKED BY Micky	DATE 2012/12/05
CUSTOMER AI TW	APPROVED BY Maslow	DATE 2012/12/05