

# NVMFD5853NL

## Power MOSFET

40 V, 10 mΩ, 34 A, Dual N-Channel Logic Level, Dual SO-8FL

### Features

- Small Footprint (5x6 mm) for Compact Designs
- Low  $R_{DS(on)}$  to Minimize Conduction Losses
- Low Capacitance to Minimize Driver Losses
- NVMFD5853NLWF – Wettable Flanks Option for Enhanced Optical Inspection
- AEC-Q101 Qualified and PPAP Capable
- This is a Pb-Free Device

### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Parameter                                                                                                                                                                            |                                                            |                                | Symbol            | Value      | Unit               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|--------------------------------|-------------------|------------|--------------------|
| Drain-to-Source Voltage                                                                                                                                                              |                                                            |                                | $V_{DSS}$         | 40         | V                  |
| Gate-to-Source Voltage                                                                                                                                                               |                                                            |                                | $V_{GS}$          | $\pm 20$   | V                  |
| Continuous Drain Current $R_{\Psi J-mb}$ (Notes 1, 2, 3, 4)                                                                                                                          | Steady State                                               | $T_{mb} = 25^{\circ}\text{C}$  | $I_D$             | 34         | A                  |
|                                                                                                                                                                                      |                                                            | $T_{mb} = 100^{\circ}\text{C}$ |                   | 24         |                    |
| Power Dissipation $R_{\Psi J-mb}$ (Notes 1, 2, 3)                                                                                                                                    |                                                            | $T_{mb} = 25^{\circ}\text{C}$  | $P_D$             | 24         | W                  |
|                                                                                                                                                                                      |                                                            | $T_{mb} = 100^{\circ}\text{C}$ |                   | 12         |                    |
| Continuous Drain Current $R_{\theta JA}$ (Notes 1, 3 & 4)                                                                                                                            | Steady State                                               | $T_A = 25^{\circ}\text{C}$     | $I_D$             | 12         | A                  |
|                                                                                                                                                                                      |                                                            | $T_A = 100^{\circ}\text{C}$    |                   | 8.5        |                    |
| Power Dissipation $R_{\theta JA}$ (Notes 1 & 3)                                                                                                                                      |                                                            | $T_A = 25^{\circ}\text{C}$     | $P_D$             | 3.0        | W                  |
|                                                                                                                                                                                      |                                                            | $T_A = 100^{\circ}\text{C}$    |                   | 1.5        |                    |
| Pulsed Drain Current                                                                                                                                                                 | $T_A = 25^{\circ}\text{C}$ , $t_p = 10\text{ }\mu\text{s}$ |                                | $I_{DM}$          | 165        | A                  |
| Operating Junction and Storage Temperature                                                                                                                                           |                                                            |                                | $T_J$ , $T_{stg}$ | -55 to 175 | $^{\circ}\text{C}$ |
| Source Current (Body Diode)                                                                                                                                                          |                                                            |                                | $I_S$             | 34         | A                  |
| Single Pulse Drain-to-Source Avalanche Energy ( $T_J = 25^{\circ}\text{C}$ , $V_{GS} = 10\text{ V}$ , $I_{L(pk)} = 28.3\text{ A}$ , $L = 0.1\text{ mH}$ , $R_G = 25\text{ }\Omega$ ) |                                                            |                                | $E_{AS}$          | 40         | mJ                 |
| Lead Temperature for Soldering Purposes (1/8" from case for 10 s)                                                                                                                    |                                                            |                                | $T_L$             | 260        | $^{\circ}\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

### THERMAL RESISTANCE MAXIMUM RATINGS (Note 1)

| Parameter                                                    | Symbol          | Value | Unit               |
|--------------------------------------------------------------|-----------------|-------|--------------------|
| Junction-to-Mounting Board (top) – Steady State (Notes 2, 3) | $R_{\Psi J-mb}$ | 6.2   | $^\circ\text{C/W}$ |
| Junction-to-Ambient – Steady State (Note 3)                  | $R_{\theta JA}$ | 51    |                    |
| Junction-to-Ambient – Steady State (min footprint)           |                 | 162   |                    |

1. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
2. Psi ( $\Psi$ ) is used as required per JESD51-12 for packages in which substantially less than 100% of the heat flows to single case surface.
3. Surface-mounted on FR4 board using a 650 mm<sup>2</sup>, 2 oz. Cu pad.
4. Continuous DC current rating. Maximum current for pulses as long as 1 second are higher but are dependent on pulse duration and duty cycle.




ON Semiconductor®

<http://onsemi.com>


| $V_{(BR)DS}$ | $R_{DS(on)}$ MAX | $I_D$ MAX |
|--------------|------------------|-----------|
| 40 V         | 10 mΩ @ 10 V     | 34 A      |
|              | 15 mΩ @ 4.5 V    |           |

### Dual N-Channel



DFN8 5x6  
(SO8FL)  
CASE 506BT

### MARKING DIAGRAM



5853NL = Specific Device Code for NVMFD5853NL

5853LW = Specific Device Code for NVMFD5853NLWF

A = Assembly Location

Y = Year

W = Work Week

ZZ = Lot Traceability

### ORDERING INFORMATION

| Device           | Package        | Shipping†          |
|------------------|----------------|--------------------|
| NVMFD5853NLT1G   | DFN8 (Pb-Free) | 1500 / Tape & Reel |
| NVMFD5853NLWFT1G | DFN8 (Pb-Free) | 1500 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

# NVMFD5853NL

## ELECTRICAL CHARACTERISTICS (T<sub>J</sub> = 25°C unless otherwise specified)

| Parameter                                                 | Symbol                               | Test Condition                                   | Min | Typ  | Max  | Unit  |
|-----------------------------------------------------------|--------------------------------------|--------------------------------------------------|-----|------|------|-------|
| <b>OFF CHARACTERISTICS</b>                                |                                      |                                                  |     |      |      |       |
| Drain-to-Source Breakdown Voltage                         | V <sub>(BR)DSS</sub>                 | V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA   | 40  |      |      | V     |
| Drain-to-Source Breakdown Voltage Temperature Coefficient | V <sub>(BR)DSS</sub> /T <sub>J</sub> |                                                  |     | 37.1 |      | mV/°C |
| Zero Gate Voltage Drain Current                           | I <sub>DSS</sub>                     | V <sub>GS</sub> = 0 V,<br>V <sub>DS</sub> = 40 V |     |      | 1.0  | μA    |
|                                                           |                                      |                                                  |     |      | 100  |       |
| Gate-to-Source Leakage Current                            | I <sub>GSS</sub>                     | V <sub>DS</sub> = 0 V, V <sub>GS</sub> = ±20 V   |     |      | ±100 | nA    |

## ON CHARACTERISTICS (Note 5)

|                                            |                                     |                                                             |     |      |     |       |
|--------------------------------------------|-------------------------------------|-------------------------------------------------------------|-----|------|-----|-------|
| Gate Threshold Voltage                     | V <sub>GS(TH)</sub>                 | V <sub>GS</sub> = V <sub>DS</sub> , I <sub>D</sub> = 250 μA | 1.4 |      | 2.4 | V     |
| Negative Threshold Temperature Coefficient | V <sub>GS(TH)</sub> /T <sub>J</sub> |                                                             |     | 5.9  |     | mV/°C |
| Drain-to-Source On Resistance              | R <sub>DS(on)</sub>                 | V <sub>GS</sub> = 10 V, I <sub>D</sub> = 15 A               |     | 8.4  | 10  | mΩ    |
|                                            |                                     | V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 15 A              |     | 12.7 | 15  |       |
| Forward Transconductance                   | g <sub>FS</sub>                     | V <sub>DS</sub> = 5 V, I <sub>D</sub> = 5 A                 |     | 22   |     | S     |

## CHARGES AND CAPACITANCES

|                              |                     |                                                                           |  |      |  |    |
|------------------------------|---------------------|---------------------------------------------------------------------------|--|------|--|----|
| Input Capacitance            | C <sub>iss</sub>    | V <sub>GS</sub> = 0 V, f = 1.0 MHz, V <sub>DS</sub> = 25 V                |  | 1100 |  | pF |
| Output Capacitance           | C <sub>oss</sub>    |                                                                           |  | 152  |  |    |
| Reverse Transfer Capacitance | C <sub>rss</sub>    |                                                                           |  | 100  |  |    |
| Total Gate Charge            | Q <sub>G(TOT)</sub> | V <sub>GS</sub> = 4.5 V, V <sub>DS</sub> = 32 V,<br>I <sub>D</sub> = 15 A |  | 12.8 |  | nC |
| Threshold Gate Charge        | Q <sub>G(TH)</sub>  |                                                                           |  | 1.0  |  |    |
| Gate-to-Source Charge        | Q <sub>GS</sub>     |                                                                           |  | 3.7  |  |    |
| Gate-to-Drain Charge         | Q <sub>GD</sub>     |                                                                           |  | 7.0  |  |    |
| Total Gate Charge            | Q <sub>G(TOT)</sub> | V <sub>GS</sub> = 10 V, V <sub>DS</sub> = 32 V, I <sub>D</sub> = 15 A     |  | 23   |  | nC |

## SWITCHING CHARACTERISTICS (Note 6)

|                     |                     |                                                                                                   |  |     |  |    |
|---------------------|---------------------|---------------------------------------------------------------------------------------------------|--|-----|--|----|
| Turn-On Delay Time  | t <sub>d(on)</sub>  | V <sub>GS</sub> = 4.5 V, V <sub>DS</sub> = 20 V,<br>I <sub>D</sub> = 15 A, R <sub>G</sub> = 2.5 Ω |  | 10  |  | ns |
| Rise Time           | t <sub>r</sub>      |                                                                                                   |  | 53  |  |    |
| Turn-Off Delay Time | t <sub>d(off)</sub> |                                                                                                   |  | 17  |  |    |
| Fall Time           | t <sub>f</sub>      |                                                                                                   |  | 30  |  |    |
| Turn-On Delay Time  | t <sub>d(on)</sub>  | V <sub>GS</sub> = 10 V, V <sub>DS</sub> = 20 V,<br>I <sub>D</sub> = 15 A, R <sub>G</sub> = 2.5 Ω  |  | 9.0 |  | ns |
| Rise Time           | t <sub>r</sub>      |                                                                                                   |  | 23  |  |    |
| Turn-Off Delay Time | t <sub>d(off)</sub> |                                                                                                   |  | 22  |  |    |
| Fall Time           | t <sub>f</sub>      |                                                                                                   |  | 4.3 |  |    |

## DRAIN-SOURCE DIODE CHARACTERISTICS

|                         |                 |                                                                                 |                        |  |      |     |    |
|-------------------------|-----------------|---------------------------------------------------------------------------------|------------------------|--|------|-----|----|
| Forward Diode Voltage   | V <sub>SD</sub> | V <sub>GS</sub> = 0 V,<br>I <sub>S</sub> = 20 A                                 | T <sub>J</sub> = 25°C  |  | 0.84 | 1.1 | V  |
|                         |                 |                                                                                 | T <sub>J</sub> = 125°C |  | 0.69 |     |    |
| Reverse Recovery Time   | t <sub>RR</sub> | V <sub>GS</sub> = 0 V, dI <sub>S</sub> /dI = 100 A/μs,<br>I <sub>S</sub> = 15 A |                        |  | 20   |     | ns |
| Charge Time             | t <sub>a</sub>  |                                                                                 |                        |  | 12   |     |    |
| Discharge Time          | t <sub>b</sub>  |                                                                                 |                        |  | 8.1  |     |    |
| Reverse Recovery Charge | Q <sub>RR</sub> |                                                                                 |                        |  | 12.1 |     | nC |

5. Pulse Test: pulse width = 300 μs, duty cycle ≤ 2%.

6. Switching characteristics are independent of operating junction temperatures.

TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs.  $V_{GS}$




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area

TYPICAL CHARACTERISTICS




Figure 12. Thermal Response

## PACKAGE DIMENSIONS

## ISSUE E



1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM THE TERMINAL TIP.
4. PROFILE TOLERANCE APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.
5. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.
6. SEATING PLANE IS DEFINED BY THE TERMINALS. A1 IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.
7. A VISUAL INDICATOR FOR PIN 1 MUST BE LOCATED IN THIS AREA.

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN         | MAX  | MAX  |
| A   | 0.90        | ---- | 1.10 |
| A1  | ----        | ---- | 0.05 |
| b   | 0.33        | 0.42 | 0.51 |
| b1  | 0.33        | 0.42 | 0.51 |
| c   | 0.20        | ---- | 0.33 |
| D   | 5.15 BSC    |      |      |
| D1  | 4.70        | 4.90 | 5.10 |
| D2  | 3.90        | 4.10 | 4.30 |
| D3  | 1.50        | 1.70 | 1.90 |
| E   | 6.15 BSC    |      |      |
| E1  | 5.70        | 5.90 | 6.10 |
| E2  | 3.90        | 4.15 | 4.40 |
| e   | 1.27 BSC    |      |      |
| G   | 0.45        | 0.55 | 0.65 |
| h   | ----        | ---- | 12 ° |
| K   | 0.51        | ---- | ---- |
| K1  | 0.56        | ---- | ---- |
| L   | 0.48        | 0.61 | 0.71 |
| M   | 3.25        | 3.50 | 3.75 |
| N   | 1.80        | 2.00 | 2.20 |

DIMENSION: MILLIMETERS

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**ON Semiconductor** and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marketing.pdf](http://www.onsemi.com/site/pdf/Patent-Marketing.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**

Phone: 421 33 790 2910

**Japan Customer Focus Center**

Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative