


INTERCONNECTION

Pluggable Terminal Strips Plug in Style

- Moulded in natural PA6, self extinguishing to UL94-V2
- Printing available on request
- CE Approved

CTSN/MF



SPECIFICATION

Voltage (max)	450V AC
Working temperature	110°C
No. of poles	2
Moulding	UL94-V2 Self extinguishing PA6
Conducting bush	Nikel plated brass
Screws	Zinc, plated steel

MALE

TYPE NO.	SIZE / RATING	INSERT DIAMETER	TERMINAL SCREWS	LENGTH	WIDTH	HEIGHT	PITCH	FIXING HOLE DIAMETER	MAX CURRENT
CTSN434/2/M	12.5mm/16A	4.3mm	M3.5	20.1mm	23.5mm	19mm	12.3mm	3.5mm	57A

FEMALE

TYPE NO.	SIZE / RATING	INSERT DIAMETER	TERMINAL SCREWS	LENGTH	WIDTH	HEIGHT	PITCH	FIXING HOLE DIAMETER	MAX CURRENT
CTSN434/2/F	12.5mm/16A	4.3mm	M3.5	20.1mm	23.5mm	19mm	12.3mm	3.5mm	57A

PCB
TERMINAL
BLOCKS

INTER-
CONNECTION

FUSES &
FUSE-
HOLDERS

LEDS &
INDICATORS

MINIATURE
SWITCHES

LIMIT &
SAFETY
SWITCHES

CONTROL
PRODUCTS

INTERFACE
MODULES &
SUPPORTS

RELAY
BASES

DIN RAIL
ENCLOSURES

BATTERIES

SOLAR
PANELS

TRANS-
FORMERS