



Description

This is a three phase AC output solid state relay, control voltage is 4-32VDC, load current is 25A and 60A. Load voltage range 24-660V AC. SCR output, dielectric strength $\geq 4000\text{Vrms}$ (Input/Output), $\geq 2500\text{Vrms}$ (Input,Output/Base). The load voltage is 480 Volts.

Features

- Zero-crossing switching
- Rated load current: 25A and 60A
- SCR output
- Dielectric strength $\geq 4000\text{Vrms}$
- Opto-isolation
- MOV protection circuit

Applications

Suitable for three-phase motor control, kiln temperature control system, large oven etc.

Technical Specification

Input Circuit

Control Voltage Range	: 4V DC to 32V DC
Min. Turn-On Voltage	: 4V DC
Min. Turn-Off Voltage	: 1V DC
Max. Reverse Voltage	: 32V DC
Max. Input Current	: 35mA @ 32V DC

Output Circuit

Load Voltage Range	: 24 ~ 530V AC
Max. Turn-on Time	: 10ms
Max. Turn-off Time	: 10ms
Max. Surge Current [@10ms]	
25A	: 300A
60A	: 1000A
Transient Over Voltage	: 1200Vpk
Max. I^2t For Fusing [@10ms]	
25A	: 450A ² S
60A	: 5000A ² S
Max. Off-State Leakage Current [@ Rated Voltage]	: 5mA
Max. On-State Voltage Drop [@ Rated Current]	: 1.6Vrms
Min. Off-State dv/dt [@ Max. Rated Voltage]	: $\geq 500\text{ V}/\mu\text{s}$

Solid State Relay



General Information

Dielectric Strength (50/60Hz)

Input/Output

: $\geq 4000V_{rms}$

Input, Output/Base

: $\geq 2500V_{rms}$

Ambient Operating Temperature Range

: $-30^{\circ}C$ to $+80^{\circ}C$


Ambient Storage Temperature Range

: $-30^{\circ}C$ to $+100^{\circ}C$


Weight [Typical]

: For 25A it is 385g and for 60A it is 520g



Diagram



Dimensions : Millimetres



Thermal Curve



Part Number Table

Description	Part Number
SSR, 25A, 4-32V DC, 3 Phase	MCKSQF480D25
SSR, 60A, 4-32V DC, 3 Phase	MCKSQF480D60

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com
www.farnell.com
www.newark.com

