



IDEAL POWER LTD

SPECIFICATION FOR APPROVAL

CUSTOMER/客户 : 01097
ARTICLE/品名: SWITCHING MODE POWER SUPPLY
SPECIFICATION /规格: BS
MODEL NO/产品型号.: DYS618-090160W-3
OUR PART NO./产品编号: DYS618-090160-17306E
CUSTOMER P. N/客户料号:
INPUT/输入 : 100-240V AC 50/60Hz
OUTPUT/输出: 9.0V DC 1.6A
INPUT/输入 : 100-240V AC 50/60Hz
REV/DATE:/版本/日期: 01 2017/03/06

Vendor Confirmation/供应商确认			Confirmation Approved/客户确认		
Made by	Checked by	Approved by	Made by	Checked by	Approved by
Zhouliu	Liufei	Rock Bin			
Remark/备注:					

IDEAL POWER LTD


Add: 14 Larks Way, Tree Beech Enterprise Park, Gunn, Barnstaple, Devon, England EX32 7NZ.

TEL: +44(0) 845 2603400

FAX: +44(0) 845 2603401

E-mail: sales@ideалpower.co.uk

[Http://www.idealpower.co.uk](http://www.idealpower.co.uk)



IDEAL POWER LTD

SWITCHING MODE POWER SUPPLY

SPECIFICATION

CONTENTS/目录

1	Compendium/简述	4
2	Input Characteristics/输入特性	4
2.1	Input Voltage & Frequency/输入电压&频率	4
2.2	Input AC Current/AC 输入电流	4
2.3	Inrush Current (Cold Start)/浪涌电流(冷启动)	4
2.4	Efficiency (Normal)/效率(额定输入)	4
2.5	Energy Consumption /空载功耗.....	4
3	Output Characteristics/输出特性	5
3.1	Static Output Characteristics <Vo & R+N>/静态输出特性	5
3.2	Line / Load Regulation/线性/负载调整率	5
3.3	Turn on Delay Time/开机延迟时间	5
3.4	Hold up Time/关机维持时间	5
3.5	Capacitance Load/容性负载.....	5
3.6	Output Overshoot / Undershoot/输出过冲/欠冲	5
3.7	Output Load Transient Response/输出负载瞬态响应	5
4	Protection Requirements/保护特性	6
4.1	Over Current Protection/过流保护	6
4.2	Short Circuit Protection/短路保护	6
4.3	Over Voltage Protection/过压保护.....	6
5	Environment Requirements/环境要求	6
5.1	Operating Temperature and Relative Humidity/操作温/湿度要求	6
5.2	Storage Temperature and Relative Humidity/存储温/湿度要求	6
5.3	Vibration/振动	6
5.4	Drop in /跌落	6
6	Reliability Requirements/可靠性要求.....	7
6.1	Burn-in/煲机.....	7
6.2	MTBF Qualification/平均间隔故障时间估算.....	7
7	EMI/EMS Standards/EMI/EMS 标准.....	7
7.1	EMI Standards/EMI 标准.....	7
7.2	EMS Standards/EMS 标准.....	7
8	Safety Standards/安规标准.....	8
8.1	Safety Accord with/安全:符合标准.....	8
8.2	Dielectric Strength(Hi-pot)/介电耐压强度(高压)	8
8.3	Leakage Current/漏电流.....	8
8.4	Insulation Resistance/绝缘阻抗.....	8
9	Outline Drawing/外观示意图:	9
10	DC Cord Drawing/DC 线示意图:	10
11	Marking Drawing/铭牌示意图:	11
12	Package Drawing/包装示意图:	12
13	Sample Test Report/样品测试报告:	13

IDEAL POWER LTD

SWITCHING MODE POWER SUPPLY

SPECIFICATION

1. Compendium/简述

The document details the electrical, mechanical and environmental specifications of a SMPS, the power supply provides 14.4 W continuous output power.

资料详细描述了一款 14.4 W(连续输出功率)开关电源的电气性，结构性及环境等要求。

The power supply shall meet the RoHS requirements.

此款电源符合 RoHS 要求。

1.1 Description/描述

- | | |
|---|---|
| ☒ SMPS Adapter(Wall mount)/插墙式适配器 | ☐ SMPS Adapter(Interchangeable)/可换头适配器 |
| ☐ SMPS Adapter(Desk-top)/桌面型适配器 | ☐ Open Frame/开放式结构 |
| ☐ SMPS Unit (With Case)/带铁壳型 | ☐ Others/其他 |

2. Input Characteristics/输入特性

2.1 Input Voltage & Frequency/输入电压与频率

The range of input voltage is from 90Vac to 264Vac with a single phase.

输入电压范围：从 90Vac 到 264Vac, 单相输入。

	Minimum/最小	Nominal/额定值	Maximum/最大
Input Voltage/输入电压	90Vac	100Vac~240Vac	264Vac
Input Frequency/输入频率	47Hz	60Hz/50Hz	63Hz

2.2 Input AC Current/AC 输入电流

0.5Amax @ 100-240Vac input & Full load/在 100 – 240 Vac 输入和满载条件下最大 0.5A 有效值

2.3 Inrush Current (cold start)/浪涌电流(冷启动)

The inrush current will not exceed 60A at 100-240Vac input and Max load for a cold start at 25℃

在 100-240V 交流电输入和最大负载冷启动环境 25℃时浪涌电流不能超过 60A

2.4 Average Efficiency/平均效率

While input 115Vac and 230Vac, the average efficiency is more than 83.92%.

The test point is at 25%, 50%, 75% and 100% of max load respectively.

在输入 115Vac 和 230Vac 条件下，平均效率不小于 83.92%。

测试点分别是最大载的 25%,50%,75%和 100%。

2.5 Energy Consumption /空载功耗

While input 115Vac or 230Vac and the output is no load,the input power loss must be less than 0.1W

IDEAL POWER LTD

SWITCHING MODE POWER SUPPLY

SPECIFICATION

在输入 115Vac/230Vac 时,空载功耗小于 0.1W

3. Output Characteristics/输出特性

3.1 Static Output Characteristics <Vo & R+N>/静态输出特性<输出&纹波+噪音>

Output	Rated Load/额定负载			Output Range	R+N	Remark
Rate	Min. Load	Max. Load		输出电压范围	纹波与噪声	备 注
+9V	0.0A	1.6A		8.55V-9.45V	150mVp-p	

Ripple & Noise: Measurement is done by 20MHz bandwidth oscilloscope and the output paralleled a 0.1uF ceramic capacitor and a 10uF electrolysis capacitor.

(test under the condition of rated input and rated output)

纹波与噪声: 量测时示波器选用 20MHz 带宽限制,输出端要并联一颗 0.1uF 的陶瓷电容和一颗 10uF 的电 解电容。(在额定输入及输出的条件下检测)

3.2 Line/ Load Regulation/线性/负载调整率

Output	Load Condition/负载条件		Line Regulation	Load Regulation	Remark
Rate	Min. Load	Max. Load	线性调整率	负载调整率	备 注
+9V	0.0A	1.6A	± 3%	± 5%	

3.3 Turn - on Delay Time/开机延迟时间

3S max. @ 100 Vac to 240 Vac input & Full load

在 100Vac 到 240Vac 输入和满载条件下最大 3S

3.4 Hold-up Time/关机维持时间

5mS min. @ Full load & 115Vac/60Hz input turn off at worst case

在 115Vac 输入,满载同时最差情况下关机, 最小 5mS

3.5 Capacitance Load/容性负载

While input 100~240Vac and capacitance load is 470uF, the adapter can turn on normally and the output is in the rated range.

在输入 100~240Vac, 470uF 容性负载条件下, 适配器能正常开机。
并且输出电压范围在额定范围下。

3.6 Output Overshoot / Undershoot/输出过冲/欠冲

10% max. When the power on or off

当电源开/关机时, 10%最大

IDEAL POWER LTD

SWITCHING MODE POWER SUPPLY

SPECIFICATION

3.7 Output Load Transient Response/输出负载瞬态响应

the output shall not exceed 10% of the nominal output voltage, load fluctuation: from 20% to 80%, R/S: 0.25A/uS, frequency: 100Hz duration and 10mS at 80%.

输出电压不能超过额定电压的 10%,负载变化: 从 20%到 80%, 斜率: 0.25A/uS, 频率: 100Hz, 80%负载持续时间为 10mS.

4. Protection Requirements/保护要求

4.1 Over Current Protection/过流保护

Over Current Point Limited/过流点限制: $I > 2.5A$

The output shall hiccup when the over currents applied to the output rail, and shall be self-recovery when the fault condition is removed

当过电流时, 输出将进入打嗝模式, 当过流情况解除后, 产品将会自动恢复正常

4.2 Short Circuit Protection/短路保护

The input power shall decrease when the output rail short, the power supply shall no damage, and shall be self-recovery when the fault condition is removed

当输出短路时,产品输入功率降低且不会损伤,当短路情况解除后,产品将会自动恢复正常

4.3 Over Voltage Protection/过压保护

The power supply shall protection when the output over voltage. The output shall latched and shall be recovery when the fault condition is removed and power on again.

当输出发生过压时, 产品进入保护模式, 故障解除后重新上电恢复正常.

5. Environment Requirements/环境要求

5.1 Operating Temperature and Relative Humidity/操作温/湿度要求

0°C to +40°C

10%RH to 90%RH

5.2 Storage Temperature and Relative Humidity/存储温/湿度要求

-20°C to +80°C

5%RH to 95%RH non-condensing @ Sea level shall be low 10,000 feet/低于 10,000 英尺

5.3 Vibration/振动

10 to 300Hz sweep at a constant acceleration of 1.0G(Breadth: 3.5mm) for 1Hour for

each of the perpendicular axes X, Y, Z

扫描频率: 10 to 300Hz, 加速度: 1.0G(位移: 3.5mm), X, Y, Z 三垂直坐标轴向各振动 1 小时

5.4 Drop in/跌落

Height: 1m; the product should be fell off on the hardwood with the thickness of 20mm, and the hardwood should be put on the base of the cement or on the ground without

IDEAL POWER LTD

SWITCHING MODE POWER SUPPLY

SPECIFICATION

flexibility. Apply one times on all surface.
跌落高度:1 米, 并跌落到厚度为 20mm 的硬木上, 且硬木应放在水泥基座或等同的无弹性地面上, 每面各 1 次.

6. Reliability Requirements/可靠性要求

6.1 Burn-in/煲机

The power supply shall be burn-in at least 4 Hours under normal input and

80% rated load at $40^{\circ}\text{C} \pm 5^{\circ}\text{C}$

产品至少要在 $40^{\circ}\text{C} \pm 5^{\circ}\text{C}$ 的环境及 80%以上额定负载条件下煲机 4 小时

6.2 MTBF Qualification/平均间隔故障时间估算

The MTBF shall be at least 50,000hours at 25°C , Full load and nominal

input condition

平均间隔故障时间: 至少 50,000 小时, 25°C 环境及额定输入与满载条件下

7. EMI/EMS Standards/EMI/EMS 标准

7.1 EMI Standards/EMI 标准

☐ FCC Part15 class B

☒ EN55022

☐ EN55013

☐ EN55014-1

☐ EN61204-3 (CISPR 22)

☐ AS/NZS CISPR22

☐ AS/NZS CISPR13

☐ AS/NZS CISPR14. 1

☐ GB9254

☐ GB13837

☐ GB17625. 1

☐ J55022

☐ J55013

☐ J55014-1

☐ KN22

☐ KN13

☐ KN14-1

☐ CNS13438

7.2 EMS Standards/EMS 标准

☒ EN55024

☐ EN55020

☐ EN55014-2

☐ EN61204-3

7.2.1 IEC 61000-4-2, electrostatic discharge(ESD) requirement/静电抗扰度要求

Discharge characteristic/静电规格	Test level/测试条件	Test criteria/测试标准
Air discharge/空气放电	+/-8KV	B
Contact discharge/接触放电	+/-4 KV	B

7.2.2 IEC 61000-4-4, electric fast transients(EFT) immunity requirement/电快速瞬变脉冲群

Coupling/测试端口	Test level/测试条件	Test criteria/测试标准
---------------	-----------------	--------------------

IDEAL POWER LTD

SWITCHING MODE POWER SUPPLY

SPECIFICATION

AC-input/交流输入	0.5KV	A
AC-input/交流输入	1KV	B

7.2.3 IEC 61000-4-5, surge capability requirement/浪涌抗扰度要求

Surge voltage/雷击电压	Test criteria/测试标准
Differential mode/差模 +/-1KV	A
Common mode/共模 +/-2KV	

7.2.4 Assessment criteria /评估标准

Acceptable criteria 可接受标准	Performance 性能
A	Performance is not allowed to be changed, any changes should be within the specified limits 性能不允许变化；如果性能会发生变化，则变化的范围在产品规格书规定的范围内。
B	During the testing process, the performance degradation is allowed within the specifications of the product specification. After the elimination, the equipment can return to normal and no reset or any manual intervention is allowed. . 设备在测试过程中，性能降低允许在产品规格书要求范围内，干扰消除后，设备能恢复正常，不允许出现复位和任何方式的人工干预。

8. Safety Standards/安规标准

8.1 Safety Accord with/安全:符合标准

- | | |
|---|---|
| ☐ UL60950-1, CSA C22.2 NO. 60950-1 | ☐ UL60065, CSA C22.2 NO. 60065 |
| ☐ UL1310 | |
| ☒ IEC60950-1 | ☐ IEC60065 |
| ☒ EN60950-1 | ☐ EN60065 |
| ☐ AS/NZS 60950.1 | ☐ AS/NZS 60065 |
| ☐ GB4943.1 | ☐ GB8898 |
| ☐ J60950-1 | ☐ J60065 |
| ☐ K60950-1 | ☐ K60065 |
| ☐ CNS14336-1 | ☐ CNS14408 |

Note: AC pins corresponding to relative national standards.

注：相应的 AC 插脚对应相应国家的标准。

IDEAL POWER LTD
SWITCHING MODE POWER SUPPLY
SPECIFICATION

8.2 Dielectric Strength(Hi-pot)/介电耐压强度(高压)

Primary to Secondary: 4242VDC / 5mA Max / 60second(3 seconds for mass production)

初级对次级: 4242VDC / 5mA Max / 60 秒(生产时高压测试时间: 3 秒)

8.3 Leakage Current/漏电流

0.25mA max. at 264Vac / 50Hz / 在 264Vac / 50Hz 输入时, 最大漏电流 0.25mA

8.4 Insulation Resistance/绝缘阻抗

50MΩ min. at primary to secondary add 500Vdc test voltage


在初级与次级间加 500Vdc 进行测试,最小绝缘阻抗 50MΩ

9. Outline Drawing/外观示意图:

IDEAL POWER LTD

SWITCHING MODE POWER SUPPLY

SPECIFICATION




10. DC Cord Drawing/DC 线示意图:

IDEAL POWER LTD

SWITCHING MODE POWER SUPPLY

SPECIFICATION



11. Marking Drawing/铭牌示意图:

IDEAL POWER LTD

SWITCHING MODE POWER SUPPLY

SPECIFICATION

1

2

3

4

5

6

A

B

C

D

E

1:1

Remark:

Layout: Black Word on Silver Back ground

Material quality: Meta lized polyester

Rating of temperature: 85℃

Thickness: 0.25 ± 0.01

Apply to lead-less Standard

1017 Where 10 represents the number of weeks
17 represents the number of year
The date niu change allordng fo prodnction
date change, if any spelial lircum sfanles, wiu
be nofiled by sales

名称:	铭牌	REV:	A	图例:	
图号:	DYS618-LB17306E	型号:	DYS618-090160W-3	页号:	6
尺寸公差	比例	1:1	绘图	校对	批准
±0.05	±0.10	单位	MM	赵柳	寅成
±0.15	±0.20	日期	2017.03.06		高峰

1

2

3

4

5

6

A

B

C

D

E

IDEAL POWER LTD
SWITCHING MODE POWER SUPPLY
SPECIFICATION

12. Package Drawing/包装示意图:

PLASTIC BAG/PE袋







WHITE BOX/白盒



CARDBOARD/纸板



PAPER CASE/纸箱



MECHANICAL DIMENSION:

	L(mm)	W(mm)	H(mm)
PLASTIC BAG	210	130	
WHITE BOX	94	60	90
CARDBOARD	395	255	
PAPER CASE	405	265	300

PACKING METHOD:

PACKING METHOD	16PCS/LAYER *3LAYERS
QTY	48PCS
N.G	5.5Kg
G.W	6.8Kg

IDEAL POWER LTD

SWITCHING MODE POWER SUPPLY

SPECIFICATION

13. Sample Test Report/样品测试报告:

Customer:01097			Product Name: Swithing Mode Power Supply				P/N:DYS618-090160-17306E			
Product Specification: AC100-240V 50/60Hz DC 9.0V/1.6A						Safety: BS				
Item No.	Testing Title		Test Result	Sample Number and Test Result						
	Items	Condition		1	2	3	4	5	PASS	
Basic Electrical Characteristics	1、No load voltage	AC90V/60Hz	DC 9.0 ± 0.45 V	9.23	9.26	9.21			PASS	
		AC180V/50Hz	DC 9.0 ± 0.45 V	9.23	9.26	9.21			PASS	
		AC264V/50Hz	DC 9.0 ± 0.45 V	9.23	9.26	9.21			PASS	
	2、Full Load voltage	AC90V/60Hz	DC 9.0 ± 0.45 V	8.92	9.03	8.86			PASS	
		AC180V/50Hz	DC 9.0 ± 0.45 V	8.94	9.03	8.66			PASS	
		AC264V/50Hz	DC 9.0 ± 0.45 V	8.94	9.03	8.66			PASS	
	3、Full Load input power	AC90V/60Hz	FULL LOAD (W)	16.92	17.00	16.92			PASS	
		AC180V/50Hz	FULL LOAD (W)	16.54	16.60	16.54			PASS	
		AC264V/50Hz	FULL LOAD (W)	16.65	16.68	16.64			PASS	
	4、Efficiency	AC115V/60Hz	≥ 83.92%(Average Of 25/50/75/100% Loads)	86.69	87.10	86.31			PASS	
		AC230V/50Hz	≥ 83.92%(Average Of 25/50/75/100% Loads)	86.37	87.14	86.15			PASS	
	5、Ripple & noise	AC90V/60Hz	≤150 mV (FULL LOAD)	90	100	105			PASS	
		AC180V/50Hz	≤150 mV (FULL LOAD)	85	80	75			PASS	
		AC264V/50Hz	≤150 mV (FULL LOAD)	70	80	70			PASS	
	6、Standby power		< 0.1 W	0.06	0.05	0.03			PASS	
	7、Short-circuit test		No output when short circuit happens work normally after recovery (240Vac)	0.22	0.17	0.19			PASS	
	8、over-current		2.5 - 4.5 A (100Vac)	3.28	3.35	3.37			PASS	
	9、over-current		2.5 - 4.5 A (240Vac)	3.35	3.43	3.40			PASS	
	10、Noise test		40db MAX, 10CM	OK	OK	OK			PASS	
	11、Hi-pot test		DC4242V 60S<5mA	OK	OK	OK			PASS	
	12、Temperature rise		At normal temperature 25℃, case surface temperature rise ≤55℃	OK	OK	OK			PASS	
	13、DC Cable size		Customer Request:2.1*5.5*12.0 L=1.5M	2.1 * 5.5 * 12.0 L = 1.5M H					PASS	
Test status	1、High temperature		□ 20℃ ■80℃ ■48H □96H	OK	OK	OK			PASS	
	2、Low temperature		■-20℃ □-40℃ ■48H □96H	OK	OK	OK			PASS	
	3、Constant humidity		■ 40℃ 95%RH ■48H □96H	OK	OK	OK			PASS	
	4、Plugfest(male to		3000 times Min	OK	OK	OK			PASS	
	5、Burn-in test		≥8hours AC100/240V each 4H full load	OK	OK	OK			PASS	

----- END -----