



Features:


- 3W Low Profile <15.5mm Height
- MTBF: 1,000,000 Hours
- Wide Input Range: 90 - 305VAC
- Low Standby Power <0.15W
- High Temperature 85°C Full Load
- EMC Compliant - No External Components
- TUV, EN62368-1, EN61558-2-16
- UL File No. E472059

Part Number	Power Rating Watts	Output Voltage (VDC)	Output Current (mA)	Ambient Temp. (°C)	Efficiency Typical	Voltage Range
VTX-214-003-303	3	3.3	900	85	>72%	90 - 305VAC
VTX-214-003-305	3	5	600			
VTX-214-003-306	3	6	500			
VTX-214-003-307	3	7.5	400			
VTX-214-003-308	3	8	375			
VTX-214-003-309	3	9	333			
VTX-214-003-310	3	10	300			
VTX-214-003-312	3	12	250			
VTX-214-003-315	3	15	200			
VTX-214-003-318	3	18	166			
VTX-214-003-324	3	24	125			
VTX-214-003-348	3	48	62			
Note: Other output voltages are available upon request.						

Optional Universal PCB mounting kit.

Part Number:

VTX-214-PCB1



Please contact Vigortronix for any enquiries. Products can be altered to suit custom requirements.
The information contained in this document is subject to change without notice.


Vigortronix, 16 De Havilland Way, Witney, Oxfordshire, OX29 0YG, UK
Tel. +44 (0)1993 777570 Web. www.vigortronix.com, E-mail: sales@vigortronix.com
Vigortronix is a trading name of Vigortronix Limited

Vigortronix.com

Model: 3 Watt		Specification
INPUT Pin 1: L Pin 2: N	Voltage Input Range	90 ~ 305VAC (100 ~ 430VDC)
	Voltage Rating	100 ~ 277VAC
	Frequency (Hz)	47 ~ 63
	Current	3.5W Max (100VAC/240VAC)
	Inrush Current	5A Max (100VAC) / 10A Max (240VAC)
	No Load power	0.15W Max
	Leakage Current	0.2 mA Max
OUTPUT Pin 5: DC+ Pin 4: 0V	Voltage Accuracy	±3% (3.3VDC 5%)
	Ripple	3% Vout (Vp~p) (3.3VDC 5%)
	Noise	3% Vout (Vp~p) (3.3VDC 5%)
	Efficiency @ 230VAC	>72%
	Minimum Load	0
Protection	Over Power	Hiccup mode
	Over Voltage	Hiccup mode
	Short Circuit Protection	Hiccup mode
Dielectric Isolation	Input to Output	>3600Vrms ,1min (>4200Vrms, 2 sec Minimum)
Enviroment	Operating Temperature	-25°C ~ +85°C (See Derating Curve)
	Storage Temperature	-40°C ~ +105°C
	MTBF	>1,000,000Hrs @ 25°C (MIL-HDBK-217F)
	Weight	24g
Safety	Agency Standards	Compliance with EN61558-1, EN61558-2-16, UL/EN62368-1
EMC	EMI	Compliance with EN55032 Class B, EN61000-3-2, 3
	EMS	Compliance with EN55035

Please contact Vigortronix for any enquiries. Products can be altered to suit custom requirements.
The information contained in this document is subject to change without notice.

Converter Schematic



Note:


A fuse is recommended on the input

Type: 2A/300V Slow Blow

MOV: 14D561K



Note: C1 and TVS are optional

Dimensions:



Derating Graph:

Unit weight: 24g



Please contact Vigortronix for any enquiries. Products can be altered to suit custom requirements.
 The information contained in this document is subject to change without notice.