

battery type: Lithium Button Cell
battery size: CR2477
chemical system: Lithium Manganese Dioxide

Conditions

nominal voltage: 3.0 V
open circuit voltage: 3.0...3.4 V new battery
 2.9...3.4 V after 1 year storage at 20°C



all measurements at 22 ± 2°C ambient

capacity
 rated: 1000 mAh continuous discharge at 4.7kΩ load; 24hours/day
 End Voltage (EV): 2.0V
 minimum: 900 mAh continuous discharge at 4.7kΩ load; 24hours/day
 EV: 2.0V

standard discharge time
 minimum: 155 h at 680Ω load (for QC measurement)
 EV: 2.0V

discharge currents
 standard: 0.2 mA
 max. recommended current
 under continuous discharge: 6 mA
 max. recommended current
 under pulse discharge: 30 mA

discharge diagrams:




shelf life: 10 years under proper storage conditions (ta: ≤ 22°C; RH: 60 ± 15%)
self-discharge: ≤ 2 % per year (at 20°C ambient temperature)

operating temperature range: - 20...70 °C

storage temperature: 0...30 °C (recommended)

mechanical specifications:

outer battery dimensions
 diameter: 24.5mm +0/-0.3mm
 height: 7.7mm +0/-0.4mm



nominal weight: 10.5 g (approx.)



107



ANSMANN Specifications for model:

data sheet no. / part no.

supplier no.

author / date

Lithium Button Cell CR2477

704080

TG / 07.10.2019