


Surface Mount – 600V



Additional Information



Resources



Accessories



Samples


Description

The BTB12 is designed for high performance full-wave AC control applications where high noise immunity and high commutating di/dt are required.


Features

- Blocking Voltage to 600 V
- On-State Current Rating of 12 Amperes RMS at 80°C
- Uniform Gate Trigger Currents in Three Quadrants
- High Immunity to dV/dt – 10 V/ μ s minimum at 125°C
- Minimizes Snubber Networks for Protection
- Industry Standard TO-220AB Package
- High Commutating di/dt – 1.75 A/ms minimum at 110°C
- These are Pb–Free Devices

Functional Diagram



Pin Out



BTB12-600TW3G

Surface Mount – 600V

Maximum Ratings (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Peak Repetitive Off-State Voltage (Note 1) (Gate Open, Sine Wave 50 to 60 Hz, T _J = -40° to 110°C)	V_{DRM}^* V_{RRM}	600	V
On-State RMS Current (Full Cycle Sine Wave, 60 Hz, T _C = 80°C)	I_T (RMS)	12	A
Peak Non-Repetitive Surge Current (One Full Cycle Sine Wave, 60 Hz, T _C = 25°C)	I_{TSM}	126	A
Circuit Fusing Consideration (t = 8.3 ms)	I^2t	66	A ² sec
Non-Repetitive Surge Peak Off-State Voltage (T _J = 25°C, t = 10 ms)	V_{DSM}^*/V_{RSM}	$V_{DSM}^*/V_{RSM} + 100$	V
Peak Gate Current (T _J = 110°C, t = 20 μs)	I_{GM}	4.0	W
Peak Gate Power (Pulse Width ≤ 1.0 μs, T _C = 80°C)	P_{GM}	20	W
Average Gate Power (T _J = 110°C)	$P_{G(AV)}$	1.0	W
Operating Junction Temperature Range	T _J	-40 to +110	°C
Storage Temperature Range	T _{stg}	-40 to +150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. V_{DRM}^* and V_{RSM} for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

Thermal Characteristics

Rating	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case (AC) Junction-to-Ambient	$R_{\theta JC}$ $R_{\theta JA}$	1.8 60	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 10 seconds	T _L	260	°C

Electrical Characteristics - OFF (T_J = 25°C unless otherwise noted ; Electricals apply in both directions)

Characteristic	Symbol	Min	Typ	Max	Unit
Peak Repetitive Blocking Current (V _D = V _{DRM} = V _{RRM} ; Gate Open)	I_{DRM}^* I_{RRM}	-	-	0.005	mA
		-	-	1.0	

Electrical Characteristics - ON (T_J = 25°C unless otherwise noted; Electricals apply in both directions)

Characteristic	Symbol	Min	Typ	Max	Unit
Forward On-State Voltage (Note 2) (I _{TM} = ±17 A Peak)	V _{TM}	–	–	1.55	V
Gate Trigger Current (Continuous dc) (V _D = 12 V, R _L = 30 Ω)	I_{GT}	1.2	–	5.0	mA
	MT2(+), G(+)	1.2	–	5.0	
	MT2(+), G(–)	1.2	–	5.0	
	MT2(–), G(–)	1.2	–	5.0	
Holding Current (V _D = 12 V, Gate Open, Initiating Current = ±100 mA)	I _H	–	–	10	mA
Latching Current (V _D = 1.2 V, I _G = 7.5 mA)	I_L	–	–	15	mA
	MT2(+), G(+)	–	–	15	
	MT2(+), G(–)	–	–	15	
	MT2(–), G(–)	–	–	15	
Gate Trigger Voltage (V _D = 12 V, R _L = 30 Ω)	V _{GT}	0.5	–	1.3	V
	MT2(+), G(+)	0.5	–	1.3	
	MT2(+), G(–)	0.5	–	1.3	
	MT2(–), G(–)	0.5	–	1.3	
Gate Non-Trigger Voltage (T _J = 110°C)	V _{GD}	0.2	–	–	V
	MT2(+), G(+)	0.2	–	–	
	MT2(+), G(–)	0.2	–	–	
	MT2(–), G(–)	0.2	–	–	

2. Indicates Pulse Test: Pulse Width ≤ 2.0 ms, Duty Cycle ≤ 2%.

BTB12-600TW3G


Surface Mount – 600V

Dynamic Characteristics


Characteristic	Symbol	Min	Typ	Max	Unit
Rate of Change of Commutating Current, See Figure 10. (Gate Open, $T_J = 125^\circ\text{C}$, No Snubber)	$(di/dt)_c$	1.75	–	–	A/ms
Critical Rate of Rise of On-State Current ($T_J = 125^\circ\text{C}$, $f = 120\text{ Hz}$, $I_G = 2 \times I_{GT}$, $tr \leq 100\text{ ns}$)	di/dt	–	–	45	A/ μs
Critical Rate of Rise of Off-State Voltage ($V_D = 0.66 \times V_{DRM}$, Exponential Waveform, Gate Open, $T_J = 125^\circ\text{C}$)	dV/dt	10	–	–	V/ μs

Voltage Current Characteristic of SCR

Symbol	Parameter
V_{DRM}	Peak Repetitive Forward Off State Voltage
I_{DRM}	Peak Forward Blocking Current
V_{RRM}	Peak Repetitive Reverse Off State Voltage
I_{RRM}	Peak Reverse Blocking Current
V_{TM}	Maximum On State Voltage
I_H	Holding Current



Quadrant Definitions for a Triac








All polarities are referenced to MT1.

With in-phase signals (using standard AC lines) quadrants I and III are used






BTB12-600TW3G

Surface Mount – 600V

Figure 1. RMS Current Derating**Figure 2. On-State Power Dissipation****Figure 3. On-State Characteristics****Figure 4. Thermal Response****Figure 5. Typical Hold Current Variation**

BTB12-600TW3G

Surface Mount – 600V


Figure 6. Typical Gate Trigger Current Variation**Figure 7. Typical Gate Trigger Voltage Variation****Figure 8. Typical Latching Current Variation****Figure 9. Critical Rate of Rise of Off-State Voltage (Exponential Waveform)****Figure 10. Simplified Test Circuit to Measure the Critical Rate of Rise of Commutating Current (di/dt)**

Note: Component values are for verification of rated (di/dt)_c. See AN1048 for additional information


BTB12-600TW3G

Surface Mount – 600V

Dimensions



Part Marking System



**TO-220AB
CASE 221A
STYLE 12**

x = 6 or 8
Y = Year
M = Month
A = Assembly Site
XX = Lot Serial Code
G = Pb-Free Package



Dim	Inches		Millimeters	
	Min	Max	Min	Max
A	0.590	0.620	14.99	15.75
B	0.380	0.420	9.65	10.67
C	0.178	0.188	4.52	4.78
D	0.025	0.035	0.64	0.89
F	0.142	0.147	3.61	3.73
G	0.095	0.105	2.41	2.67
H	0.110	0.130	2.79	3.30
J	0.018	0.024	0.46	0.61
K	0.540	0.575	13.72	14.61
L	0.060	0.075	1.52	1.91
N	0.195	0.205	4.95	5.21
Q	0.105	0.115	2.67	2.92
R	0.085	0.095	2.16	2.41
S	0.045	0.060	1.14	1.52
T	0.235	0.255	5.97	6.47
U	0.000	0.050	0.00	1.27
V	0.045	-	1.15	-
Z	-	0.080	-	2.04

1. Dimensioning and tolerancing per ANSI Y14.5m, 1982.
2. Controlling dimension: inch.
3. Dimension Z defines a zone where all body and lead irregularities are allowed.

Pin Assignment	
1	Main Terminal 1
2	Main Terminal 2
3	Gate
4	No Connection

Ordering Information

Device	Package	Shipping
BTB12-600TW3G	TO-220AB (Pb-Free)	1000 Units / Box

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.