P-Channel Enhancement-Mode Vertical DMOS FETs

Features

- Free from secondary breakdown
- Low power drive requirement
- Ease of paralleling
- Low C_{ISS} and fast switching speeds
- Excellent thermal stability
- Integral source-drain diode
- High input impedance and high gain

Applications

- Motor controls
- Converters
- Amplifiers
- Switches
- Power supply circuits
- Drivers (relays, hammers, solenoids, lamps, memories, displays, bipolar transistors, etc.)

General Description

This enhancement-mode (normally-off) transistor utilizes a vertical DMOS structure and Supertex's well-proven, silicon-gate manufacturing process. This combination produces a device with the power handling capabilities of bipolar transistors and the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, this device is free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where very low threshold voltage, high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

Ordering Information

Part Number	Package Option	Packing
VP0106N3-G	TO-92	1000/Bag
VP0106N3-G P002	TO-92	2000/Reel
VP0106N3-G P003		
VP0106N3-G P005		
VP0106N3-G P013		
VP0106N3-G P014		

-G denotes a lead (Pb)-free / RoHS compliant package.
Contact factory for Wafer / Die availablity.
Devices in Wafer / Die form are lead (Pb)-free / RoHS compliant.

Product Summary

BV_{DSS}/BV_{DGS}	$R_{DS(ON)}$ (max)	$I_{D(ON)}$ (min)
-60V	8.0Ω	-500mA

Pin Configuration



TO-92

Absolute Maximum Ratings

Parameter	Value
Drain-to-source voltage	BV_{DSS}
Drain-to-gate voltage	BV_{DGS}
Gate-to-source voltage	±20V
Operating and storage temperature	-55°C to +150°C

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.

Product Marking

YY = Year Sealed
WW = Week Sealed
_____ = "Green" Packaging

Package may or may not include the following marks: Si or

TO-92

Typical Thermal Resistance

Package	θ_{ja}
TO-92	132°C/W

Thermal Characteristics

Package	I_D (continuous)†	I_D (pulsed)	Power Dissipation @T_c = 25°C	I_{DR}†	I_{DRM}
TO-92	-250mA	-800mA	1.0W	-250mA	-800A

Notes:

† I_D *(continuous) is limited by max rated* T_j .

Electrical Characteristics *(T_A = 25°C unless otherwise specified)*

Sym	Parameter	Min	Typ	Max	Units	Conditions
BV_{DSS}	Drain-to-source breakdown voltage	-60	-	-	V	V_{GS} = 0V, I_D = -1.0mA
$V_{GS(th)}$	Gate threshold voltage	-1.5	-	-3.5	V	V_{GS} = V_{DS}, I_D = -1.0mA
$\Delta V_{GS(th)}$	Change in $V_{GS(th)}$ with temperature	-	5.8	6.5	mV/°C	V_{GS} = V_{DS}, I_D = -1.0mA
I_{GSS}	Gate body leakage current	-	-1.0	-100	nA	V_{GS} = ±20V, V_{DS} = 0V
I_{DSS}	Zero gate voltage drain current	-	-	-10	µA	V_{GS} = 0V, V_{DS} = Max Rating
		-	-	-1.0	mA	V_{DS} = 0.8 Max Rating, V_{GS} = 0V, T_A = 125°C
$I_{D(ON)}$	On-state drain current	-0.15	-0.25	-	A	V_{GS} = -5.0V, V_{DS} = -25V
		-0.5	-1.2	-		V_{GS} = -10V, V_{DS} = -25V
$R_{DS(ON)}$	Static drain-to-source on-state resistance	-	11	15	Ω	V_{GS} = -5.0V, I_D = -100mA
		-	6.0	8.0		V_{GS} = -10V, I_D = -500mA
$\Delta R_{DS(ON)}$	Change in $R_{DS(ON)}$ with temperature	-	0.55	1.0	%/°C	V_{GS} = -10V, I_D = -500mA
G_{FS}	Forward transconductance	150	190	-	mmho	V_{DS} = -25V, I_D = -500mA
C_{ISS}	Input capacitance	-	45	60	pF	V_{GS} = 0V, V_{DS} = -25V, f = 1.0MHz
C_{OSS}	Common source output capacitance	-	22	30		
C_{RSS}	Reverse transfer capacitance	-	3.0	8.0		
$t_{d(ON)}$	Turn-on delay time	-	4.0	6.0	ns	V_{DD} = -25V, I_D = -500mA, R_{GEN} = 25Ω
t_r	Rise time	-	3.0	10		
$t_{d(OFF)}$	Turn-off delay time	-	8.0	12		
t_f	Fall time	-	4.0	10		
V_{SD}	Diode forward voltage drop	-	-1.2	-2.0	V	V_{GS} = 0V, I_{SD} = -1.0A
t_{rr}	Reverse recovery time	-	400	-	ns	V_{GS} = 0V, I_{SD} = -1.0A

Notes:

1. *All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300µs pulse, 2% duty cycle.)*
2. *All A.C. parameters sample tested.*

Switching Waveforms and Test Circuit



Typical Performance Curves

BV_{DSS} Variation with Temperature



On-Resistance vs. Drain Current



Transfer Characteristics



$V_{(th)}$ and R_{DS} Variation with Temperature



Capacitance vs. Drain-to-Source Voltage



Gate Drive Dynamic Characteristics



Typical Performance Curves *(cont.)*

Output Characteristics



Saturation Characteristics



Transconductance vs. Drain Current



Power Dissipation vs. Case Temperature



Maximum Rated Safe Operating Area



Thermal Response Characteristics



3-Lead TO-92 Package Outline (N3)



Front View



Side View



Bottom View

Symbol		A	b	c	D	E	E1	e	e1	L
Dimensions (inches)	MIN	.170	.014†	.014†	.175	.125	.080	.095	.045	.500
	NOM	-	-	-	-	-	-	-	-	-
	MAX	.210	.022†	.022†	.205	.165	.105	.105	.055	.610*

JEDEC Registration TO-92.
** This dimension is not specified in the JEDEC drawing.*
† This dimension differs from the JEDEC drawing.
Drawings not to scale.
***Supertex Doc.#:** DSPD-3TO92N3, Version E041009.*

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to http://www.supertex.com/packaging.html.)

Supertex inc. does not recommend the use of its products in life support applications, and will not knowingly sell them for use in such applications unless it receives an adequate "product liability indemnification insurance agreement." **Supertex inc.** does not assume responsibility for use of devices described, and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions and inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications refer to the **Supertex inc.** (website: http//www.supertex.com)

©2013 **Supertex inc.** All rights reserved. Unauthorized use or reproduction is prohibited.

Supertex inc.
1235 Bordeaux Drive, Sunnyvale, CA 94089
Tel: 408-222-8888
www.supertex.com