




THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.



REVIEWS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	12/13/16	D.FRISIELLO



"P1"
USB 3.0 SERIES "A" PLUG
CONTACTS 30μ GOLD



"P2"
USB 3.0 SERIES "MICRO B"
RIGHT ANGLE PLUG
CONTACTS 30μ GOLD



PART NUMBER	LENGTH METERS [FEET]
CA3A-90RMICB-03M	0.3 [.98]
CA3A-90RMICB-05M	0.5 [1.64]
CA3A-90RMICB-1M	1.0 [3.28]
CA3A-90RMICB-2M	2.0 [6.56]
CA3A-90RMICB-3M	3.0 [9.84]
CA3A-90RMICB-5M	5.0 [16.41]

UL STYLE 20276,
(2) TWISTED PAIR, 30AWG WITH
ALUM/POLY FOIL SHIELD AND DRAIN WIRE,
(1) UNSHIELDED TWISTED PAIR, 30AWG,
(2) CONDUCTORS, 24AWG,
OVERALL ALUMINUM/MYLAR AND BRAIDED SHIELD,
JACKET: PVC, BLUE (PANTONE 300C)
(NOM DIA. .217" [5.5], MIN BEND RAD 2.17" [55])

NOTES:

1. CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
2. CABLE ASSEMBLY MUST MEET USB 3.0 REQUIREMENTS.
3. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
4. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:
CE2011/65/EU(RoHS DIRECTIVE)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 [5.08] .XX = ±.02 [51] .XXX = ±.005 [13] PROJECTION 	APPROVALS	DATE	 50 HIGH STREET NORTH ANDOVER, MA 01845	
	DRAWN BY D.CASTRO	1/15/15		
	CHECKED BY S.LI	12/13/16	CATEGORY USB	
	APPROVED BY S.PAN	12/13/16	PRODUCT DESCRIPTION CA USB 3.0 STR A/90RT MICRO B	
CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		SIZE A	FSCM NO. 43321	DWG. NO. CA3A-90RMICB
COLOR VARIATIONS MAY OCCUR		SCALE: NONE	CAD FILE: CA3A-90RMICB.SLDDRW	REV. A
		SHEET 1 OF 1		