

# XMLP006GD71P

pressure transmitter 6bar - 0..10V - G1/4A  
male - EPDM - M12



## Main

|                           |                                                                                              |
|---------------------------|----------------------------------------------------------------------------------------------|
| Range of product          | OsiSense XM                                                                                  |
| Product or component type | Electronic pressure sensors                                                                  |
| Pressure sensor type      | Pressure transmitter                                                                         |
| Pressure sensor name      | XMLP                                                                                         |
| Electrical circuit type   | Control circuit                                                                              |
| Pressure sensor size      | 6 bar                                                                                        |
| Local display             | Without                                                                                      |
| Controlled fluid          | Fresh water 0...125 °C<br>Air -15...125 °C<br>Gas -15...125 °C<br>Hydraulic oil -15...125 °C |
| Fluid connection type     | G 1/4A (male) conforming to DIN 3852-E                                                       |
| Electrical connection     | 1 male connector M12 4 pins                                                                  |
| [Us] rated supply voltage | 24 V DC SELV, voltage limits: 12...33 V                                                      |
| Current consumption       | < 7 mA                                                                                       |
| Type of output signal     | Analogue                                                                                     |
| Analogue output function  | 0...10 V, 3-wire                                                                             |
| Quantity per set          | Set of 1                                                                                     |
| Type of packing           | Individual                                                                                   |

## Complementary

|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pressure setting range                  | 0...6 bar                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Maximum permissible accidental pressure | 18 bar                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Destruction pressure                    | 24 bar                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Materials in contact with fluid         | Stainless steel AISI 316L<br>Ceramic<br>Fluorocarbon FPM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Operating position                      | Any position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Protection type                         | Load short-circuit<br>Reverse polarity                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Electromagnetic compatibility           | 1.2/50 µs shock waves immunity test conforming to EN/IEC 61000-4-5 - test level 1 kV (f = 42 Ohm)<br>Immunity to magnetic fields conforming to EN/IEC 61000-4-8 - test level 100 A/m (f = 50 Hz)<br>Susceptibility to electromagnetic fields conforming to EN/IEC 61000-4-3 - test level 10 V/m (f = 80...1000 MHz)<br>Electrical fast transient/burst immunity test conforming to EN/IEC 61000-4-4 - test level 2 kV<br>Radiated RF fields conforming to EN/IEC 61000-4-6 - test level 10 V (f = 0.15...80 MHz)<br>Electrostatic discharge immunity test conforming to EN/IEC 61000-4-2 - test level 8 kV air, 4 kV contact |
| [Uimp] rated impulse withstand voltage  | 0.5 kV                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Response time on output                 | <= 2 ms for 10...90 % of full scale                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Measurement accuracy                    | +/- 0.5 % of the measuring range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Accuracy                                | 0.1 % of the measuring range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Drift of the sensitivity                | +/- 0.02 % of measuring range/°K                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Drift of the zero point                 | +/- 0.02 % of measuring range/°K                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Repeat accuracy                         | +/- 0.25 % of the measuring range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

|                       |                    |
|-----------------------|--------------------|
| Mechanical durability | >= 10000000 cycles |
| Product weight        | 0.075 kg           |
| Diameter              | 26 mm              |
| Length                | 32.3 mm            |

## Environment

|                                       |                                                                                                     |
|---------------------------------------|-----------------------------------------------------------------------------------------------------|
| Standards                             | EN/IEC 61326-2-3<br>NSF ANSI 61                                                                     |
| Product certifications                | EAC<br>CE<br>CULus<br>RCM                                                                           |
| Ambient air temperature for operation | -30...85 °C                                                                                         |
| Ambient air temperature for storage   | -50...100 °C                                                                                        |
| Vibration resistance                  | 20 gn (f = 10...2000 Hz) conforming to EN/IEC 60068-2-6                                             |
| Shock resistance                      | 100 gn for 11 ms conforming to EN/IEC 60068-2-27                                                    |
| IP degree of protection               | IP65 conforming to EN/IEC 60529<br>IP67 conforming to EN/IEC 60529<br>IP69K conforming to DIN 40050 |

## Offer Sustainability

|                                  |                                                                                                                                    |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                                                              |
| RoHS (date code: YYWW)           | Compliant - since 1541 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                                                                  |
| Product environmental profile    | Available <a href="#">Product Environmental</a>                                                                                    |
| Product end of life instructions | Need no specific recycling operations                                                                                              |

## Dimensions



(1) SW24 tightening torque  $\leq 25$  N.m / 221 lb-in


---

## Connection and Schema

---

### Wiring Diagram

3-Wire Technique (0-10 V)



(a) V out

---

Performance Curves

---

Curves

