

Signal towers



KL70-401B

1SFC151507F001



KL70-401Y

1SFC151508F001



KA4-102...

1SFC151509F001

6

Description

Colors	Red	Green	Yellow	Blue	Clear
Replace ☒ in type with	R	G	Y	L	C
Replace ☐ in order code with	1	2	3	4	8

Description	Type	Order code	Pkg qty	Weight (1pce) Kg
-------------	------	------------	---------	------------------

Light element

Available in red, green, yellow, blue and clear

Permanent light, 12-240 V AC/DC For bulb BA 15d.				
Bulb not included	KL70-401■	1SFA616070R401□	1	0.09
Blinking light, 24 V AC/DC with integrated LED	KL70-306■	1SFA616070R306□	1	0.10
Flashing light, 24 V AC/DC with integrated xenon tube	KL70-203■	1SFA616070R203□	1	0.12
Blinking light, 115 V AC with integrated LED	KL70-342■	1SFA616070R342□	1	0.10
Flashing light, 115 V AC with integrated xenon tube	KL70-113■	1SFA616070R113□	1	0.11
Blinking light, 230 V AC with integrated LED	KL70-352■	1SFA616070R352□	1	0.10
Flashing light, 230 V AC with integrated xenon tube	KL70-123■	1SFA616070R123□	1	0.11
LED permanent light, 24 V AC/DC with integrated LED	KL70-305■	1SFA616070R305□	1	0.10
LED rotating light, 24 V AC/DC with integrated LED	KL70-307■	1SFA616070R307□	1	0.10

Bulbs: Bulb Ba 15d, 42mm, max 7 W for permanent or blinking light

24 V, 5 W, AC/DC	KA4-1021	1SFA616923R1028	10	0.009
115 V, 5 W, AC/DC	KA4-1118	1SFA616923R1118	10	0.009
230 V, 5 W, AC/DC	KA4-1148	1SFA616923R1148	10	0.009

LED bulbs Ba 15d, 40mA

Available in red, green, yellow, blue and white

24 V AC/DC	KA4-102■	1SFA616924R102□	1	0.009
------------	----------	-----------------	---	-------

Audible modules buzzer element. 85 dB, continuous or pulsating tone, adjustable

24 V AC/DC	KB70-3001	1SFA616071R3001	1	0.11
115 V AC	KB70-3101	1SFA616071R3101	1	0.11
230 V AC	KB70-1201	1SFA616071R1201	1	0.12



Signal towers



KT70-10...

1SFC151510F0001



KA70-1001

1SFC151511F0001



KA70-1034

1SFC151512F0001

Description	Type	Order code		Pkg qty	Weight (1 pce) Kg
Siren element					
Multi function, 8 diff. Tones adjustable, volume adjustable 100 dB, 115 V AC	KS70-1104	1SFA616073R1104		1	0.13
Multi function, 8 diff. Tones adjustable, volume adjustable 100 dB, 230 V AC	KS70-1204	1SFA616073R1204		1	0.12
Multi function, 7 diff. Tones adjustable, volume adjustable, 100 dB, 24 V DC	KS70-2004	1SFA616073R2004		1	0.12
Multi function, 8 diff. Tones adjustable, volume adjustable 100 dB, 24 V AC/DC	KS70-3004	1SFA616073R3004		1	0.12
Continuous tone alternating 108 dB, 24 V DC	KS70-2002	1SFA616073R2002		1	0.15
Terminal elements					
For tube mounting, including cap	KT70-1001	1SFA616075R1001		1	0.15
For bracket or base, including cap	KT70-1002	1SFA616075R1002		1	0.15
Special parts					
Contact box					
Cable exit at side	KA70-1001	1SFA616077R1001		1	0.07
Magnetic base	KA70-1002	1SFA616077R1002		1	0.07
Base with tube					
D=25 mm L=110 mm	KA70-1011	1SFA616077R1011		1	0.06
Base for tube					
D=25 mm, plastic	KA70-1012	1SFA616077R1012		1	0.03
D=25 mm, metal	KA70-1013	1SFA616077R1013		1	0.32
Tube, anodized aluminum					
D=25 mm L=250 mm	KA70-1021	1SFA616077R1021		1	0.08
D=25 mm L=400 mm	KA70-1022	1SFA616077R1022		1	0.12
D=25 mm L=800 mm	KA70-1023	1SFA616077R1023		1	0.24
Bracket					
1-sided mounting	KA70-1031	1SFA616077R1031		1	0.07
2-sided mounting	KA70-1032	1SFA616077R1032		1	0.07
For tube mounting	KA70-1033	1SFA616077R1033		1	0.07
For surface mounting	KA70-1034	1SFA616077R1034		1	0.07