




Description: USB 2.0 A Plug to B Plug
Part No: 30-3007-XX


DRAWING NO.
30-3007-XX-CUST

REVISIONS

01	OFFICIAL RELEASE					
	12-19-12	G Z	M W	M L		ECO-12-0335



Part No.	Cable length
30-3007-3	3 ft.
30-3007-6	6 ft.
30-3007-10	10 ft.
30-3007-15	15 ft.



DIM OUTLINE

PIN ASSIGNMENT

P1	P2
1	1 RED 24#
2	2 WHITE
3	3 GREEN
4	4 BLACK 24#
SHIELD	SHIELD+BRAID

Cable Assembly Parts List			
ITEM	MATERIAL /SPECIFICATION	QTY	UNIT
1	USB A MALE 2.0, GOLD PLATING 30u" ON CONTACT WHITE INSULATOR, SHORT A PIERCE TYPE	1	PCS
2	USB B MALE 2.0, GOLD PLATING 30u" ON CONTACT WHITE INSULATOR, SHORT A PIERCE TYPE	1	PCS
3	USB 2.0,Cable UL Style one twisted pair 28 AWG,and 2C 24 AWG,BRAID SHIELDED WITH DRAIN WIRE, OD 4.5mm, JACKET GRAY-WHITE	L-25	mm
4	MOLDED PVC GRAY-WHITE		PCS
5	MOLDED PVC GRAY-WHITE		PCS

TOLERANCE UNLESS OTHERWISE SPECIFIED		DRAWN BY GARY.ZHG	DATE 12-19-12
DECIMALS	mm	CHECKED BY MONICA.W	DATE 12-19-12
X.X	± 0.2	APPROVED BY MA LIN	DATE 12-19-12
X.XX	± 0.1		
X.XXX	± 0.08		
ANGLES	± 0.5°	U/M	mm

THIS DRAWING WAS PRODUCED BY COMPUTER,
DO NOT SCALE DRAWING OR UPDATE MANUALLY.

 Connectivity Solutions		
TITLE USB 2.0 A Plug to B Plug		
SHEET 1 OF 1	DRAWING NO. 30-3007-XX-CUST	SIZE A