

Product data sheet

Characteristics

70-379-1

Socket, Legacy general purpose relay
accessory, 4PDT, 5A, 120 V, 14 pins, pins for
printed circuit board, 782H/792 S



Main

Product Range	Legacy
Product Type	Socket
Product Compatibility	Relay 792XDX Relay 782XDXH
Number of Terminals	14
Switch Function	4PDT
Contact Composition	4 NO + 4 NC

Complementary

Rated Current	5 A
Rated voltage	120 V
Contact Terminal Arrangement	Mixed
Connections Terminals	Pins for printed circuit board
Fixing Mode	By screws printed circuit boards
Product Weight	0.20 oz (5.8 g)
Width	0.65 in (16.6 mm)
Depth	1.00 in (25.40 mm)

Environment

Ambient Air Temperature for Storage	-40...221 °F (-40...105 °C)
Ambient Air Temperature for Operation	-40...131 °F (-40...55 °C)
Flame Retardance	UL94-V0
Product Certifications	UL CSA CE RoHS

Ordering and shipping details


GTIN	03606480277900
------	----------------

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Wiring Diagram



- (1) : N.C.
- (2) : N.O.
- (3) : COM
- (4) : Input
- (5) : Ground lug