

Panel Mount Solid State Relay

2 Channel AC Output

multicomp PRO

**RoHS
Compliant**



Description

The industrial 2 channel relay with SCR output is widely used in industry applications. The relay can be used for resistive, inductive or capacitive load. The load voltage is 24-530V AC, output current is rated at 25A and 50A.

Application

High-low Temperature Chamber, Plastics Machinery, Incubation Machine, Oiling Machine, HVAC, Elevator, Lighting, Fountain Controller.

Features

- Zero Crossing or Random-on
- Load Current: 25A and 50A @ 24-530V AC
- SCR Output
- DC Input
- IP20 Safety Cover Protection (Option)

Technical Specification

Input Circuit		
Control Voltage Range		4-15V DC
		15-32V DC
Must Turn-on Voltage		4V DC
		15V DC
Must Turn-off Voltage		1V DC
Maximum Input Current		50mA
		20mA
Output Circuit		
Load Voltage Range	240V AC	24-280V AC
	480V AC	24-530V AC
Maximum Turn-on Time	Random-on	1ms
	Zero Crossing	10ms
Maximum Turn-off Time		10ms
Maximum Surge Current [@10 ms]	25A	300A
	50A	500A
Maximum I ² t [@10 ms]	25A	450A ² s
	50A	1250A ² s
Transient Over voltage	240V AC	600Vpk
	480V AC	1200Vpk
Transient Over voltage	240V AC	600Vpk
	480V AC	1200Vpk

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO


Panel Mount Solid State Relay

2 Channel AC Output

multicomp PRO


Maximum Off-State Leakage Current [@ Rated Voltage]	5mA	
Maximum On-State Voltage Drop [@ Rated Current]	1.5Vrms	
Minimum Off-State dv/dt [@ Maximum Rated Voltage]	500V/μs	
General Information		
Dielectric Strength [50/60Hz]	Input/Output	4000Vrms
	Input, Output/Base	2500Vrms
Ambient Operating Temperature Range	-30°C to +80°C	
Ambient Storage Temperature Range	-30°C to +100°C	

Installation Drawing





Dimensions : Millimetres

Connection Drawing



Thermal Curve



Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 Element14.com/multicomp-pro

multicomp PRO

Panel Mount Solid State Relay

2 Channel AC Output

multicomp PRO

Part Number Table

Description	Part Number
SSR, Panel Mount, Screw, DPST-NO, 25A, 240V AC, 4-15V DC, Zero Crossing, IP20	MC002348
SSR, Panel Mount, Screw, DPST-NO, 25A, 480V AC, 4-15V DC, Zero Crossing, IP20	MC002349
SSR, Panel Mount, Screw, DPST-NO, 50A, 240V AC, 4-15V DC, Zero Crossing, IP20	MC002350
SSR, Panel Mount, Screw, DPST-NO, 50A, 240V AC, 4-15V DC, Random Turn on, IP20	MC002351
SSR, Panel Mount, Screw, DPST-NO, 25A, 480V AC, 15-32V DC, Zero Crossing, IP20	MC002352
SSR, Panel Mount, Screw, DPST-NO, 50A, 480V AC, 15-32V DC, Random Turn on, IP20	MC002353
SSR, Panel Mount, Screw, DPST-NO, 50A, 480V AC, 4-15V DC, Zero Crossing, IP20	MC002354

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO