

# 2N6284 (NPN); 2N6286, 2N6287 (PNP)

Preferred Device

## Darlington Complementary Silicon Power Transistors

These packages are designed for general-purpose amplifier and low-frequency switching applications.

### Features

- High DC Current Gain @  $I_C = 10 \text{ A dc}$  –  
 $h_{FE} = 2400 \text{ (Typ)} - 2N6284$   
 $= 4000 \text{ (Typ)} - 2N6287$
- Collector-Emitter Sustaining Voltage –  
 $V_{CEO(sus)} = 100 \text{ Vdc (Min)}$
- Monolithic Construction with Built-In Base-Emitter Shunt Resistors
- Pb-Free Packages are Available\*

### MAXIMUM RATINGS (Note 1)

| Rating                                                                                | Symbol         | Value        | Unit                     |
|---------------------------------------------------------------------------------------|----------------|--------------|--------------------------|
| Collector-Emitter Voltage<br>2N6286<br>2N6284/87                                      | $V_{CEO}$      | 80<br>100    | Vdc                      |
| Collector-Base Voltage<br>2N6286<br>2N6284/87                                         | $V_{CB}$       | 80<br>100    | Vdc                      |
| Emitter-Base Voltage                                                                  | $V_{EB}$       | 5.0          | Vdc                      |
| Collector Current – Continuous<br>Peak                                                | $I_C$          | 20<br>40     | Adc                      |
| Base Current                                                                          | $I_B$          | 0.5          | Adc                      |
| Total Power Dissipation @ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 160<br>0.915 | W<br>W/ $^\circ\text{C}$ |
| Operating and Storage Temperature<br>Range                                            | $T_J, T_{stg}$ | -65 to +200  | $^\circ\text{C}$         |

### THERMAL CHARACTERISTICS (Note 1)

| Characteristic                       | Symbol          | Max  | Unit               |
|--------------------------------------|-----------------|------|--------------------|
| Thermal Resistance, Junction-to-Case | $R_{\theta JC}$ | 1.09 | $^\circ\text{C/W}$ |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Indicates JEDEC Registered Data.



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.



ON Semiconductor®

<http://onsemi.com>

## 20 AMPERE COMPLEMENTARY SILICON POWER TRANSISTORS 100 VOLTS, 160 WATTS



TO-204AA (TO-3)  
CASE 1-07  
STYLE 1

### MARKING DIAGRAM



2N628x = Device Code  
x = 4, 6 or 7  
G = Pb-Free Package  
A = Location Code  
YY = Year  
WW = Work Week  
MEX = Country of Origin

### ORDERING INFORMATION

| Device  | Package           | Shipping       |
|---------|-------------------|----------------|
| 2N6284  | TO-3              | 100 Units/Tray |
| 2N6284G | TO-3<br>(Pb-Free) | 100 Units/Tray |
| 2N6286  | TO-3              | 100 Units/Tray |
| 2N6286G | TO-3<br>(Pb-Free) | 100 Units/Tray |
| 2N6287  | TO-3              | 100 Units/Tray |
| 2N6287G | TO-3<br>(Pb-Free) | 100 Units/Tray |

## 2N6284 (NPN); 2N6286, 2N6287 (PNP)




Figure 1. Power Derating

### ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C unless otherwise noted) (Note 2)

| Characteristic                                                                                                                                                                                               | Symbol                | Min        | Max         | Unit |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------------|-------------|------|
| <b>OFF CHARACTERISTICS</b>                                                                                                                                                                                   |                       |            |             |      |
| Collector-Emitter Sustaining Voltage<br>(I <sub>C</sub> = 0.1 Adc, I <sub>B</sub> = 0)                                                                                                                       | V <sub>CEO(sus)</sub> | 80<br>100  | –<br>–      | Vdc  |
| Collector Cutoff Current<br>(V <sub>CE</sub> = 40 Vdc, I <sub>B</sub> = 0)<br>(V <sub>CE</sub> = 50 Vdc, I <sub>B</sub> = 0)                                                                                 | I <sub>CEO</sub>      | –<br>–     | 1.0<br>1.0  | mAdc |
| Collector Cutoff Current<br>(V <sub>CE</sub> = Rated V <sub>CB</sub> , V <sub>BE(off)</sub> = 1.5 Vdc)<br>(V <sub>CE</sub> = Rated V <sub>CB</sub> , V <sub>BE(off)</sub> = 1.5 Vdc, T <sub>C</sub> = 150°C) | I <sub>CEX</sub>      | –<br>–     | 0.5<br>5.0  | mAdc |
| Emitter Cutoff Current<br>(V <sub>BE</sub> = 5.0 Vdc, I <sub>C</sub> = 0)                                                                                                                                    | I <sub>EBO</sub>      | –          | 2.0         | mAdc |
| <b>ON CHARACTERISTICS</b> (Note 3)                                                                                                                                                                           |                       |            |             |      |
| DC Current Gain<br>(I <sub>C</sub> = 10 Adc, V <sub>CE</sub> = 3.0 Vdc)<br>(I <sub>C</sub> = 20 Adc, V <sub>CE</sub> = 3.0 Vdc)                                                                              | h <sub>FE</sub>       | 750<br>100 | 18,000<br>– | –    |
| Collector-Emitter Saturation Voltage<br>(I <sub>C</sub> = 10 Adc, I <sub>B</sub> = 40 mAdc)<br>(I <sub>C</sub> = 20 Adc, I <sub>B</sub> = 200 mAdc)                                                          | V <sub>CE(sat)</sub>  | –<br>–     | 2.0<br>3.0  | Vdc  |
| Base-Emitter On Voltage<br>(I <sub>C</sub> = 10 Adc, V <sub>CE</sub> = 3.0 Vdc)                                                                                                                              | V <sub>BE(on)</sub>   | –          | 2.8         | Vdc  |
| Base-Emitter Saturation Voltage<br>(I <sub>C</sub> = 20 Adc, I <sub>B</sub> = 200 mAdc)                                                                                                                      | V <sub>BE(sat)</sub>  | –          | 4.0         | Vdc  |
| <b>DYNAMIC CHARACTERISTICS</b>                                                                                                                                                                               |                       |            |             |      |
| Magnitude of Common Emitter Small-Signal Short-Circuit<br>Forward Current Transfer Ratio<br>(I <sub>C</sub> = 10 Adc, V <sub>CE</sub> = 3.0 Vdc, f = 1.0 MHz)                                                | h <sub>fe</sub>       | 4.0        | –           | MHz  |
| Output Capacitance<br>(V <sub>CB</sub> = 10 Vdc, I <sub>E</sub> = 0, f = 0.1 MHz)                                                                                                                            | C <sub>ob</sub>       | –<br>–     | 400<br>600  | pF   |
| Small-Signal Current Gain<br>(I <sub>C</sub> = 10 Adc, V <sub>CE</sub> = 3.0 Vdc, f = 1.0 kHz)                                                                                                               | h <sub>fe</sub>       | 300        | –           | –    |

2. Indicates JEDEC Registered Data.

3. Pulse test: Pulse Width = 300 μs, Duty Cycle = 2%

## 2N6284 (NPN); 2N6286, 2N6287 (PNP)




Figure 2. Switching Times Test Circuit




Figure 3. Switching Times




Figure 4. Thermal Response

## 2N6284 (NPN); 2N6286, 2N6287 (PNP)

### ACTIVE-REGION SAFE OPERATING AREA




Figure 5. 2N6284, 2N6287

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate  $I_C - V_{CE}$  limits of the transistor that must be observed for reliable operation; i.e. the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 5 is based on  $T_{J(pk)} = 200^\circ\text{C}$ ;  $T_C$  is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided  $T_{J(pk)} < 200^\circ\text{C}$ .  $T_{J(pk)}$  may be calculated from the data in Figure 4. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.




Figure 6. Small-Signal Current Gain






Figure 7. Capacitance

## 2N6284 (NPN); 2N6286, 2N6287 (PNP)



**NPN  
2N6284**





**PNP  
2N6287**



**Figure 8. DC Current Gain**



**Figure 9. Collector Saturation Region**



**Figure 10. "On" Voltages**

## 2N6284 (NPN); 2N6286, 2N6287 (PNP)




Figure 11. Temperature Coefficients




Figure 12. Collector Cut-Off Region





Figure 13. Darlington Schematic

# 2N6284 (NPN); 2N6286, 2N6287 (PNP)

## PACKAGE DIMENSIONS

TO-204 (TO-3)  
CASE 1-07  
ISSUE Z



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. ALL RULES AND NOTES ASSOCIATED WITH REFERENCED TO-204AA OUTLINE SHALL APPLY.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 1.550 REF |       | 39.37 REF   |       |
| B   | ---       | 1.050 | ---         | 26.67 |
| C   | 0.250     | 0.335 | 6.35        | 8.51  |
| D   | 0.038     | 0.043 | 0.97        | 1.09  |
| E   | 0.055     | 0.070 | 1.40        | 1.77  |
| G   | 0.430 BSC |       | 10.92 BSC   |       |
| H   | 0.215 BSC |       | 5.46 BSC    |       |
| K   | 0.440     | 0.480 | 11.18       | 12.19 |
| L   | 0.665 BSC |       | 16.89 BSC   |       |
| N   | ---       | 0.830 | ---         | 21.08 |
| Q   | 0.151     | 0.165 | 3.84        | 4.19  |
| U   | 1.187 BSC |       | 30.15 BSC   |       |
| V   | 0.131     | 0.188 | 3.33        | 4.77  |

### STYLE 1:

- PIN 1. BASE
  - EMITTER
- CASE: COLLECTOR

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5773-3850

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative