XUKT1KSMM12

photo-electric sensor - XUKT - reflex - Sn 1.5m - 12..24VDC - M12





Main

Range of product	OsiSense XU
Series name	Application packaging
Electronic sensor type	Photo-electric sensor
Sensor name	XUK
Sensor design	Compact 50 x 50
Detection system	Reflex
Material	Plastic
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	3-wire
Discrete output type	PNP or NPN
Discrete output function	1 NO or 1 NC programmable
Electrical connection	1 male connector M12 adjustable 2 positions, 4 pins
Product specific application	Detection of transparent object
Emission	Red reflex
[Sn] nominal sensing distance	4.92 ft (1.5 m) reflex need reflector XUZC50

Complementary

Complementary	
Enclosure material	PC
Lens material	PMMA
Output type	Solid state
Output function governance	Dark
Add on output	Without
Cable composition	2 x 0.34 mm²
Wire insulation material	PVC
Cable outer diameter	0.24 in (6 mm)
Status LED	1 LEDoutput state
[Us] rated supply voltage	1224 V DC reverse polarity protection
Supply voltage limits	1030 V AC/DC
Switching capacity in mA	<= 100 mA overload and short-circuit protection)
Switching frequency	<= 1.5 kHz
Maximum voltage drop	<2 V closed state)
Current consumption	<= 35 mA no-load
Time delay range	0.15 s monostable, on-delay or off-delay (programmable)
Maximum delay first up	80 ms
Maximum delay response	0.3 ms
Maximum delay recovery	0.3 ms
Setting-up	Sensitivity adjustment by potentiometer
Depth	1.97 in (50 mm)
Height	1.97 in (50 mm)
Maximum Width	0.71 in (18 mm)
Net Weight	0.08 lb(US) (0.035 kg)
Kit composition	Bracket XULZ41
	Sensor

Environment

Product certifications	UL CSA CE	
Ambient air temperature for operation	-13131 °F (-2555 °C)	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Vibration resistance	7 gn +/- 2 mm 1055 Hz) IEC 60068-2-6	
Shock resistance	20 gn 11 ms) IEC 60068-2-27	
IP degree of protection	IP65 IEC 60529 IP651 NF C 20-010	

Ordering and shipping details

Discount Schedule DS2 GTIN 00785901613664 Nbr. of units in pkg. 1 Package weight(Lbs) 0.32 lb(US) (0.15 kg) Returnability No	
Nbr. of units in pkg. 1 Package weight(Lbs) 0.32 lb(US) (0.15 kg)	
Package weight(Lbs) 0.32 lb(US) (0.15 kg)	
Returnability No	
Country of origin ID	

Packing Units

Package 1 Height	1.080 dm	
Package 1 width	0.900 dm	
Package 1 Length	0.370 dm	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information

Contractual warranty


Warranty	18 months

Product data sheet Dimensions Drawings


XUKT1KSMM12

Dimensions

- With cover open
- · Fixing bracket mounting according to position of connector




Bracket Fixing



- (2) 1 elongated hole Ø 6 x 12
- (3) 1 elongated hole Ø 6 x 13

Wiring Schemes

Connector Scheme




2: Alarm output

3:

(-) Output signal

NC Programmed

PNP programmed output




NPN programmed output




NO Programmed

PNP programmed output




NPN programmed output



Alarm Output

NPN programmed



PNP programmed

