XS2M12PC410D

inductive sensor XS2 - cylindrical M12 - 12..24VDC





Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Sensor name	XS2
Sensor design	Cylindrical M12
Size	66 mm
Body type	Fixed
Detector flush mounting acceptance	Non flush mountable
Material	Metal
Type of output signal	Discrete
Wiring technique	4-wire
Discrete output function	1 NO + 1 NC
Output circuit type	DC
Discrete output type	PNP
Electrical connection	Male connector M12, 4 pins
[Us] rated supply voltage	1224 V DC reverse polarity protection
Switching capacity in mA	<= 200 mA overload and short-circuit protection
IP degree of protection	IP68 double insulation conforming to IEC 60529

Complementary

Thread type	M12 x 1
Detection face	Frontal
Front material	PPS
Enclosure material	Nickel Plated Brass
Operating zone	0.000.13 in (03.2 mm)
Differential travel	115% of Sr
Status LED	Output state 1 LED yellow)
Supply voltage limits	1036 V DC
Maximum voltage drop	<2 V closed)
Current consumption	010 mA no-load
Maximum delay first up	5 ms
Marking	CE
Threaded length	1.65 in (42 mm)
Length	2.60 in (66 mm)

Environment

Product certifications	UL CSA	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Ambient air temperature for storage	-40185 °F (-4085 °C)	
Vibration resistance	25 gn +/- 2 mm 1055 Hz)IEC 60068-2-6	
Shock resistance	50 gn 11 ms IEC 60068-2-27	

Ordering and shipping details

Category	22486 - SENSORS, PROXIMITY
Discount Schedule	DS2
GTIN	03389118318373
Nbr. of units in pkg.	1
Package weight(Lbs)	0.25 lb(US) (0.11 kg)
Returnability	No
Country of origin	FR

Packing Units

PCE
0.75 in (1.9 cm)
2.99 in (7.6 cm)
4.61 in (11.7 cm)
BAG
1
1.52 oz (43 g)
0.47 in (1.2 cm)
7.87 in (20 cm)
5.91 in (15 cm)
S01
22
35.11 oz (995.333 g)
5.91 in (15 cm)
5.91 in (15 cm)
15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information