Please download the latest datasheet of DLW32SH510XK2#from the official website of Murata Manufacturing

Co., Ltd

https://www.murata.com/en-global/products/productdetail?partno=DLW32SH510XK2%23

DLW32SH510XK2#

"#" indicates a package specification code.

Note: This datasheet may be out of date










< List of part numbers with package codes > DLW32SH510XK2B DLW32SH510XK2L



Appearance & Shape







Features

DLW32S series is a high performance wound type chip common mode choke coil.

Features

- 1. Suitable for noise suppression at car area networks like CAN (Controller Area Network) bus.
- DLW32S has high common mode impedance so it is suitable for noise suppression through wide frequency range.
- 3. Wide operating temperature range (-40 to +125 degrees C)

Applications

Noise suppression at car area networks like CAN bus or car navigation system.



Automotive
Usage

Powertrain/Safety



Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	500
L	180mm Embossed Tape	1500

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/05/21



Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=DLW32SH510XK2%23

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ DLW32SH510XK2\# from \ the \ of ficial \ website \ of \ Murata \ Manufacturing} }$

DLW32SH510XK2#

"#" indicates a package specification code.

Note: This datasheet may be out of date



Shape	SMD
Size Code (in mm)	3225
Size Code (in inch)	1210
Length	3.2mm
Length Tolerance	±0.2mm
Width	2.5mm
Width Tolerance	±0.2mm
Thickness	2.35mm
Thickness Tolerance	±0.15mm
Rated Current	200mA
Rated Voltage	80Vdc
Withstanding Voltage	200Vdc
DC Resistance(max.)	0.7Ω
DC Resistance	0.7Ω max.
Insulation Resistance(min.)	10ΜΩ
Operating Temperature Range	-40°C to 125°C
Mass(typ.)	0.072g

Number of Circuit	1
Common Mode Inductance	51μH-30%/+50% (at 0.1MHz)
Operating Temperature Range(Self- temperature rise is included)	No

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/05/21


^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


https://www.murata.com/en-global/products/productdetail?partno=DLW32SH510XK2%23

DLW32SH510XK2#

"#" indicates a package specification code.








Impedance-Frequency Characteristics

Impedance-Frequency Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/05/21