



Main

Range	TeSys
Product name	TeSys LE
Device short name	LE1D
Product or component type	Enclosed DOL starter
Device application	Standard
Utilisation category	AC-3
Device composition	Thermal overload relay to be ordered separately Contactor
Control type	Without

Complementary

[Ie] rated operational current	65 A AC-3
Motor power kW	30 kW at 380/400 V AC 50/60 Hz 37 kW at 415 V AC 50/60 Hz 37 kW at 440 V AC 50/60 Hz 37 kW at 500 V AC 50/60 Hz 37 kW at 660/690 V AC 50/60 Hz 18.5 kW at 220/230 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	65 A
[Uc] control circuit voltage	230 V AC 50/60 Hz
Cable entry number	1 cable entry : ISO32 top 3 cable entry : 1 ISO20 + 2 ISO32 bottom
Width	200 mm
Height	300 mm
Depth	150 mm
Product weight	4.85 kg
Compatibility code	LE1D

Environment

Material	Sheet steel
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to IEC 60529

Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

Offer Sustainability

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
-------	--