



# OMNIMATE Signal - series BL/SL 5.08 BLT 5.08HC/08/180F SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



Female plugs with TOP screw connection system for connecting wires with straight outlet direction and screw flange. The female connectors provide space for labelling and can be coded. HC = High Current.

## General ordering data

|              |                                                                                                                         |
|--------------|-------------------------------------------------------------------------------------------------------------------------|
| Type         | BLT 5.08HC/08/180F SN OR BX                                                                                             |
| Order No.    | <a href="#">1844050000</a>                                                                                              |
| Version      | PCB plug-in connector, female plug, 5.08 mm, No. of poles: 8, 180°, TOP connection, Clamping range, max. : 2.5 mm², Box |
| GTIN (EAN)   | 4032248355976                                                                                                           |
| Qty.         | 36 pc(s).                                                                                                               |
| Product data | IEC: 400 V / 27 A / 0.2 - 2.5 mm²<br>UL: 300 V / 17 A / AWG 26 - AWG 14                                                 |
| Packaging    | Box                                                                                                                     |

## OMNIMATE Signal - series BL/SL 5.08 BLT 5.08HC/08/180F SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

### Technical data

#### Dimensions and weights

|            |        |
|------------|--------|
| Net weight | 25.4 g |
|------------|--------|

#### System parameters

|                                              |                                     |                                          |                     |
|----------------------------------------------|-------------------------------------|------------------------------------------|---------------------|
| Product family                               | OMNIMATE Signal - series BL/SL 5.08 | Type of connection                       | TOP connection      |
| Wire connection method                       | TOP connection                      | Pitch in mm (P)                          | 5.08 mm             |
| Pitch in inches (P)                          | 0.2 inch                            | Conductor outlet direction               | 180°                |
| No. of poles                                 | 8                                   | L1 in mm                                 | 35.56 mm            |
| L1 in inches                                 | 1.4 inch                            | Number of rows                           | 1                   |
| Pin series quantity                          | 1                                   | Rated cross-section                      | 2.5 mm <sup>2</sup> |
| Touch-safe protection acc. to DIN VDE 57 106 | Safe from finger touch              | Volume resistance                        | 4.50 mΩ             |
| Can be coded                                 | Yes                                 | Stripping length                         | 13 mm               |
| Tightening torque for screw flange, min.     | 0.15 Nm                             | Tightening torque for screw flange, max. | 0.2 Nm              |
| Tightening torque, min.                      | 0.4 Nm                              | Tightening torque, max.                  | 0.5 Nm              |
| Clamping screw                               | M 2.5                               | Screwdriver blade                        | 0.6 x 3.5           |
| Screwdriver blade standard                   | DIN 5264                            | Plugging cycles                          | 25                  |
| push-in force/pole                           | 10 N                                | Withdrawal force per pole                | 8 N                 |
| Packaging                                    | Box                                 |                                          |                     |

#### Material data

|                                       |          |                                       |                          |
|---------------------------------------|----------|---------------------------------------|--------------------------|
| Insulating material                   | PBT      | Colour                                | Orange                   |
| Colour chart (similar)                | RAL 2000 | Insulating material group             | IIIa                     |
| CTI                                   | ≥ 200    | Insulation resistance                 | ≥ 10 <sup>8</sup> Ω      |
| UL 94 flammability rating             | V-0      | Contact material                      | CuSn                     |
| Contact surface                       | tinned   | Layer structure of plug contact       | 4-8 μm Sn hot-dip tinned |
| Storage temperature, min.             | -25 °C   | Storage temperature, max.             | 55 °C                    |
| Max. relative humidity during storage | 80 %     | Operating temperature, min.           | -50 °C                   |
| Operating temperature, max.           | 100 °C   | Temperature range, installation, min. | -25 °C                   |
| Temperature range, installation, max. | 100 °C   |                                       |                          |

#### Conductors suitable for connection

|                                                 |                          |                                                 |                     |
|-------------------------------------------------|--------------------------|-------------------------------------------------|---------------------|
| Clamping range, min.                            | 0.13 mm <sup>2</sup>     | Clamping range, max.                            | 2.5 mm <sup>2</sup> |
| Wire connection cross section AWG, min.         | AWG 28                   | Wire connection cross section AWG, max.         | AWG 14              |
| Solid, min. H05(07) V-U                         | 0.2 mm <sup>2</sup>      | Solid, max. H05(07) V-U                         | 2.5 mm <sup>2</sup> |
| Flexible, min. H05(07) V-K                      | 0.2 mm <sup>2</sup>      | Flexible, max. H05(07) V-K                      | 1.5 mm <sup>2</sup> |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.2 mm <sup>2</sup>      | w. plastic collar ferrule, DIN 46228 pt 4, max. | 1.5 mm <sup>2</sup> |
| w. wire end ferrule, DIN 46228 pt 1, min.       | 0.2 mm <sup>2</sup>      | w. wire end ferrule, DIN 46228 pt 1, max.       | 1.5 mm <sup>2</sup> |
| Plug gauge acc. to EN 60999 a x b; Ø            | 2.4 mm x 1.5 mm ; 2.4 mm |                                                 |                     |

**OMNIMATE Signal - series BL/SL 5.08**  
**BLT 5.08HC/08/180F SN OR BX**
**Weidmüller Interface GmbH & Co. KG**

 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Rated data acc. to IEC**

tested acc. to standard

IEC 60664-1, IEC 61984

 Rated current, max. no. of poles  
 (Tu=20°C)

19 A

 Rated current, max. no. of poles  
 (Tu=40°C)

16 A

 Rated voltage for surge voltage class /  
 pollution degree III/2

320 V

 Rated impulse voltage for surge voltage  
 class/ pollution degree II/2

4 kV

 Rated impulse voltage for surge voltage  
 class/ contamination degree III/3

4 kV

 Rated current, min. no. of poles  
 (Tu=20°C)

27 A

 Rated current, min. no. of poles  
 (Tu=40°C)

24 A

 Rated voltage for surge voltage class /  
 pollution degree II/2

400 V

 Rated voltage for surge voltage class /  
 pollution degree III/3

250 V

 Rated impulse voltage for surge voltage  
 class/ pollution degree III/2

4 kV

Short-time withstand current resistance

3 x 1s with 100 A

**Rated data acc. to CSA**

Rated voltage (Use group B)

300 V

Rated current (use group B)

15 A

Wire cross-section, AWG, min.

AWG 26

Rated voltage (use group D)

300 V

Rated current (use group D)

15 A

Wire cross-section, AWG, max.

AWG 14

**Rated data acc. to UL 1059**

Institute (cURus)



Certificate No. (cURus)

E60693

Rated voltage (use group B)

300 V

Rated current (use group B)

17 A

Wire cross-section, AWG, min.

AWG 26

Reference to approval values

 Specifications are  
 maximum values, details -  
 see approval certificate.

Rated voltage (use group D)

300 V

Rated current (use group D)

10 A

Wire cross-section, AWG, max.

AWG 14

**Classifications**

ETIM 3.0

EC001284

ETIM 5.0

EC002637

UNSPSC

30-21-18-10

eClass 6.2

27-26-07-04

eClass 8.1

27-44-04-02

eClass 9.1

27-44-04-02

ETIM 4.0

EC002637

ETIM 6.0

EC002637

eClass 5.1

27-26-07-04

eClass 7.1

27-44-04-02

eClass 9.0

27-44-04-02

## OMNIMATE Signal - series BL/SL 5.08 BLT 5.08HC/08/180F SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Technical data

### Notes

#### Notes

- Additional colours on request
- Gold-plated contact surfaces on request
- Rated current related to rated cross-section & min. No. of poles.
- Wire end ferrule without plastic collar to DIN 46228/1
- Wire end ferrule with plastic collar to DIN 46228/4
- Crimp form A for wire end ferrules with PZ 6/5 crimping tool are recommended for the largest cable sizes.
- P on drawing = pitch
- Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.

#### IPC conformity

Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.

### Approvals

#### Approvals



#### ROHS

Conform

### Downloads

#### Approval/Certificate/Document of Conformity

[Declaration of the Manufacturer](#)

#### Brochure/Catalogue

[FL DRIVES EN](#)  
[MB DEVICE MANUF. EN](#)  
[FL DRIVES DE](#)  
[CAT 2 PORTFOLIOGUIDE EN](#)  
[FL BUILDING SAFETY EN](#)  
[FL APPL LED LIGHTING EN](#)  
[FL INDUSTR.CONTROLS EN](#)  
[FL MACHINE SAFETY EN](#)  
[FL HEATING ELECTR EN](#)  
[FL APPL INVERTER EN](#)  
[FL BASE STATION EN](#)  
[FL ELEVATOR EN](#)  
[FL POWER SUPPLY EN](#)  
[FL 72H SAMPLE SER EN](#)  
[PO OMNIMATE EN](#)

#### Engineering Data


[WSCAD](#)

## OMNIMATE Signal - series BL/SL 5.08 BLT 5.08HC/08/180F SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

## Dimensional drawing



## Graph

BLT 5.08HC/./180 - SL-SMT 5.08HC/./90

