



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	11/29/17	J.LABOY



UL STYLE 20276,  
 (2) TWISTED PAIR, 30AWG WITH  
 ALUM/POLY FOIL SHIELD AND DRAIN WIRE,  
 (1) UNSHIELDED TWISTED PAIR, 30AWG,  
 (2) CONDUCTORS, 24AWG,  
 OVERALL ALUMINUM/MYLAR AND BRAIDED SHIELD,  
 JACKET: PVC, WHITE  
 (NOM DIA. .217" [5.5])

PART NUMBER	LENGTH METERS [FEET]
U3A00059-05M	0.5 [1.64]
U3A00059-075M	0.75 [2.46]
U3A00059-1M	1.0 [3.28]
U3A00059-105M	1.5 [4.92]

- NOTES:**
- CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
  - CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
  - CABLE ASSEMBLY MUST MEET USB 3.0 REQUIREMENTS.
  - CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

**REGULATORY COMPLIANCE:**  
 CE2011/65/EU(RoHS DIRECTIVE)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 [5.08] .XX = ±.02 [51] .XXX = ±.005 [1.27]	APPROVALS	DATE	50 HIGH STREET NORTH ANDOVER, MA 01845
	DRAWN BY S.LI	10/16/17	
PROJECTION 	CHECKED BY B.ZHANG	10/16/17	PRODUCT DESCRIPTION <b>CA, USB 3.0 TYPE A/A WHITE</b>
	APPROVED BY S.PAN	10/16/17	
COLOR VARIATIONS MAY OCCUR		SCALE: NONE    CAD FILE: U3A00059.SLDDRW    SHEET 1 OF 1	