

FDMS1D2N03DSD

POWERTRENCH® Power Clip 30 V Asymmetric Dual N-Channel MOSFETs

General Description

This device includes two specialized N-Channel MOSFETs in a dual package. The switch node has been internally connected to enable easy placement and routing of synchronous buck converters. The control MOSFET (Q1) and synchronous SyncFET™ (Q2) have been designed to provide optimal power efficiency.

Features

Q1: N-Channel

- Max $R_{DS(on)}$ = 3.25 m Ω at V_{GS} = 10 V, I_D = 19 A
- Max $R_{DS(on)}$ = 4 m Ω at V_{GS} = 4.5 V, I_D = 17 A

Q2: N-Channel

- Max $R_{DS(on)}$ = 0.97 m Ω at V_{GS} = 10 V, I_D = 37 A
- Max $R_{DS(on)}$ = 1.25 m Ω at V_{GS} = 4.5 V, I_D = 34 A
- Low Inductance Packaging Shortens Rise/Fall Times, Resulting in Lower Switching Losses.
- MOSFET Integration Enables Optimum Layout for Lower Circuit Inductance and Reduced Switch Node Ringing.
- RoHS Compliant

Applications


- Computing
- Communications
- General Purpose Point of Load




ON Semiconductor®

www.onsemi.com

ELECTRICAL CONNECTION




N-Channel MOSFET



Power Clip 56
(PQFN8 5x6)
CASE 483AR

PIN ASSIGNMENT



*PAD9 V+(HSD)

MARKING DIAGRAM



\$Y = ON Semiconductor Logo
&Z = Assembly Plant Code
&3 = Numeric Date Code
&K = Lot Code
FDMS1D2N03DSD = Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

FDMS1D2N03DSD

MOSFET MAXIMUM RATINGS (T_A = 25°C, Unless otherwise specified)

Symbol	Parameter	Q1	Q2	Unit
V _{DS}	Drain to Source Voltage	30	30	V
V _{GS}	Gate to Source Voltage	+16/-12	+16/-12	V
I _D	Drain Current – Continuous (T _C = 25°C) (Note 5)	70	164	A
	– Continuous (T _C = 85°C) (Note 5)	54	126	
	– Continuous (T _A = 25°C)	19 (Note 1a)	37 (Note 1b)	
	– Continuous (T _A = 85°C)	15 (Note 1a)	29 (Note 1b)	
	– Pulsed (T _A = 25°C) (Note 4)	362	1199	
E _{AS}	Single Pulsed Avalanche Energy (Note 3)	121	337	mJ
P _D	Power Dissipation for Single Operation (T _C = 25°C) (T _A = 25°C)	26 2.1 (Note 1a)	42 2.3 (Note 1b)	W
T _J , T _{STG}	Operating and Storage Junction Temperature Range	–55 to +150		°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Symbol	Parameter	Q1	Q2	Unit
R _{θJC}	Thermal Resistance, Junction to Case	4.8	3.0	°C/W
R _{θJA}	Thermal Resistance, Junction to Ambient	60 (Note 1a)	55 (Note 1b)	°C/W
R _{θJA}	Thermal Resistance, Junction to Ambient	130 (Note 1c)	120 (Note 1d)	°C/W

PACKAGE MARKING AND ORDERING INFORMATION

Device	Top Marking	Package	Reel Size	Tape Width	Quantity
FDMS1D2N03DSD	FDMS1D2N03DSD	Power Clip 56 (PGFN8) (Pb-Free / Halogen Free)	13"	12 mm	3,000 Units

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Unit
--------	-----------	-----------------	------	-----	-----	-----	------

OFF CHARACTERISTICS

BV _{DSS}	Drain to Source Breakdown Voltage	I _D = 1 mA, V _{GS} = 0 V	Q1 Q2	30 30	– –	– –	V
ΔBV _{DSS} /ΔT _J	Breakdown Voltage Temperature Coefficient	I _D = 10 mA, referenced to 25°C	Q1 Q2	– –	15 21	– –	mV/°C
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 24 V, V _{GS} = 0 V	Q1 Q2	– –	– –	1 500	μA
I _{GSS}	Gate to Source Leakage Current, Forward	V _{GS} = +16 V/-12 V, V _{DS} = 0 V	Q1 Q2	– –	– –	±100 ±100	nA nA

ON CHARACTERISTICS

V _{GS(th)}	Gate to Source Threshold Voltage	V _{GS} = V _{DS} , I _D = 320 μA V _{GS} = V _{DS} , I _D = 1 mA	Q1 Q2	0.8 1.0	1.3 1.5	2.5 3.0	V
ΔV _{GS(th)} /ΔT _J	Gate to Source Threshold Voltage Temperature Coefficient	I _D = 1 mA, referenced to 25°C I _D = 10 mA, referenced to 25°C	Q1 Q2	– –	–3 –3	– –	mV/°C

FDMS1D2N03DSD

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Unit
--------	-----------	-----------------	------	-----	-----	-----	------

ON CHARACTERISTICS

$R_{DS(on)}$	Drain to Source On Resistance	$V_{GS} = 10\text{ V}, I_D = 19\text{ A}$ $V_{GS} = 4.5\text{ V}, I_D = 17\text{ A}$ $V_{GS} = 10\text{ V}, I_D = 19\text{ A},$ $T_J = 125^\circ\text{C}$	Q1	–	2.5	3.25	m Ω
		$V_{GS} = 10\text{ V}, I_D = 37\text{ A}$ $V_{GS} = 4.5\text{ V}, I_D = 34\text{ A}$ $V_{GS} = 10\text{ V}, I_D = 37\text{ A},$ $T_J = 125^\circ\text{C}$	Q2	–	0.73	0.97	
g_{FS}	Forward Transconductance	$V_{DS} = 5\text{ V}, I_D = 19\text{ A}$	Q1	–	95	–	S
		$V_{DS} = 5\text{ V}, I_D = 37\text{ A}$	Q2	–	247	–	

DYNAMIC CHARACTERISTICS

C_{iss}	Input Capacitance	Q1: $V_{DS} = 15\text{ V}, V_{GS} = 0\text{ V},$ $f = 1\text{ MHz}$ Q2: $V_{DS} = 15\text{ V}, V_{GS} = 0\text{ V},$ $f = 1\text{ MHz}$	Q1	–	1410	–	pF
			Q2	–	4860	–	
C_{oss}	Output Capacitance		Q1	–	564	–	pF
			Q2	–	1845	–	
C_{rss}	Reverse Transfer Capacitance		Q1	–	40	–	pF
			Q2	–	123	–	
R_g	Gate Resistance		Q1	–	0.3	–	Ω
			Q2	–	0.3	–	

SWITCHING CHARACTERISTICS

$t_{d(on)}$	Turn-On Delay Time	Q1: $V_{DD} = 15\text{ V}, I_D = 19\text{ A},$ $R_{GEN} = 6\text{ }\Omega$ Q2: $V_{DD} = 15\text{ V}, I_D = 37\text{ A},$ $R_{GEN} = 6\text{ }\Omega$	Q1	–	8	–	ns
			Q2	–	13	–	
t_r	Rise Time		Q1	–	2	–	ns
			Q2	–	5	–	
$t_{d(off)}$	Turn-Off Delay Time		Q1	–	22	–	ns
			Q2	–	37	–	
t_f	Fall Time		Q1	–	2	–	ns
			Q2	–	4	–	
Q_g	Total Gate Charge	$V_{GS} = 0\text{ V to }10\text{ V}$ Q1: $V_{DD} = 15\text{ V}, I_D = 19\text{ A}$ Q2: $V_{DD} = 15\text{ V}, I_D = 37\text{ A}$	Q1	–	23	33	nC
			Q2	–	84	117	
Q_g	Total Gate Charge	$V_{GS} = 0\text{ V to }4.5\text{ V}$ Q1: $V_{DD} = 15\text{ V}, I_D = 19\text{ A}$ Q2: $V_{DD} = 15\text{ V}, I_D = 37\text{ A}$	Q1	–	11	15	nC
			Q2	–	39	54	
Q_{gs}	Gate to Source Gate Charge	Q1: $V_{DD} = 15\text{ V}, I_D = 19\text{ A}$ Q2: $V_{DD} = 15\text{ V}, I_D = 37\text{ A}$	Q1	–	3.1	–	nC
			Q2	–	13	–	
Q_{gd}	Gate to Drain “Miller” Charge	Q1: $V_{DD} = 15\text{ V}, I_D = 19\text{ A}$ Q2: $V_{DD} = 15\text{ V}, I_D = 37\text{ A}$	Q1	–	2.5	–	nC
			Q2	–	9	–	

SOURCE-DRAIN DIODE CHARACTERISTICS


V_{SD}	Source to Drain Diode Forward Voltage	$V_{GS} = 0\text{ V}, I_S = 19\text{ A}$ (Note 2) $V_{GS} = 0\text{ V}, I_S = 37\text{ A}$ (Note 2)	Q1	–	0.8	1.2	V
			Q2	–	0.8	1.2	
t_{rr}	Reverse Recovery Time	Q1: $I_F = 19\text{ A}, di/dt = 100\text{ A}/\mu\text{s}$	Q1	–	28	–	ns
			Q2	–	43	–	
Q_{rr}	Reverse Recovery Charge	Q2: $I_F = 37\text{ A}, di/dt = 300\text{ A}/\mu\text{s}$	Q1	–	12	–	nC
			Q2	–	63	–	

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.


FDMS1D2N03DSD

NOTES:


1. $R_{\theta JA}$ is determined with the device mounted on a 1 in² pad 2 oz copper pad on a 1.5 × 1.5 in. board of FR-4 material. $R_{\theta CA}$ is determined by the user's board design.



a) 60°C/W when mounted on a 1 in² pad of 2 oz copper.



b) 55°C/W when mounted on a 1 in² pad of 2 oz copper.



c) 130°C/W when mounted on a minimum pad of 2 oz copper.



d) 120°C/W when mounted on a minimum pad of 2 oz copper.

2. Pulse Test: Pulse Width < 300 μ s, Duty cycle < 2.0%.
3. Q1: E_{AS} of 121 mJ is based on starting $T_J = 25^\circ\text{C}$; N-ch: $L = 3\text{ mH}$, $I_{AS} = 9\text{ A}$, $V_{DD} = 30\text{ V}$. 100% tested at $L = 0.1\text{ mH}$, $I_{AS} = 29\text{ A}$.
Q2: E_{AS} of 337 mJ is based on starting $T_J = 25^\circ\text{C}$; N-ch: $L = 3\text{ mH}$, $I_{AS} = 15\text{ A}$, $V_{DD} = 30\text{ V}$. 100% tested at $L = 0.1\text{ mH}$, $I_{AS} = 47\text{ A}$.
4. Pulsed I_d please refer to Figure 11 and Figure 24 SOA graphs for more details.
5. Computed continuous current limited to Max Junction Temperature only, actual continuous current will be limited by thermal & electro-mechanical application board design.

TYPICAL CHARACTERISTICS (Q1 N-Channel)

($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 1. On-Region Characteristics




Figure 2. Normalized On-Resistance vs. Drain Current and Gate Voltage




Figure 3. Normalized On-Resistance vs. Junction Temperature




Figure 4. On-Resistance vs. Gate to Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Source to Drain Diode Forward Voltage vs. Source Current

FDMS1D2N03DSD

TYPICAL CHARACTERISTICS (Q1 N-Channel)

($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance vs. Drain to Source Voltage




Figure 9. Unclamped Inductive Switching Capability




Figure 10. Maximum Continuous Drain Current vs. Case Temperature




Figure 11. Forward Bias Safe Operating Area




Figure 12. Single Pulse Maximum Power Dissipation

FDMS1D2N03DSD

TYPICAL CHARACTERISTICS (Q1 N-Channel)

($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 13. Junction-to-Case Transient Thermal Response Curve

TYPICAL CHARACTERISTICS (Q2 N-Channel)

($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 14. On-Region Characteristics




Figure 15. Normalized On-Resistance vs. Drain Current and Gate Voltage




Figure 16. Normalized On-Resistance vs. Junction Temperature




Figure 17. On-Resistance vs. Gate to Source Voltage




Figure 18. Transfer Characteristics




Figure 19. Source to Drain Diode Forward Voltage vs. Source Current

FDMS1D2N03DSD

TYPICAL CHARACTERISTICS (Q2 N-Channel)

($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 20. Gate Charge Characteristics




Figure 21. Capacitance vs. Drain to Source Voltage




Figure 22. Unclamped Inductive Switching Capability




Figure 23. Maximum Continuous Drain Current vs. Case Temperature




Figure 24. Forward Bias Safe Operating Area




Figure 25. Single Pulse Maximum Power Dissipation

FDMS1D2N03DSD

TYPICAL CHARACTERISTICS (Q2 N-Channel)

($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 26. Junction-to-Case Transient Thermal Response Curve

FDMS1D2N03DSD

TYPICAL CHARACTERISTICS (continued)

SyncFET Schottky Body Diode Characteristics

ON's SyncFET process embeds a Schottky diode in parallel with PowerTrench MOSFET. This diode exhibits similar characteristics to a discrete external Schottky diode in parallel with a MOSFET. Figure 27 shows the reverse recovery characteristic of the FDMS1D2N03DSD.




Figure 27. FDMS1D2N03DSD SyncFET Body Diode Reverse Recovery Characteristic

Schottky barrier diodes exhibit significant leakage at high temperature and high reverse voltage. This will increase the power in the device.







Figure 28. SyncFET Body Diode Reverse Leakage vs. Drain-Source Voltage

PQFN8 5X6, 1.27P
CASE 483AR
ISSUE O

DATE 30 SEP 2016



NOTES: UNLESS OTHERWISE SPECIFIED

- A) DOES NOT FULLY CONFORM TO JEDEC REGISTRATION, MO-229, DATED 11/2001.
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH. MOLD FLASH OR BURRS DOES NOT EXCEED 0.10MM.
- D) DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.

DOCUMENT NUMBER:	98AON13666G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
STATUS:	ON SEMICONDUCTOR STANDARD	
NEW STANDARD:		
DESCRIPTION:	PQFN8 5X6, 1.27P	PAGE 1 OF 2

[illegible]

ON Semiconductor and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative