


## Fast Soft Recovery Rectifier Diode, 10 A



2L TO-220AC



### FEATURES

- Glass passivated pellet chip junction
- Meets JESD 201 class 1A whisker test
- Flexible solution for reliable AC power rectification
- High surge, low  $V_F$  rugged blocking diode for DC charging stations
- AEC-Q101 qualified
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

### APPLICATIONS

- On-board and off-board EV/HEV battery chargers
- Input rectification

### DESCRIPTION

The VS-10ETF12THM3 fast soft recovery rectifier series has been optimized for combined short reverse recovery time and low forward voltage drop.

The glass passivation ensures stable reliable operation in the most severe temperature and power cycling conditions.

### PRIMARY CHARACTERISTICS

|                       |             |
|-----------------------|-------------|
| $I_{F(AV)}$           | 10 A        |
| $V_R$                 | 1200 V      |
| $V_F$ at $I_F$        | 1.33 V      |
| $I_{FSM}$             | 140 A       |
| $t_{rr}$              | 80 ns       |
| $T_J$ max.            | 150 °C      |
| Snap factor           | 0.6         |
| Package               | 2L TO-220AC |
| Circuit configuration | Single      |

### MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL      | CHARACTERISTICS     | VALUES      | UNITS |
|-------------|---------------------|-------------|-------|
| $V_{RRM}$   |                     | 1200        | V     |
| $I_{F(AV)}$ | Sinusoidal waveform | 10          | A     |
| $I_{FSM}$   |                     | 140         |       |
| $t_{rr}$    | 1 A, 100 A/μs       | 80          | ns    |
| $V_F$       | 10 A, $T_J = 25$ °C | 1.33        | V     |
| $T_J$       |                     | -40 to +150 | °C    |

### VOLTAGE RATINGS

| PART NUMBER    | $V_{RRM}$ , MAXIMUM PEAK REVERSE VOLTAGE<br>V | $V_{RSM}$ , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE<br>V | $I_{RRM}$ AT 150 °C<br>mA |
|----------------|-----------------------------------------------|--------------------------------------------------------------|---------------------------|
| VS-10ETF12THM3 | 1200                                          | 1300                                                         | 4                         |

### ABSOLUTE MAXIMUM RATINGS


| PARAMETER                                           | SYMBOL        | TEST CONDITIONS                                | VALUES | UNITS             |
|-----------------------------------------------------|---------------|------------------------------------------------|--------|-------------------|
| Maximum average forward current                     | $I_{F(AV)}$   | $T_C = 125$ °C, 180° conduction half sine wave | 10     | A                 |
| Maximum peak one cycle non-repetitive surge current | $I_{FSM}$     | 10 ms sine pulse, rated $V_{RRM}$ applied      | 115    |                   |
|                                                     |               | 10 ms sine pulse, no voltage reapplied         | 140    |                   |
| Maximum $I^2t$ for fusing                           | $I^2t$        | 10 ms sine pulse, rated $V_{RRM}$ applied      | 66     | A <sup>2</sup> s  |
|                                                     |               | 10 ms sine pulse, no voltage reapplied         | 94     |                   |
| Maximum $I^2\sqrt{t}$ for fusing                    | $I^2\sqrt{t}$ | $t = 0.1$ to 10 ms, no voltage reapplied       | 940    | A <sup>2</sup> √s |

**ELECTRICAL SPECIFICATIONS**

| PARAMETER                       | SYMBOL      | TEST CONDITIONS                          |                               | VALUES | UNITS            |
|---------------------------------|-------------|------------------------------------------|-------------------------------|--------|------------------|
| Maximum forward voltage drop    | $V_{FM}$    | 10 A, $T_J = 25\text{ }^{\circ}\text{C}$ |                               | 1.33   | V                |
| Forward slope resistance        | $r_t$       | $T_J = 150\text{ }^{\circ}\text{C}$      |                               | 22.9   | $\text{m}\Omega$ |
| Threshold voltage               | $V_{F(TO)}$ |                                          |                               | 0.96   | V                |
| Maximum reverse leakage current | $I_{RM}$    | $T_J = 25\text{ }^{\circ}\text{C}$       | $V_R = \text{Rated } V_{RRM}$ | 0.1    | mA               |
|                                 |             | $T_J = 150\text{ }^{\circ}\text{C}$      |                               | 4      |                  |

**RECOVERY CHARACTERISTICS**

| PARAMETER                | SYMBOL   | TEST CONDITIONS                                                             | VALUES | UNITS         |
|--------------------------|----------|-----------------------------------------------------------------------------|--------|---------------|
| Reverse recovery time    | $t_{rr}$ | $I_F$ at 10 A <sub>pk</sub><br>25 A/ $\mu\text{s}$<br>25 $^{\circ}\text{C}$ | 310    | ns            |
| Reverse recovery current | $I_{rr}$ |                                                                             | 4.7    | A             |
| Reverse recovery charge  | $Q_{rr}$ |                                                                             | 1.05   | $\mu\text{C}$ |
| Typical snap factor      | S        |                                                                             | 0.6    |               |

**THERMAL - MECHANICAL SPECIFICATIONS**

| PARAMETER                                      | SYMBOL                            | TEST CONDITIONS                      | VALUES      | UNITS                  |
|------------------------------------------------|-----------------------------------|--------------------------------------|-------------|------------------------|
| Maximum junction and storage temperature range | T <sub>J</sub> , T <sub>Stg</sub> |                                      | -40 to +150 | °C                     |
| Maximum thermal resistance junction to case    | R <sub>thJC</sub>                 | DC operation                         | 1.5         | °C/W                   |
| Maximum thermal resistance junction to ambient | R <sub>thJA</sub>                 |                                      | 62          |                        |
| Typical thermal resistance, case to heatsink   | R <sub>thCS</sub>                 | Mounting surface, smooth and greased | 0.5         |                        |
| Approximate weight                             |                                   |                                      | 2           | g                      |
|                                                |                                   |                                      | 0.07        | oz.                    |
| Mounting torque                                | minimum                           |                                      | 6 (5)       | kgf · cm<br>(lbf · in) |
|                                                | maximum                           |                                      | 12 (10)     |                        |
| Marking device                                 |                                   | Case style 2L TO-220AC               | 10ETF12TH   |                        |




Fig. 1 - Current Rating Characteristics




Fig. 2 - Current Rating Characteristics




Fig. 3 - Forward Power Loss Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 4 - Forward Power Loss Characteristics




Fig. 7 - Forward Voltage Drop Characteristics











Fig. 5 - Maximum Non-Repetitive Surge Current


Fig. 8 - Recovery Time Characteristics,  $T_J = 25\text{ }^{\circ}\text{C}$


Fig. 9 - Recovery Time Characteristics,  $T_J = 150\text{ }^{\circ}\text{C}$ 

Fig. 11 - Recovery Charge Characteristics,  $T_J = 150\text{ }^{\circ}\text{C}$ 

Fig. 10 - Recovery Charge Characteristics,  $T_J = 25\text{ }^{\circ}\text{C}$ 

Fig. 12 - Recovery Current Characteristics,  $T_J = 25\text{ }^{\circ}\text{C}$ 

Fig. 13 - Recovery Current Characteristics,  $T_J = 150\text{ }^{\circ}\text{C}$


Fig. 14 - Thermal Impedance  $Z_{thJC}$  Characteristics

### ORDERING INFORMATION TABLE

|             |            |           |          |          |          |           |          |          |           |
|-------------|------------|-----------|----------|----------|----------|-----------|----------|----------|-----------|
| Device code | <b>VS-</b> | <b>10</b> | <b>E</b> | <b>T</b> | <b>F</b> | <b>12</b> | <b>T</b> | <b>H</b> | <b>M3</b> |
|             | ①          | ②         | ③        | ④        | ⑤        | ⑥         | ⑦        | ⑧        | ⑨         |

- 1** - Vishay Semiconductors product
- 2** - Current rating (10 = 10 A)
- 3** - Circuit configuration:  
E = 2L TO-220AC
- 4** - Package:  
T = TO-220
- 5** - Type of silicon:  
F = fast soft recovery rectifier
- 6** - Voltage code x 100 =  $V_{RRM}$  ——— **12 = 1200 V**
- 7** -
  - None = TO-220AB
  - T = true pin TO-220
- 8** - H = AEC-Q101 qualified
- 9** - Environmental digit:  
M3 = halogen-free, RoHS-compliant, and terminations lead (Pb)-free


| ORDERING INFORMATION (Example) |                  |                        |                         |
|--------------------------------|------------------|------------------------|-------------------------|
| PREFERRED P/N                  | QUANTITY PER T/R | MINIMUM ORDER QUANTITY | PACKAGING DESCRIPTION   |
| VS-10ETF12THM3                 | 50               | 1000                   | Antistatic plastic tube |

| LINKS TO RELATED DOCUMENTS |                                                                        |
|----------------------------|------------------------------------------------------------------------|
| Dimensions                 | <a href="http://www.vishay.com/doc?96069">www.vishay.com/doc?96069</a> |
| Part marking information   | <a href="http://www.vishay.com/doc?95391">www.vishay.com/doc?95391</a> |



## 2L TO-220AC

DIMENSIONS in millimeters and inches



| SYMBOL | MILLIMETERS |       | INCHES |       | NOTES |
|--------|-------------|-------|--------|-------|-------|
|        | MIN.        | MAX.  | MIN.   | MAX.  |       |
| A      | 4.25        | 4.65  | 0.167  | 0.183 |       |
| A1     | 1.14        | 1.40  | 0.045  | 0.055 |       |
| A2     | 2.56        | 2.92  | 0.101  | 0.115 |       |
| b      | 0.69        | 1.01  | 0.027  | 0.040 |       |
| b1     | 0.38        | 0.97  | 0.015  | 0.038 | 4     |
| b2     | 1.20        | 1.73  | 0.047  | 0.068 |       |
| b3     | 1.14        | 1.73  | 0.045  | 0.068 | 4     |
| c      | 0.36        | 0.61  | 0.014  | 0.024 |       |
| c1     | 0.36        | 0.56  | 0.014  | 0.022 | 4     |
| D      | 14.85       | 15.25 | 0.585  | 0.600 | 3     |
| D1     | 8.38        | 9.02  | 0.330  | 0.355 |       |
| D2     | 11.68       | 12.88 | 0.460  | 0.507 | 6     |
| E      | 10.11       | 10.51 | 0.398  | 0.414 | 3, 6  |

| SYMBOL | MILLIMETERS |       | INCHES |       | NOTES |
|--------|-------------|-------|--------|-------|-------|
|        | MIN.        | MAX.  | MIN.   | MAX.  |       |
| E1     | 6.86        | 8.89  | 0.270  | 0.350 | 6     |
| E2     | -           | 0.76  | -      | 0.030 | 7     |
| e      | 2.41        | 2.67  | 0.095  | 0.105 |       |
| e1     | 4.88        | 5.28  | 0.192  | 0.208 |       |
| H1     | 6.09        | 6.48  | 0.240  | 0.255 | 6, 7  |
| L      | 13.52       | 14.02 | 0.532  | 0.552 |       |
| L1     | 3.32        | 3.82  | 0.131  | 0.150 | 2     |
| Ø P    | 3.54        | 3.73  | 0.139  | 0.147 |       |
| Q      | 2.60        | 3.00  | 0.102  | 0.118 |       |

## Notes

- Dimensioning and tolerancing as per ASME Y14.5M-1994
- Lead dimension and finish uncontrolled in L1
- Dimension D, D1 and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outermost extremes of the plastic body
- Dimension b1, b3 and c1 apply to base metal only
- Controlling dimension: inches
- Thermal pad contour optional within dimensions E, H1, D2 and E1
- Dimension E2 x H1 define a zone where stamping and singulation irregularities are allowed
- Outline conforms to JEDEC® TO-220, except D2, where JEDEC® minimum is 0.480".



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.