



Laird's unique patented Phantom[®] antenna is ideal for cell, GSM, PCE, WIFI, 802.11 and Bluetooth wireless applications. Measuring only 2.7" tall, the Phantom 800 MHz to 5.8 GHz antenna models' revolutionary design features a robust IP67 rated mechanical solution with frequency agility, low visibility, wide bandwidth and a low angle radiation pattern that is superior to traditional gain antennas in most applications, both outdoor and indoor.

The industry standard NMO mounting socket mates with all Laird Technologies' magnetic, trunk lid, and hole mounts. A threaded permanent stud mount model is also available for vandal resistant mounting on brackets, panels, ceilings or any other kind of housing.

The Phantom[®] patented technology is beneficial when high performance is desired and extreme ruggedness and low profile is required.

FEATURES AND BENEFITS

- A low profile mechanically robust high-power solution.
- Outperforms a 3-dB whip in many applications
- U.S. Patent Nos. 5,977,931 – 6,292,156 and 7,209,096

ELECTRICAL SPECIFICATIONS	
Operating Frequency (MHz)	806-870/821-896/890-960/902-928/1850-1990/2400-2500/4900-6000
VSWR	< 2.1
Gain (dBi)	3
Max Power - Ambient 25°C (W)	100
Nominal Impedance (Ohms)	50
Polarization	Vertical
Pattern	Omnidirectional
Half-Power Beamwidth (Elevation° x Azimuth°)	130 x 360


MECHANICAL SPECIFICATIONS	
Dimensions – diameter x height – mm (inches)	36.52 x 69.85 (1.438 x 2.75)
Weight – kg (lbs.)	0.078 (0.173)
Material	SABIC Lexan
Color	Black or White
Mounting Information	NMO (PN: MB8, MAB8) – Sold separately
Noise Suppressor	BlackHawk NS1535 1-35 VOLT, 15 Amp – Sold separately

CONFIGURATION


PART NUMBER	DESCRIPTION
TRA8063	806-870 MHz 3 dBi Phantom [®] ¾ NMO, White Radome
TRA8213	821-896 MHz 3 dBi Phantom [®] ¾ NMO, White Radome
TRA8903	890-960 MHz 3 dBi Phantom [®] ¾ NMO, White Radome
TRA9023	902-928 MHz 3 dBi Phantom [®] ¾ NMO, White Radome
TRA18503	1.85 - 1.99 GHz 3 dBi Phantom [®] ¾ NMO, White Radome
TRA24003	2.4 – 2.5 GHz 3 dBi Phantom [®] ¾ NMO, White Radome
TRA58003	4.9 – 6.0 GHz 3 dBi Phantom [®] ¾ NMO, White Radome
TRADCAGP	G - Drop ceiling antenna adaptor for P-mount Phantom w/ 6"x6"x0.016" ground plane
Sealtube3	Heat shrink tubing 3 in. x 1 in. DIA install (use for jaw protector on installation wrench)

Note: Add "B" to model number for black radome. Example: TRAB8063
Add "P" to model number for Permanent Mount. Example: TRA8063P

ANTENNA PATTERNS



Elevation Pattern (Y, Z, or H-plane)
Normalized to 3 Db-MEG



Azimuth Pattern (X,Y, or E-plane)
Normalized to 3 dB-MEG

Americas: +1.847 839.6925
IAS-AmericasSales@lairdtech.com
Europe: +44.1628.858941
IAS-EUSales@lairdtech.com
Asia: IAS-AsiaSales@lairdtech.com
Middle East and Africa:
+44.1628.858941
IAS-MEASales@lairdtech.com
<https://connectivity.lairdtech.com>



Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2018 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

