

USB 2.0 and 3.0 Cables

Stewart Connector's USB cable assemblies are fully shielded and compliant to USB 2.0 and 3.0 standards. The USB cables are designed to simplify the number of ports required to provide data and power over one cable assembly.

Features & Benefits

- USB 3.0 can deliver 5 Gbps and allows a maximum of 900 mA
- USB 2.0 can achieve 480 Mbps and allows a maximum of 500 mA
- Shielded cable design to allow for Power to be supplied over a communication signal
- Multiple end configurations for all USB offerings
- Plug and play capability that allows for hot pluggable insertion and ejection
- Over molded design to increase strain relief
- Nickel plated shell
- RoHS compliant



Applications

- IOT Applications
- Printers and Scanners
- Instrumentation
- POS Equipment
- Laptops and Desktop Computers
- Consumer Applications
- Game Ports

Part Number	Performance	Conn End A	Conn End B	Length Available	Shielded
SC-3AAKXXXF	USB 3.0	Type A	Type A	3ft, 6ft	Yes
SC-3ABKXXXF	USB 3.0	Type A	Type B	3ft, 6ft	Yes
SC-3ATKXXXF	USB 3.0	Type A	Micro B 10-Pin	3ft, 6ft	Yes
SC-2AAEXXXF	USB 2.0	Type A	Type A	3ft, 6ft, 10ft	Yes
SC-2ABEXXXF	USB 2.0	Type A	Type B	3ft, 6ft, 10ft	Yes
SC-2ANKXXXF	USB 2.0	Type A	Mini B 5-Pin	1ft, 3ft, 6ft	Yes
SC-2AMKXXXF	USB 2.0	Type A	Micro B 5-Pin	1ft, 3ft, 6ft	Yes

* "XXX" Designates cable length. Example: "003" = 3ft



Stewart Connector
11118 Susquehanna Trail South
Glen Rock, PA 17327-9199

+1 717.235.7512
techhelp@belf.com
belfuse.com/stewart-connector