

ELECTRICAL CHARACTERISTICS: (ALL DATA APPLIES AT 23° C UNLESS OTHERWISE SPECIFIED)

COIL DATA:

NOMINAL VOLTAGE: 24 VDC
 OPERATE VOLTAGE: 14.4 VDC MAXIMUM
 RELEASE VOLTAGE: 2.4 VDC MINIMUM
 EQUIVALENT COIL RESISTANCE: 317.6 OHMS ± 10%
 OPERATE TIME: Typ. 7 mSec. EXCLUDING BOUNCE
 RELEASE TIME: Typ. 5 mSec. EXCLUDING BOUNCE
 TEMPERATURE RANGE: STORAGE -40° C TO +155° C
 OPERATE -40° C TO +85° C
 OPERATE -40° C TO +125° C (APPLICATION DEPENDENT)

CONTACT DATA: (CONTACT DATA IS FORMATTED N.O./N.C.)


CONTACT ARRANGEMENT: 1 FORM C (SPDT)
 CONTACT MATERIAL: Silver based
 INITIAL VOLTAGE DROP: NO CONTACT AT 10A, typ./max. 15/200 mV
 NC CONTACT AT 10A, typ./max. 20/250 mV

MAXIMUM MAKE CURRENT: 120A/45A (LAMP) AT 28 VDC
 MAXIMUM BRAKE CURRENT: 20A/15A AT 28 VDC RESISTIVE
 MAXIMUM CONTINUOUS CURRENT: 60A/45A AT 23° C, 40A/30A AT 85° C
 INITIAL BREAKDOWN VOLTAGE: 500V RMS CONTACTS TO COIL

EXPECTED LIFE: 100,000 OPERATIONS, 20A, 28 VDC RESISTIVE ON NORMALLY OPEN CONTACT

MECHANICAL CHARACTERISTICS:

EXPECTED LIFE: 10 MILLION OPERATIONS, NO CONTACT LOAD, 20 OPERATIONS PER SECOND MAXIMUM



PROPRIETARY THE REPRODUCTION, TRANSMISSION OR USE OF THIS DOCUMENT OR IT'S CONTENTS IS NOT PERMITTED WITHOUT EXPRESSED WRITTEN AUTHORITY. OFFENDERS WILL BE LIABLE FOR ALL DAMAGES. ALL RIGHTS, INCLUDING RIGHTS CREATED BY REGISTERED PATENT(S) GRANTED FOR A UTILITY MODEL OR DESIGN, ARE RESERVED.			CHANGES TO THIS DRAWING MUST BE DONE ONLY IN CAD	PAPER SIZE A3
APPLICABLE SPEC.:			FINISH DIMENSIONS APPLY PLATING	
TOLERANCE UNLESS SPECIFIED OTHERWISE		DIMENSIONS IN MM	SCALE	WEIGHT
MATERIAL			PART NAME DATA SHEET V23134-A4064-X551	
LOCATION			DWG NO. V23134-A4064-X551	SHT. 1 OF 1
Al Initial Release 05JAN2017 KBieh	A --- 11NOV2016 KBieh			
REV. CHANGE ORDER	DATE	APP.		