XAPM2204

Empty control station, zinc alloy, blue, 4 cutouts, Ø22, 80 x 130 x 51.5 mm





Main

Range of product	Harmony XAP
Product or component type	Die-cast empty control station
Device short name	XAPM
Product destination	For Ø 22 mm control and signalling units
Product front plate size	80 x 130 mm
Usable depth	1.93 in (49 mm)
Number of cut-out	4 cut-outs
Colour of base of enclosure	Blue
Colour of cover	Blue
Material	Zinc alloy
Cable entry	1 hole with blanking plug for cable gland 0.55 in (14 mm) 1 hole without blanking plug for cable gland 0.55 in (14 mm)
Device mounting	Flush
IP degree of protection	IP65 conforming to IEC 60529 IP69 NF C 20-010 IP69K

Complementary

Number of vertical rows	2
Net Weight	1.32 lb(US) (0.6 kg)

Environment

Protective treatment	TC				
Ambient air temperature for storage	-40158 °F (-4070 °C)				
Ambient air temperature for operation	-40158 °F (-4070 °C)				
Overvoltage category	Class I IEC 60536 Class I conforming to NF C 20-030				

Ordering and shipping details

22475 - WALL STATIONS				
CS2				
00785901273066				
1				
1.53 lb(US) (0.69 kg)				
No				
MA				
	CS2 00785901273066 1 1.53 lb(US) (0.69 kg) No			

Packing Units

Unit Type of Package 1	PCE				
Package 1 Height	3.54 in (9 cm)				
Package 1 width	3.74 in (9.5 cm)				
Package 1 Length	6.10 in (15.5 cm)				
Unit Type of Package 2	S03				
Number of Units in Package 2	12				

Package 2 Weight	19.14 lb(US) (8.68 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability


stainable offer status Green Premium product							
alifornia proposition 65 WARNING: This product can expose you to chemicals including: Di phthalate (DIDP), which is known to the State of California to cause or other reproductive harm. For more information go to www.P65Wa							
REACh Regulation	REACh Declaration						
REACh free of SVHC	Yes						
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)						
Toxic heavy metal free	Yes						
Mercury free	Yes						
RoHS exemption information	₫Yes						
China RoHS Regulation	China RoHS Declaration						
Environmental Disclosure	Product Environmental Profile						
Circularity Profile							
	· ·						

Contractual warranty

Warranty 18 months	

XAPM2204

Dimensions and Fixing



- (1) 1 hole, without blanking plug, for cable gland with 14 mm/0.55 in. maximum clamping capacity
- (2) 1 hole, with blanking plug (protrusion 6 mm/0.23 in.), for cable gland with 14 mm/0.55 in. maximum clamping capacity
- (3) 2 x Ø 5.6 mm/0.22 in. holes, depth 20 mm/0.78 in.
- P Usable depth

a b			С		G		Н		Р		
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
80	3.15	130	5.12	51.5	2.03	50	1.97	115	4.53	49	1.93

Refer to the product characteristics to get the number of cut-outs.

Cut-out interaxis dimensions (vertical mounting)



- b1 Vertical interaxis: 40 mm/1.57 in.
- b2 Horizontal interaxis: 30 mm/1.18 in.