XAPM3204

Empty control station, zinc alloy, blue, 4 cutouts, Ø22, 80 x 175 x 51.5 mm





Main Range of product Harmony XAP Product or component Die-cast empty control station type Device short name XAPM Product destination For Ø 22 mm control and signalling units 80 x 175 mm Product front plate size Usable depth 1.93 in (49 mm) Number of cut-out 4 cut-outs Colour of base of Blue enclosure Colour of cover Blue Material Zinc alloy Cable entry 1 hole with blanking plug for cable gland, clamping capacity: 18 mm 1 hole without blanking plug for cable gland, clamping capacity: 18 mm

IP65 conforming to IEC 60529

IP69 NF C 20-010

Flush

IP69K

Complementary

Number of vertical rows	1
Net Weight	1.94 lb(US) (0.88 kg)

Device mounting

IP degree of protection

Environment

Protective treatment	TC			
Ambient air temperature for storage	-40158 °F (-4070 °C)			
Ambient air temperature for operation	-40158 °F (-4070 °C)			
Overvoltage category	Class I IEC 60536 Class I conforming to NF C 20-030			

Ordering and shipping details

Category	22466 - PUSHBUTTON, ACCESSORIES
Discount Schedule	CS2
GTIN	00785901312789
Nbr. of units in pkg.	1
Package weight(Lbs)	2.16 lb(US) (0.98 kg)
Returnability	No
Country of origin	MA
Country of origin	IVIA

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	3.35 in (8.5 cm)	
Package 1 width	4.72 in (12 cm)	
Package 1 Length	7.40 in (18.8 cm)	
Unit Type of Package 2	S02	
Number of Units in Package 2	6	

Package 2 Weight	13.22 lb(US) (5.996 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Unit Type of Package 3	P06
Number of Units in Package 3	48
Package 3 Weight	129.41 lb(US) (58.7 kg)
Package 3 Height	30.31 in (77 cm)
Package 3 width	31.50 in (80 cm)
Package 3 Length	23.62 in (60 cm)


Offer Sustainability

Sustainable offer status	Green Premium product WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov					
California proposition 65						
REACh Regulation	REACh Declaration					
REACh free of SVHC	Yes					
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)					
Toxic heavy metal free	Yes					
Mercury free	Yes					
RoHS exemption information	₫Yes					
China RoHS Regulation	☐ China RoHS Declaration					
Environmental Disclosure	Product Environmental Profile					
Circularity Profile	☑ End Of Life Information					

Contractual warranty

Warranty 18 months	
--------------------	--

Dimensions and Fixing



- (1)
- 1 hole, without blanking plug, for cable gland with 18 mm/0.71 in. maximum clamping capacity 1 hole, with blanking plug (protrusion 6 mm/0.23 in.), for cable gland with 18 mm/0.71 in. maximum clamping capacity (2)
- (3) 2 x Ø 5.6 mm/0.22 in. holes, depth 20 mm/0.78 in.
- Usable depth

a b		С		G		Н		Р			
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
80	3.15	175	6.89	51.5	2.03	50	1.97	160	6.30	49	1.93

Refer to the product characteristics to get the number of cut-outs.

Cut-out interaxis dimensions



b1 Vertical interaxis: 30 mm/1.18 in.