XAPM3503

Empty control station, zinc alloy, blue, 3 cutouts, Ø22, 80 x 175 x 77 mm





Main

Range of product	Harmony XAP					
Product or component type	Die-cast empty control station					
Device short name	XAPM					
Product destination	For Ø 22 mm control and signalling units					
Product front plate size	80 x 175 mm					
Usable depth	2.93 in (74.5 mm)					
Number of cut-out	3 cut-outs					
Colour of base of enclosure	Blue					
Colour of cover	Blue					
Material	Zinc alloy					
Cable entry	1 hole with blanking plug for cable gland, clamping capacity: 18 mm 1 hole without blanking plug for cable gland, clamping capacity: 18 mm					
Device mounting	Flush					
IP degree of protection	IP65 conforming to IEC 60529 IP69 NF C 20-010 IP69K					

Complementary

<u></u>	
Number of vertical rows	1
Net Weight	2524.29 lb(US) (1145 kg)

Environment

Protective treatment	TC				
Ambient air temperature for storage	-40158 °F (-4070 °C)				
Ambient air temperature for operation	-40158 °F (-4070 °C)				
Overvoltage category	Class I IEC 60536 Class I conforming to NF C 20-030				

Ordering and shipping details

Category	22475 - WALL STATIONS				
Discount Schedule	CS2				
GTIN	00785901450511				
Nbr. of units in pkg.	1				
Package weight(Lbs)	2.91 lb(US) (1.32 kg)				
Returnability	No				
Country of origin	MA				

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	3.35 in (8.5 cm)	
Package 1 width	4.72 in (12 cm)	
Package 1 Length	7.28 in (18.5 cm)	
Unit Type of Package 2	S02	
Number of Units in Package 2	6	

Package 2 Weight	17.96 lb(US) (8.148 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Unit Type of Package 3	P06
Number of Units in Package 3	48
Package 3 Weight	164.54 lb(US) (74.636 kg)
Package 3 Height	30.31 in (77 cm)
Package 3 width	31.50 in (80 cm)
Package 3 Length	23.62 in (60 cm)

Offer Sustainability


Green Premium product					
WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov					
☑ REACh Declaration					
Yes					
Pro-active compliance (Product out of EU RoHS legal scope) [™] EU RoHS Declaration					
Yes					
Yes					
₫Yes					
☑ China RoHS Declaration					
Product Environmental Profile					
End Of Life Information					

Contractual warranty

Warranty	18 months
----------	-----------

XAPM3503

Dimensions and Fixing



- (1)
- 1 hole, without blanking plug, for cable gland with 18 mm/0.71 in. maximum clamping capacity 1 hole, with blanking plug (protrusion 6 mm/0.23 in.), for cable gland with 118 mm/0.71 in. maximum clamping capacity (2)
- (3) 2 x Ø 5.6 mm/0.22 in. holes, depth 20 mm/0.78 in.
- Usable depth

а	b b		С		G		Н		Р		
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
80	3.15	175	6.89	77	3.03	50	1.97	160	6.30	74.5	2.93

Refer to the product characteristics to get the number of cut-outs.

Cut-out interaxis dimensions



b1 Vertical interaxis: 40 mm/1.57 in.