XAPM44

Empty control station, zinc alloy, blue, undrilled, 80 x 220 x 77 mm





Main

| Range of product | Harmony XAP | | | | |
|-----------------------------|--|--|--|--|--|
| Product or component type | Die-cast empty control station | | | | |
| Device short name | XAPM | | | | |
| Product front plate size | 80 x 220 mm | | | | |
| Usable depth | 2.93 in (74.5 mm) | | | | |
| Number of cut-out | Undrilled | | | | |
| Colour of base of enclosure | Blue | | | | |
| Colour of cover | Blue | | | | |
| Material | Zinc alloy | | | | |
| Cable entry | 1 hole without blanking plug for cable gland 0.71 in (18 mm) | | | | |
| Product mounting | Flush mounting | | | | |
| IP degree of protection | IP65 IEC 60529 IP69 NF C 20-010 IP69K | | | | |

Complementary

| Net Weight | 3.11 lb(US) (1.41 kg) |
|------------|-----------------------|
|------------|-----------------------|

Environment

| Protective treatment | TC | | | | |
|---------------------------------------|--|--|--|--|--|
| Ambient air temperature for storage | -40158 °F (-4070 °C) | | | | |
| Ambient air temperature for operation | -40158 °F (-4070 °C) | | | | |
| Electrical shock protection class | Class I IEC 60536 Class I conforming to NF C 20-030 | | | | |

Ordering and shipping details

| Category | 18406 - WORLD SERVICE PARTS(OTHER OP INT) | | | |
|-----------------------|---|--|--|--|
| Discount Schedule | CS2 | | | |
| GTIN | 00785901450542 | | | |
| Nbr. of units in pkg. | 1 | | | |
| Package weight(Lbs) | 3.52 lb(US) (1.60 kg) | | | |
| Returnability | No | | | |
| Country of origin | MA | | | |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|--------------------------|--|
| Package 1 Height | 3.46 in (8.8 cm) | |
| Package 1 width | 5.12 in (13 cm) | |
| Package 1 Length | 9.13 in (23.2 cm) | |
| Unit Type of Package 2 | S03 | |
| Number of Units in Package 2 | 7 | |
| Package 2 Weight | 25.70 lb(US) (11.658 kg) | |
| Package 2 Height | 11.81 in (30 cm) | |
| Package 2 width | 11.81 in (30 cm) | |

| Package 2 Length | 15.75 in (40 cm) | | | |
|------------------------------|--------------------------|--|--|--|
| Unit Type of Package 3 | P06 | | | |
| Number of Units in Package 3 | 32 | | | |
| Package 3 Weight | 136.42 lb(US) (61.88 kg) | | | |
| Package 3 Height | 30.31 in (77 cm) | | | |
| Package 3 width | 31.50 in (80 cm) | | | |
| Package 3 Length | 23.62 in (60 cm) | | | |

Offer Sustainability

| Sustainable offer status | Green Premium product | | | | |
|----------------------------|---|--|--|--|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov | | | | |
| REACh Regulation | ☑ REACh Declaration | | | | |
| REACh free of SVHC | Yes | | | | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration | | | | |
| Toxic heavy metal free | Yes | | | | |
| Mercury free | Yes | | | | |
| RoHS exemption information | ₫Yes | | | | |
| China RoHS Regulation | ☑ China RoHS Declaration | | | | |
| Environmental Disclosure | Product Environmental Profile | | | | |
| Circularity Profile | ☐ End Of Life Information | | | | |
| | | | | | |


Contractual warranty

| Contraction Warranty | |
|----------------------|-----------|
| Warranty | 18 months |

Product data sheet **Dimensions Drawings**

XAPM44

Dimensions and Fixing



- (1) 1 hole, without blanking plug, for cable gland with 18 mm/0.71 in. maximum clamping capacity (3) $2 \times \emptyset$ 5.6 mm/0.22 in. holes, depth 20 mm/0.79 in.

| а | | b | | С | | G | | Н | | Р | |
|----|------|-----|------|----|------|----|------|-----|------|------|------|
| mm | in. | mm | in. | mm | in. | mm | in. | mm | in. | mm | in. |
| 80 | 3.15 | 220 | 8.66 | 77 | 3.03 | 50 | 1.97 | 205 | 8.07 | 74.5 | 2.93 |