XAPM4508

Empty control station, zinc alloy, blue, 8 cutouts, Ø22, 80 x 220 x 77 mm





Main Range of product Harmony XAP Product or component Die-cast empty control station type Device short name XAPM Product destination For Ø 22 mm control and signalling units 80 x 220 mm Product front plate size Usable depth 2.93 in (74.5 mm) Number of cut-out 8 cut-outs Colour of base of Blue enclosure Colour of cover Blue Material Zinc alloy Cable entry 1 hole without blanking plug for cable gland, clamping capacity: 18 mm Device mounting Flush IP degree of protection IP65 conforming to IEC 60529 IP69 NF C 20-010 IP69K

Complementary

Number of vertical rows	2
Net Weight	3.02 lb(US) (1.37 kg)

Environment

Protective treatment	TC
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-40158 °F (-4070 °C)
Overvoltage category	Class I IEC 60536 Class I conforming to NF C 20-030

Ordering and shipping details

Category 22475 - WALL STATIONS Discount Schedule CS2 GTIN 00785901450559 Nbr. of units in pkg. 1 Package weight(Lbs) 3.39 lb(US) (1.54 kg) Returnability No Country of origin MA	Cracing and shipping actains	
GTIN 00785901450559 Nbr. of units in pkg. 1 Package weight(Lbs) 3.39 lb(US) (1.54 kg) Returnability No	Category	22475 - WALL STATIONS
Nbr. of units in pkg. 1 Package weight(Lbs) 3.39 lb(US) (1.54 kg) Returnability No	Discount Schedule	CS2
Package weight(Lbs) 3.39 lb(US) (1.54 kg) Returnability No	GTIN	00785901450559
Returnability No	Nbr. of units in pkg.	1
<u> </u>	Package weight(Lbs)	3.39 lb(US) (1.54 kg)
Country of origin MA	Returnability	No
	Country of origin	MA

Packing Units

Package 1 Height	1.310 dm
Package 1 width	0.830 dm
Package 1 Length	2.350 dm

Offer Sustainability

Contractual warranty


Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

18 months

XAPM4508

Dimensions and Fixing



- 1 hole, without blanking plug, for cable gland with 18 mm/0.71 in. maximum clamping capacity 2 x \varnothing 5.6 mm/0.22 in. holes, depth 20 mm/0.78 in. (1)
- Usable depth

a b		b		С		G		Н		Р	
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
80	3.15	220	6.89	77	3.03	50	1.97	205	8.07	74.5	2.93

Refer to the product characteristics to get the number of cut-outs.

Cut-out interaxis dimensions (vertical mounting)



- Vertical interaxis: 40 mm/1.57 in.
- Horizontal interaxis: 30 mm/1.18 in.