XMLP300PD230

pressure transmitter - XMLP - 300psi - 1/4"18NPT - 4..20mA - M12 - set 1





Main

Range of product	OsiSense XM
Product or component type	Electronic pressure sensors
Pressure sensor type	Pressure transmitter
Pressure sensor name	XMLP
Electrical circuit type	Control circuit
Pressure sensor size	300 psi (2068.43 kPa)
Local display	Without
Controlled fluid	Fresh water (0135 °C) Air -40275 °F (-40135 °C)) Hydraulic oil -40275 °F (-40135 °C)) Gas -40275 °F (-40135 °C)) Refrigeration fluid -40275 °F (-40135 °C))
Fluid connection type	1/4" - 18 NPT (male)
Electrical connection	1 male connector M12 4 pins
[Us] rated supply voltage	1224 V DC SELV (voltage limits: 733 V)
Current consumption	< 23 mA
Type of output signal	Analogue
Analogue output function	420 mA, 2-wire
Quantity per set	Set of 1
Type of packing	Individual

Complementary

<u>'</u>	900 psi (6205.28 kPa)
Destruction pressure	
	2200 psi (15168.47 kPa)
Materials in contact with fluid	Stainless steel AISI 316L
Operating position	Any position
	Load short-circuit Reverse polarity
	Electrostatic discharge immunity test EN/IEC 61000-4-2 8 kV air, 4 kV contact 1.2/50 µs shock waves immunity test conforming to EN/IEC 61000-4-5 1 kV 42 Ohm Immunity to magnetic fields conforming to EN/IEC 61000-4-8 100 A/m 50 Hz Electrical fast transient/burst immunity test EN/IEC 61000-4-4 4 kV Susceptibility to electromagnetic fields conforming to EN/IEC 61000-4-3 10 V/m 803000 MHz Radiated RF fields conforming to EN/IEC 61000-4-6 10 V 0.0180 MHz
[Uimp] rated impulse withstand voltage	0.5 kV
Response time on output	<= 2 ms 1090 % of full scale
Measurement accuracy	+/- 0.5 % of the measuring range
Resolution	0.1 % of the measuring range
Drift of the sensitivity	+/- 0.02 % of measuring range/°K
Drift of the zero point	+/- 0.02 % of measuring range/°K
Mechanical durability	10000000 cycles
Net weight	0.19 lb(US) (0.088 kg)
Diameter	1.02 in (26 mm)
Length	1.42 in (36 mm)

Environment

Standards	EN/IEC 61326-2-3	
	NSF ANSI 61	
Product certifications	CE	
	CULus	
	RCM	
	EAC	
Protective treatment	TC	
Ambient air temperature for operation	-22185 °F (-3085 °C)	
Ambient air temperature for storage	-58212 °F (-50100 °C)	
Vibration resistance	20 gn 152000 Hz) EN/IEC 60068-2-6	
Shock resistance	100 gn for 11 ms conforming to EN/IEC 60068-2-27	
IP degree of protection	IP65 EN/IEC 60529	
	IP67 conforming to EN/IEC 60529	
	IP69K EN/IEC 60529	

Ordering and shipping details

22419 - PRESSURE SWITCH IEC (HIGH,LOW,GEN)
DS2
00785901717546
1
0.19 lb(US) (0.09 kg)
Yes
CH

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.65 in (4.2 cm)	
Package 1 width	1.65 in (4.2 cm)	
Package 1 Length	3.43 in (8.7 cm)	


Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
	Product Environmental Profile

Product data sheet Dimensions Drawings

XMLP300PD230

Dimensions




(1) SW24 tightening torque ≤ 25 N.m / 221 lb-in

XMLP300PD230

Wiring Diagram

2-Wire Technique (4-20 mA)



(a) I out

XMLP300PD230

Curves

