# **XS7T2PC440**

inductive sensor XS7 26x26x26 - plastic - Sn10mm - 12..48VDC - cable 2m



## Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XS7
Sensor design	Cubic form 26 x 26 x 26
Size	26 mm
Body type	Fixed
Detector flush mounting acceptance	Flush mountable
Material	Plastic
Enclosure material	Plastic
Type of output signal	Discrete
Wiring technique	4-wire
[Sn] nominal sensing distance	10 mm
Discrete output function	1 NO + 1 NC
Output circuit type	DC
Discrete output type	PNP
Electrical connection	Cable
Cable length	2 m
[Us] rated supply voltage	1248 V DC
Switching capacity in mA	<= 200 mA
IP degree of protection	IP67

### Complementary

Detection face	5 positions turret head	
Front material	Plastic	
Cable composition	4 x 0.34 mm²	
Wire insulation material	PVC	
Switching frequency	<= 1000 Hz	
Marking	CE	
Depth	26 mm	
Height	26 mm	
Width	26 mm	

#### **Environment**

product certifications	CCC CSA
	UL
ambient air temperature for operation	-2570 °C

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0836 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Warranty period 18 months

