XVR10B03

Rotating beacon, 106 mm, green, without buzzer, 24 V AC DC





Main Range of product Harmony XVR Product or component Prewired rotating mirror beacon type Sound signalling Without Device short name XVR Mounting diameter 4.17 in (106 mm) IP degree of protection IP55 IEC 60529 with accessory) IP23 IEC 60529 [Us] rated supply 24 V AC/DC

High luminosity LED, green

Complementary

o o mpio montary		
Material	ABS (acrylonitrile butadiene-styrene) body part PMMA (polymethyl methacrylate) globe	
CAD overall width	4.17 in (106 mm)	
CAD overall depth	4.17 in (106 mm)	
Net Weight	1.10 lb(US) (0.5 kg)	
Marking	CE	
Product mounting	By 3 M4 screws	
Supply voltage limits	1930 V DC 21.626.4 V AC	
[Uimp] rated impulse withstand voltage	0.8 kV	
Current consumption	125 mA	
Flashing frequency	2.3 Hz	
Clamping connection capacity	0.83 mm²	
AWG gauge	AWG 18	
Cable length	15.75 in (400 mm)	

voltage Light source

Environment

Standards	EN 61000-6-2
	EN 61000-6-4
Product certifications	UL
Protective treatment	TC
Ambient air temperature for storage	-31158 °F (-3570 °C)
Ambient air temperature for operation	14122 °F (-1050 °C)
Electrical shock protection class	Class II IEC 61140

Ordering and shipping details

XV	
00785901964667	
1	
1.37 lb(US) (0.62 kg)	
No	
ID	
	00785901964667 1 1.37 lb(US) (0.62 kg) No

Packing Units

Package 1 Height	1.950 dm
Package 1 width	1.380 dm
Package 1 Length	1.400 dm

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty


Contractidal warranty		
Warranty	18 months	


Product data sheet Dimensions Drawings

XVR10B03

Rotating Mirror Beacon

Dimensions





Product data sheet Mounting and Clearance

XVR10B03

Rotating Mirror Beacon

Panel Cut-out

