## XVR12B05

# Rotating beacon, 120 mm, orange, without buzzer, 24 V AC DC





# Main

TTT-COLOR	
Range of product	Harmony XVR
Product or component type	Prewired rotating mirror beacon
Sound signalling	Without
Device short name	XVR
Mounting diameter	4.72 in (120 mm)
IP degree of protection	IP23 IEC 60529
[Us] rated supply voltage	24 V AC/DC
Light source	High luminosity LED, orange

#### Complementary

Material	ABS (acrylonitrile butadiene-styrene) body part AS globe	
CAD overall width	4.72 in (120 mm)	
CAD overall depth	4.72 in (120 mm)	
Net Weight	1.10 lb(US) (0.5 kg)	
Marking	CE	
Product mounting	By 3 M5 screws	
Supply voltage limits	1930 V DC 21.626.4 V AC	
[Uimp] rated impulse withstand voltage	0.8 kV	
Current consumption	125 mA	
Flashing frequency	2.3 Hz	
Clamping connection capacity	0.83 mm²	
AWG gauge	AWG 18	
Cable length	15.75 in (400 mm)	

#### Environment

Environment	
Standards	EN 61000-6-2 EN 61000-6-4
Protective treatment	TC
Ambient air temperature for storage	-31158 °F (-3570 °C)
Ambient air temperature for operation	14122 °F (-1050 °C)
Electrical shock protection class	Class II IEC 61140

### Ordering and shipping details

22617 - XVC TOWER LIGHTS	
XV	
00785901556299	
1	
1.31 lb(US) (0.59 kg)	
No	
JP	
	XV 00785901556299 1 1.31 lb(US) (0.59 kg) No

## Packing Units

Package 1 Height	1.950 dm
Package 1 width	1.380 dm
Package 1 Length	1.400 dm

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

#### Contractual warranty


Contraction warranty		
Warranty	18 months	


# Product data sheet Dimensions Drawings

## XVR12B05

### **Rotating Mirror Beacon**

### Dimensions





# Product data sheet Mounting and Clearance

## XVR12B05

### Rotating Mirror Beacon

### Panel Cut-out

