XVR13B04

Rotating beacon, 130 mm, red, without buzzer, 24 V DC





Main

Mairi	
Range of product	Harmony XVR
Product or component type	Prewired rotating mirror beacon
Sound signalling	Without
Device short name	XVR
Mounting diameter	5.12 in (130 mm)
IP degree of protection	IP66 IEC 60529 resistant to vibration)
[Us] rated supply voltage	24 V DC
Light source	High luminosity LED, red

Complementary

Material	ABS (acrylonitrile butadiene-styrene) body part PC globe	
CAD overall width	5.12 in (130 mm)	
CAD overall depth	5.12 in (130 mm)	
Net Weight	1.76 lb(US) (0.8 kg)	
Marking	CE	
Product mounting	By 3 M8 screws	
Supply voltage limits	1930 V DC	
[Uimp] rated impulse withstand voltage	0.8 kV	
Current consumption	125 mA	
Flashing frequency	2.7 Hz	
Clamping connection capacity	1.25 mm²	
AWG gauge	AWG 18	
Cable length	15.75 in (400 mm)	

Environment

Liviloninon		
Standards	EN 61000-6-2 EN 61000-6-4	
Protective treatment	TC	
Ambient air temperature for storage	-31158 °F (-3570 °C)	
Ambient air temperature for operation	-22122 °F (-3050 °C)	
Electrical shock protection class	Class II IEC 61140	

Ordering and shipping details

Category	22617 - XVC TOWER LIGHTS	
Discount Schedule	XV	
GTIN	00785901686309	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.6 lb(US) (1.18 kg)	
Returnability	No	
Country of origin	ID	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	7.36 in (18.7 cm)	
Package 1 width	7.36 in (18.7 cm)	
Package 1 Length	10.47 in (26.6 cm)	
Unit Type of Package 2	S04	
Number of Units in Package 2	6	
Package 2 Weight	18.71 lb(US) (8.488 kg)	
Package 2 Height	11.81 in (30 cm)	
Package 2 width	15.75 in (40 cm)	
Package 2 Length	23.62 in (60 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information


Contractual warranty


Warranty	18 months

XVR13B04

Rotating Mirror Beacon

Dimensions





Product data sheet Mounting and Clearance

XVR13B04

Rotating Mirror Beacon

Panel Cut-out

