



## Main

|                                    |                                                  |
|------------------------------------|--------------------------------------------------|
| Range of product                   | Harmony XVU                                      |
| Product or component type          | Modular tower light                              |
| Beacon or indicator bank unit type | LED unit                                         |
| Mounting diameter                  | 2.36 in (60 mm)                                  |
| Component name                     | XVU                                              |
| Light source                       | LED, red                                         |
| Device application                 | Packaging machine<br>Automotive<br>Machine tools |

## Complementary

|                                |                                                                            |
|--------------------------------|----------------------------------------------------------------------------|
| Signalling type                | Steady                                                                     |
| Assembly style                 | Up to 4 units with buzzer<br>Customer assembly, up to 5 units              |
| Material                       | PC (polycarbonate) V-2 conforming to UL 94<br>PC (polycarbonate) V-0 UL 94 |
| [Us] rated supply voltage      | 24 V AC/DC                                                                 |
| Maximum power dissipation in W | 2 W                                                                        |
| Current consumption            | <= 40 mA                                                                   |
| Signalling type                | Steady                                                                     |
| Length                         | 1.97 in (50 mm)                                                            |
| Net Weight                     | 0.14 lb(US) (0.064 kg)                                                     |

## Environment

|                                       |                            |
|---------------------------------------|----------------------------|
| Product certifications                | CE<br>RoHS<br>CSA<br>UL    |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C) |
| IP degree of protection               | IP65                       |
| Ambient air temperature for operation | -13...122 °F (-25...50 °C) |
| Vibration resistance                  | 2 gn                       |

## Ordering and shipping details

|                       |                          |
|-----------------------|--------------------------|
| Category              | 22618 - XVU TOWER LIGHTS |
| Discount Schedule     | XV                       |
| GTIN                  | 00785901219217           |
| Nbr. of units in pkg. | 1                        |
| Package weight(Lbs)   | 0.32 lb(US) (0.15 kg)    |
| Returnability         | Yes                      |
| Country of origin     | ID                       |

## Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Package 1 Height             | 3.54 in (9 cm)          |
| Package 1 width              | 3.58 in (9.1 cm)        |
| Package 1 Length             | 5.24 in (13.3 cm)       |
| Unit Type of Package 2       | S03                     |
| Number of Units in Package 2 | 24                      |
| Package 2 Weight             | 9.89 lb(US) (4.488 kg)  |
| Package 2 Height             | 11.81 in (30 cm)        |
| Package 2 width              | 11.81 in (30 cm)        |
| Package 2 Length             | 15.75 in (40 cm)        |
| Unit Type of Package 3       | P06                     |
| Number of Units in Package 3 | 192                     |
| Package 3 Weight             | 95.66 lb(US) (43.39 kg) |
| Package 3 Height             | 30.31 in (77 cm)        |
| Package 3 width              | 31.50 in (80 cm)        |
| Package 3 Length             | 23.62 in (60 cm)        |


## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                             |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                       |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                           |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                              |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                               |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                                                                                                                                                                                     |


## Illuminated LED Unit

### Dimensions

mm  
in.




## Modular Tower Lights Mounting



| Drawing  | Part number          | Part name                    |
|----------|----------------------|------------------------------|
| A1       | -                    | Top cover                    |
| -        | Top cover (Silver)   |                              |
| A2       | XVUC9S               | Buzzer unit                  |
| XVUC9SQ  | Buzzer unit (Silver) |                              |
| A3       | XVUC23               | Green LED unit               |
| XVUC24   | Red LED unit         |                              |
| XVUC25   | Orange LED unit      |                              |
| XVUC26   | Blue LED unit        |                              |
| XVUC27   | White LED unit       |                              |
| XVUC28   | Yellow LED unit      |                              |
| A4       | XVUC29               | Multi-LED unit               |
| A5       | XVUC29P              | Multi-LED unit, Pulse signal |
| A6       | XVUC9V               | Sound unit                   |
| A7       | XVUC9VP              | Sound unit, Pulse signal     |
| A8       | XVUC020              | Extender                     |
| XVUC020Q | Extender (Silver)    |                              |
| A9       | XVUC21B              | DC body                      |

| Drawing   | Part number                                    | Part name                                             |
|-----------|------------------------------------------------|-------------------------------------------------------|
| XVUC21BQ  | DC body (Silver)                               |                                                       |
| A10       | XVUC21M                                        | AC body NPN                                           |
| XVUC21MP  | AC body PNP                                    |                                                       |
| XVUC21MQP | AC body PNP (Silver)                           |                                                       |
| A11       | XVUZ06                                         | Flexible option                                       |
| A12       | XVUZ01                                         | Fixing Unit - Direct mounting (3 pins)                |
| XVUZ01Q   | Fixing Unit - Direct mounting (Silver,3 pins)  |                                                       |
| XVUZ03    | Fixing Unit - Direct mounting (2 pins)         |                                                       |
| XVUZ04    | Fixing Unit - Direct mounting (4 pins)         |                                                       |
| A13       | XVUZ02                                         | Fixing Unit - Plate with Pole (100 mm)                |
| XVUZ02Q   | Fixing Unit - Plate with Pole (100 mm, Silver) |                                                       |
| XVUZ400   | Fixing Unit - Plate with Pole (400 mm)         |                                                       |
| XVUZ800   | Fixing Unit - Plate with Pole (800 mm)         |                                                       |
| A14       | XVUZ05                                         | Fixing Unit - Plate with adjustment pole (100-385 mm) |
| A15       | XVUC43                                         | Green LED unit, Flash                                 |
| XVUC44    | Red LED unit, Flash                            |                                                       |
| XVUC45    | Orange LED unit, Flash                         |                                                       |
| XVUC46    | Blue LED unit, Flash                           |                                                       |
| XVUC47    | White LED unit, Flash                          |                                                       |
| XVUC48    | Yellow LED unit, Flash                         |                                                       |
| A16       | XVUZ100T                                       | Fixing Unit - Metal bracket with pole (100 mm)        |
| XVUZ250T  | Fixing Unit - Metal bracket with pole(250 mm)  |                                                       |
| XVUZ400T  | Fixing Unit - Metal bracket with pole (400 mm) |                                                       |
| A17       | XVUZ12                                         | Fixing plate for use on vertical support - black      |

## Illuminated Units, Multi-LED and Audible Units Wiring



- (A) Fixing Unit
- (1) Dimensions of Wiring size
- (2) Push-in Wire Connectors
- (3) Fuse : 2A ,250V
- (4) Fuse : 0.5A ,125V
- (5) Modular Tower Lights 24V AC/DC
- (6) Modular Tower Lights 100...240V AC
- L1 to Illuminated LED Units
- L5 :