


## Features

- P-Channel MOSFET
- Low On-Resistance
  - 150 mΩ @  $V_{GS} = -4.5V$
  - 200 mΩ @  $V_{GS} = -2.5V$
  - 240 mΩ @  $V_{GS} = -1.8V$
- Very Low Gate Threshold Voltage  $V_{GS(th)} \leq 1V$
- Low Input Capacitance
- Fast Switching Speed
- Low Input/Output Leakage
- **Lead Free By Design/RoHS Compliant (Note 2)**
- **"Green" Device (Note 3)**
- **Qualified to AEC-Q101 standards for High Reliability**

## Mechanical Data

- Case: SOT-323
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals Connections: See Diagram Below
- Terminals: Finish — Matte Tin annealed over Alloy 42 leadframe. Solderable per MIL-STD-202, Method 208
- Marking Information: See Page 4
- Ordering Information: See Page 4
- Weight: 0.006 grams (approximate)



## Maximum Ratings @ $T_A = 25^\circ C$ unless otherwise specified

| Characteristic         | Symbol    | Value        | Units |
|------------------------|-----------|--------------|-------|
| Drain-Source Voltage   | $V_{DSS}$ | -20          | V     |
| Gate-Source Voltage    | $V_{GSS}$ | $\pm 12$     | V     |
| Drain Current (Note 1) | $I_D$     | -1.5<br>-1.0 | A     |
| Pulsed Drain Current   | $I_{DM}$  | -5           | A     |

## Thermal Characteristics

| Characteristic                          | Symbol          | Value       | Units        |
|-----------------------------------------|-----------------|-------------|--------------|
| Total Power Dissipation (Note 1)        | $P_D$           | 250         | mW           |
| Thermal Resistance, Junction to Ambient | $R_{\theta JA}$ | 500         | $^\circ C/W$ |
| Operating and Storage Temperature Range | $T_J, T_{STG}$  | -55 to +150 | $^\circ C$   |

- Notes:
1. Device mounted on FR-4 substrate PC board, 2oz. Copper, with minimum recommended pad layout.
  2. No purposefully added lead.
  3. Diodes Inc.'s "Green" policy can be found on our website at [http://www.diodes.com/products/lead\\_free/index.php](http://www.diodes.com/products/lead_free/index.php).

**Electrical Characteristics** @ $T_A = 25^\circ\text{C}$  unless otherwise specified

| Characteristic                      | Symbol       | Min   | Typ              | Max               | Unit       | Test Condition                                                                                  |
|-------------------------------------|--------------|-------|------------------|-------------------|------------|-------------------------------------------------------------------------------------------------|
| <b>OFF CHARACTERISTICS (Note 4)</b> |              |       |                  |                   |            |                                                                                                 |
| Drain-Source Breakdown Voltage      | $BV_{DSS}$   | -20   | —                | —                 | V          | $V_{GS} = 0V, I_D = -250\mu A$                                                                  |
| Zero Gate Voltage Drain Current     | $I_{DSS}$    | —     | —                | -1.0<br>-5.0      | $\mu A$    | $T_J = 25^\circ\text{C}$<br>$T_J = 125^\circ\text{C}$<br>$V_{DS} = -20V, V_{GS} = 0V$           |
| Gate-Source Leakage                 | $I_{GSS}$    | —     | —                | $\pm 100$         | nA         | $V_{GS} = \pm 12V, V_{DS} = 0V$                                                                 |
| <b>ON CHARACTERISTICS (Note 4)</b>  |              |       |                  |                   |            |                                                                                                 |
| Gate Threshold Voltage              | $V_{GS(th)}$ | -0.45 | —                | -1.0              | V          | $V_{DS} = V_{GS}, I_D = -250\mu A$                                                              |
| Static Drain-Source On-Resistance   | $R_{DS(on)}$ | —     | 92<br>134<br>180 | 150<br>200<br>240 | m $\Omega$ | $V_{GS} = -4.5V, I_D = -2.0A$<br>$V_{GS} = -2.5V, I_D = -1.5A$<br>$V_{GS} = -1.8V, I_D = -0.5A$ |
| Forward Transconductance            | $g_{FS}$     | —     | 3.1              | —                 | S          | $V_{DS} = -10V, I_D = -810mA$                                                                   |
| Diode Forward Voltage (Note 4)      | $V_{SD}$     | —     | —                | -0.9              | V          | $V_{GS} = 0V, I_S = -0.5A$                                                                      |
| <b>DYNAMIC CHARACTERISTICS</b>      |              |       |                  |                   |            |                                                                                                 |
| Input Capacitance                   | $C_{iss}$    | —     | 320              | —                 | pF         | $V_{DS} = -16V, V_{GS} = 0V$<br>$f = 1.0MHz$                                                    |
| Output Capacitance                  | $C_{oss}$    | —     | 80               | —                 | pF         |                                                                                                 |
| Reverse Transfer Capacitance        | $C_{rss}$    | —     | 60               | —                 | pF         |                                                                                                 |
| Turn-On Delay Time                  | $t_{D(on)}$  | —     | 12.5             | —                 | ns         | $V_{DS} = -10V, V_{GS} = -4.5V,$<br>$R_L = 10\Omega, R_G = 1.0\Omega$                           |
| Turn-On Rise Time                   | $t_r$        | —     | 10.3             | —                 | ns         |                                                                                                 |
| Turn-Off Delay Time                 | $t_{D(off)}$ | —     | 46.5             | —                 | ns         |                                                                                                 |
| Turn-Off Fall Time                  | $t_f$        | —     | 22.2             | —                 | ns         |                                                                                                 |

Notes: 4. Short duration pulse test used to minimize self-heating effect.




Fig.1 Typical Output Characteristics




Fig. 2 Typical Transfer Characteristics




Fig. 3 On-Resistance Variation with Temperature




Fig. 4 On-Resistance vs Drain Current and Gate Voltage




Fig. 5 Drain-Source On-Resistance Vs. Drain Current and Temperature




Fig. 6: Typical Capacitance




Fig. 7 Static Drain-Source On-State Resistance vs Ambient Temperature




Fig. 8 Drain-Source Leakage Current vs Voltage





Fig. 9 Diode Forward Voltage vs. Current

## Ordering Information (Note 5)

| Part Number | Case    | Packaging        |
|-------------|---------|------------------|
| DMP2240UW-7 | SOT-323 | 3000/Tape & Reel |

Notes: 5. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

## Marking Information



DMV = Product Type Marking Code  
 YM = Date Code Marking  
 Y = Year (ex: V = 2008)  
 M = Month (ex: 9 = September)


### Date Code Key

| Year | 2008 | 2009 | 2010 | 2011 | 2012 | 2013 | 2014 | 2015 |
|------|------|------|------|------|------|------|------|------|
| Code | V    | W    | X    | Y    | Z    | A    | B    | C    |


| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3   | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |

## Package Outline Dimensions



| SOT-323              |      |      |      |
|----------------------|------|------|------|
| Dim                  | Min  | Max  | Typ  |
| A                    | 0.25 | 0.40 | 0.30 |
| B                    | 1.15 | 1.35 | 1.30 |
| C                    | 2.00 | 2.20 | 2.10 |
| D                    | -    | -    | 0.65 |
| G                    | 1.20 | 1.40 | 1.30 |
| H                    | 1.80 | 2.20 | 2.15 |
| J                    | 0.0  | 0.10 | 0.05 |
| K                    | 0.90 | 1.00 | 1.00 |
| L                    | 0.25 | 0.40 | 0.30 |
| M                    | 0.10 | 0.18 | 0.11 |
| $\alpha$             | 0°   | 8°   | -    |
| All Dimensions in mm |      |      |      |

## Suggested Pad Layout



| Dimensions | Value (in mm) |
|------------|---------------|
| Z          | 2.8           |
| X          | 0.7           |
| Y          | 0.9           |
| C          | 1.9           |
| E          | 1.0           |

### IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

### LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2010, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)