XUB9ANANL2

photo-electric sensor - XUB - polarised - Sn 2m - 12..24VDC - cable 2m





Main

Range of product	OsiSense XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor
Sensor name	XUB
Sensor design	Cylindrical M18
Detection system	Polarised reflex
Material	Plastic
Line of sight type	Axial
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	3-wire
Discrete output type	NPN
Discrete output function	1 NO
Electrical connection	Cable
Cable length	6.56 ft (2 m)
Product specific application	-
Emission	Red polarised reflex
[Sn] nominal sensing distance	6.56 ft (2 m) polarised reflex need reflector XUZC50

Complementary

- Comprehensi	
Enclosure material	PBT
Lens material	PMMA
Maximum sensing distance	9.84 ft (3 m) polarised reflex
Output type	Solid state
Add on output	Without
Wire insulation material	PvR
Status LED	1 LED yellow)output state
[Us] rated supply voltage	1224 V DC with reverse polarity protection
Supply voltage limits	1036 V DC
Switching capacity in mA	<= 100 mA overload and short-circuit protection)
Switching frequency	<= 500 Hz
Maximum voltage drop	<1.5 V closed state)
Current consumption	35 mA no-load
Maximum delay first up	15 ms
Maximum delay response	1 ms
Maximum delay recovery	1 ms
Setting-up	Without sensitivity adjustment
Diameter	0.71 in (18 mm)
Length	2.44 in (62 mm)
Net Weight	0.09 lb(US) (0.04 kg)

Environment

Product certifications	CSA CE UL	
Ambient air temperature for operation	-13131 °F (-2555 °C)	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Vibration resistance	7 gn +/- 1.5 mm 1055 Hz) IEC 60068-2-6	
Shock resistance	30 gn 11 ms) IEC 60068-2-27	
IP degree of protection	IP67 double insulation IEC 60529 IP65 double insulation IEC 60529	

Ordering and shipping details

Category	22415 - SENSORS, PHOTOELECTRIC, BASIC
Discount Schedule	DS2
GTIN	00785901415534
Nbr. of units in pkg.	1
Package weight(Lbs)	0.2 lb(US) (0.09 kg)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.65 in (4.2 cm)	
Package 1 width	3.82 in (9.7 cm)	
Package 1 Length	5.20 in (13.2 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information


Contractual warranty

	_ •
Warranty	18 months
Trairie	To monate

Product data sheet Dimensions Drawings

XUB9ANANL2

Dimensions




Product data sheet Connections and Schema

XUB9ANANL2

Wiring Schemes

NPN Outputs




BN: Brown BU: Blue BK: Black

Product data sheet Performance Curves

XUB9ANANL2

Detection Curves



(Y) Ø of beam With reflector XUZC50