

## 200W CONVECTION COOLED



The ALM200 has medical (2  $\times$  MOPP), home healthcare and ITE safety approvals, available as class I, or class II construction with a smooth wipe clean IP32 sealed case that is ideal for healthcare applications.

The standard class I version has an IEC320-C14 inlet, the class II version with suffix C2-8 has a polarized IEC320-C8 inlet.



#### **Features**

- Regulated single outputs 12V to 48VDC
- Energy efficiency level VI
- ► European CoC tier 2 compliant
- ► Medical (2 x MOPP) & ITE approvals
- Home healthcare approval
- ▶ 4th edition medical EMC
- ► Class I as standard, class II optional
- ▶ Input voltage range 80 to 264VAC
- ► Low earth leakage current
- <0.15W standby power</p>
- ▶ IP32 environmental rating
- Optional AC cable restraint (Class I versions with C14 inlet only)
- 0° to +60°C operating temperature
- 3 year warranty

## **Applications**







Home Healthcare



Healthcare

#### **Dimensions**

209.0 x 82.0 x 43.0mm (8.23" x 3.23" x 1.69")

#### **Documentation**

For further information click the link or scan the code





### Models & ratings

Model number	Output voltage	Output current	Total regulation	Efficiency	Output power
ALM200PS12	12.0VDC	16.7A	0.50/	91.7%	
ALM200PS15	15.0VDC	13.4A	3.5%	92.4%	
ALM200PS19	19.0VDC	10.6A		92.8%	200W
ALM200PS24	24.0VDC	8.4A	3.0%	92.2%	
ALM200PS48	48.0VDC	4.2A		92.4%	

#### Notes

- 1. For class II versions, add suffix 'C2-8' to the end of the part number e.g. ALM200PS24C2-8.
- 2. For optional input connector retention clip add suffix '-A' to the model number, e.g. ALM200PS24-A (not available for C2 versions)
- 3. Power de-rated <100VAC for 12 & 15VDC models, refer to input specifications.
- 4. Typical average value measured at 25%, 50%, 75% and 100% load at 230VAC  $\,$



## Input

Characteristic	Minimum	Typical	Maximum	Units	Notes & conditions
Input voltage	80		264	VAC	19, 24 & 48VDC models: Derate linearly from 100% load at 90VAC to 80% load at 80VAC. 300VAC/5 s maximum. 12 & 15VDC models: Derate linearly from 100% load at 100VAC to 95% load at 90VAC and then derate linearly 80% load at 80VAC, 300VAC/5 s maximum.
Input frequency	47		63	Hz	
Input current		2.0/1.0		Α	Measured at 115/230VAC
Inrush current			160	Α	115/230VAC, cold start at 25°C
Power factor		>0.9			EN61000-3-2 Class A
Earth leakage current			250	μA	264VAC, 60Hz
No load input power			0.15	W	
Input protection	T3.15A/250 VAC internal fuse in both line & neutral				

## Output

Characteristic	Minimum	Typical	Maximum	Units	Notes & conditions
Output voltage	12		48	VDC	See models and ratings table
Initial set accuracy			±2	%	At 50% load
Minimum load	No minimum I	oad required			
Start up delay		1	1.5	s	
Start up rise time			40	ms	
Hold up time	20	30		ms	Full load and 115/230VAC
Line regulation			±0.5	%	
Load regulation				%	See models and ratings table
Transient response			4	%	Maximum deviation, recovering to less than 1% within 500µs for 50-75-50% load change
Ripple and noise			1.5	% pk-pk	20MHz bandwidth, measured with 20MHz Bandwidth and 10μF electrolytic in parallel with 0.1μF ceramic capacitor.
Overshoot		5	10	%	At turn on / turn off
Overload protection	115		175	%	
Overvoltage protection			150	%	Recycle mains to reset
Short circuit protection	Trip and resta	Trip and restart (hiccup), auto resetting			
Thermal protection	Measured inte	rnally, auto reset	ting		
Temperature coefficient		0.02		%/°C	
Patient leakage current			95	μA	264VAC, 60Hz

## General

Characteristic	Minimum	Typical	Maximum	Units	Notes & conditions
Efficiency		92		%	See models and ratings table and curves.
			4000	VAC	2 x MOPP
Isolation			1800	VAC	1 x MOPP (Class I versions only)
			500	VAC	Class I versions only
	45		140		PFC
Switching frequency	85 190 KHz Ma	Main converter			
Power density		0.39 (6.4)		cm <sup>3</sup> (W/in <sup>3</sup> )	
Mean time between failure		>300		khrs	MIL-HDBK-217F at 25°C GB
Weight		910 (2.01)		g (lb)	





## **Environmental**

Characteristic	Minimum	Typical	Maximum	Units	Notes & conditions
Operating temperature	0		+60	°C	Derate from 100% load at +40°C to 30% load at +60°C
Cooling	Natural conve	ction			
Operating humidity	5		95	%RH	Non-condensing
Storage temperature	-25		+80	°C	
Operating altitude			5000	m	
Shock	IEC68-2-27, 30g, 11ms half sine, 3 times in each of 6 axes				
Vibration	IEC68-2-6, 10-500Hz, 2g 10 mins/sweep, 60 mins for each of 3 axes				

## **Emissions - EMC**

Phenomenon	Standard	Test level	Notes & conditions
Emissions	EN55032	Level B	Conducted and radiated
Harmonic currents	EN61000-3-2	Class A	
Voltage flicker	EN61000-3-3		

## **Emissions - immunity**

Phenomenon	Standard	Test level	Criteria	Notes & conditions
ESD immunity	EN61000-4-2	3	А	±15kV air/±8kV contact
Radiated immunity	EN61000-4-3	10V/m	А	80-2700MHz. IEC60601-1-2 Ed.4 at other frequencies
EFT/burst	EN61000-4-4	3	А	
Surge	EN61000-4-5	Installation class 3	А	
Conducted	EN61000-4-6	10V	А	
Magnetic fields	EN61000-4-8	4	А	
		Dip: 30% 500 ms	А	
		Dip: 60% 200 ms	A/B	High line/low line
		Dip: 80% 5000 ms	В	
	EN61000-4-11	Int: 100% 10 ms	А	
		Int: 100% 20 ms	А	
Dips and interruptions		Int: 100% 5000 ms	В	
		Dip: 30% 25 AC Cycles	А	
		Dip: 60% 5 AC Cycles	А	230VAC 100% load, 100VAC 25% load
	EN60601-1-2	Int: 100% 0.5 AC Cycles	А	
		Int: 100% 1.0 AC Cycles	А	
		Int: 100% 250 AC Cycles	В	


## Safety approvals

Safety agency	Standard	Notes & conditions
UL	UL62368-1, ANSI/AAMI ES 60601-1/ANSI/AAMI HA60601-1-11	
EN	EN62368-1, EN60601-1/EN60601-1-11	60601-1-11 is for class II versions only
СВ	IEC62368-1, IEC60950-1, IEC60601-1/ IEC60601-1-11	
CE	LVD	
Others	CSA C22.2 No. 60601, CCC, PSE, KC & RCM	May require additional importer information
CE	Meets all applicable legislation	
UKCA	Meets all applicable legislation	<u> </u>






### **Derating curve**




#### **Efficiency curve**

#### **ALM200US12**



#### **ALM200US24** Load 100% 90% 115Vac input Efficiency 80% 230Vac input 70% 60% 10% 20% 30% 40% 50% 60% 70% 80% 90% 100%

#### Mechanical details



Pin	Connection
1	RTN
2	RTN
3	+Vout
4	+Vout

#### Notes:

- 1. All dimensions shown in inches (mm). Tolerance is 0.02 (0.5) maximum, except output cable length.
- 2. Weight: 910g (2.01lbs) approx.
- 3. For European mains lead order part EU-MAINS-IEC for C14 versions, or EU-MAINS-8 for C8 versions
- 4. For UK mains lead order part UK-MAINS-IEC for C14 versions, or UK-MAINS-8 for C8 versions.
- 5. For US mains lead order part US-MAINS-IEC for C14 versions, or US-MAINS-8 for C8 versions
- Output connector: 4 pin molex Mini-Fit part number 39-03-9042 housing with 45750 crimp terminals and mates with molex header 46999-0516 or equivalent