



## Main

|                                    |                    |
|------------------------------------|--------------------|
| Range of product                   | OsiSense XU        |
| Product or component type          | Ring light         |
| Accessory / separate part category | Lighting accessory |
| Light source                       | LED white          |

## Complementary

|                           |                                                            |
|---------------------------|------------------------------------------------------------|
| Material                  | Aluminium box<br>PMMA (polymethyl methacrylate) front face |
| Product compatibility     | XUW                                                        |
| Product weight            | 0.15 kg                                                    |
| [Us] rated supply voltage | 24 V DC with reverse polarity protection                   |
| Supply voltage limits     | 21...26 V DC                                               |
| Current consumption       | <= 390 mA (no-load)                                        |
| Electrical connection     | 2 male connectors M12 12 pins                              |
| Input type                | Trigger mode                                               |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Product certifications                | CE                           |
| Ambient air temperature for operation | 0...50 °C                    |
| Ambient air temperature for storage   | -20...60 °C                  |
| IP degree of protection               | IP65 conforming to IEC 60529 |

## Offer Sustainability

|                        |                                                |
|------------------------|------------------------------------------------|
| RoHS (date code: YYWW) | Will not be compliant<br>Will not be compliant |
|------------------------|------------------------------------------------|