# RM35TM50MW

Modular motor voltage and temperature control relay, 5 A , 2 NO, 24..240 V AC/DC





#### Main

Range of product	Zelio Control
Product or component type	Modular measurement and control relays
Relay type	Motor temperature control relay
Product specific application	For 3-phase supply
Relay name	RM35TM
Relay monitored parameters	Phase sequence Motor temperature via PTC probe Phase failure detection
Time delay	Fixed 0.3 s
Switching capacity in VA	1250 VA
Measurement range	208480 V voltage AC 020 Ohm short-circuit detection

Complementary

Complementary	
Reset time	10000 ms output
Maximum switching voltage	250 V AC 250 V DC
Minimum switching current	10 mA 5 V DC
Maximum switching current	5 A AC 5 A DC
Supply voltage limits	20.4264 V AC 20.4264 V DC
Power consumption in VA	04 VA 24240 V AC
Power consumption	0.5 W DC
Control circuit frequency	5060 Hz +/- 10 %
Resistance across terminals	602 mOhm
Output contacts	2 NO
Nominal output current	5 A
Measurement voltage limits	176528 V AC
Delay at power up	500 ms
Voltage range	176528 V
Response time	> 50 ms input Y1 (contact Y1-T1) and push-button)
[Uc] control circuit voltage	<= 3.6 V temperature control circuit T1-T2 terminals open)
Short-circuit current	0.007 A temperature sensing circuit T1-T2 terminals short circuited)
Maximum resistance	1500 Ohm temperature sensor 68 °F (20 °C)
Tripping threshold	3100 Ohm +/- 10 % temperature control circuit
Reset threshold	1650 Ohm +/- 10 % temperature control circuit
Marking	CE
Overvoltage category	III IEC 60664-1
Insulation resistance	<ul> <li>&gt; 500 MOhm 500 V DC between supply and relay output IEC 60255-5</li> <li>&gt; 500 MOhm 500 V DC between measurement and relay output IEC 60664-1</li> <li>&gt; 1 MOhm 500 V DC between supply and measurement IEC 60255-5</li> <li>&gt; 500 MOhm 500 V DC between supply and relay output IEC 60664-1</li> <li>&gt; 500 MOhm 500 V DC between measurement and relay output IEC 60255-5</li> <li>&gt; 1 MOhm 500 V DC between supply and measurement IEC 60664-1</li> </ul>
[Ui] rated insulation voltage	400 V IEC 60664-1
Supply frequency	50/60 Hz +/- 10 %

Operating position	Any position without derating
Connections - terminals	Screw terminals, 1 x 0.51 x 4 mm² AWG 20AWG 11) solid without cable end Screw terminals, 2 x 0.52 x 2.5 mm² AWG 20AWG 14) solid without cable end
	Screw terminals, 1 x 0.21 x 2.5 mm $^2$ AWG 24AWG 12) flexible with cable end Screw terminals, 2 x 0.22 x 1.5 mm $^2$ AWG 24AWG 16) flexible with cable end
Tightening torque	5.318.85 lbf.in (0.61 N.m) IEC 60947-1
Housing material	Self-extinguishing plastic
Local signalling	LED (green) for power ON Phase of relay (R2) LED yellow) Temperature of relay (R1) LED yellow)
Mounting support	35 mm symmetrical DIN rail EN/IEC 60715
Electrical durability	10000 cycles
Mechanical durability	30000000 cycles
Operating rate	<= 360 operations/hour full load
Utilisation category	AC-12 IEC 60947-5-1 AC-13 IEC 60947-5-1 AC-14 IEC 60947-5-1 AC-15 IEC 60947-5-1 DC-12 IEC 60947-5-1 DC-13 IEC 60947-5-1
Maximum Width	1.38 in (35 mm)
Net Weight	0.29 lb(US) (0.13 kg)

#### Environment

Immunity to microbreaks	20 ms 20.4 V
Electromagnetic compatibility	Emission standard for industrial environments EN/IEC 61000-6-4 Emission standard for residential, commercial and light-industrial environments EN/IEC 61000-6-3 Immunity for industrial environments EN/IEC 61000-6-2
Standards	EN/IEC 60255-6 IEC 60034-11-2
Product certifications	GL UL GOST C-tick CSA
Directives	73/23/EEC - low voltage directive 89/336/EEC - electromagnetic compatibility
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-4122 °F (-2050 °C)
Relative humidity	95 % 131 °F (55 °C) IEC 60068-2-30
Vibration resistance	0.35 mm 557.6 Hz)IEC 60068-2-6 1 gn 57.6150 Hz)IEC 60255-21-1
Shock resistance	15 gn 11 ms IEC 60255-21-1
IP degree of protection	IP20 IEC 60529 terminals) IP30 IEC 60529 casing)
Pollution degree	3 IEC 60664-1
Dielectric test voltage	2 kV AC 50 Hz, 1 min
Non-dissipating shock wave	4 kV

#### Ordering and shipping details

Category	22380 - RELAYS-MEASUREMENT (RM17-RM35)	
Discount Schedule	CP2	
GTIN	00785901492177	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.29 lb(US) (0.13 kg)	
Returnability	No	
Country of origin	ID	

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.77 in (4.5 cm)
Package 1 width	3.07 in (7.8 cm)
Package 1 Length	3.78 in (9.6 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	48
Package 2 Weight	15.25 lb(US) (6.918 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

#### Offer Sustainability


Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty		
Warranty	18 months	

# RM35TM50MW

#### 3-Phase Supply and Motor Temperature Control Relays

#### **Dimensions and Mounting**




## Product data sheet Connections and Schema

# RM35TM50MW

3-Phase Supply and Motor Temperature Control Relays

#### Wiring Diagram




# Product data sheet Technical Description


### RM35TM50MW

#### **Function Diagrams**

Phase Sequence Control and Phase Failure Detection (U measured < 0.7 x nominal supply voltage)



#### Motor Temperature Control via PTC Probe



#### Legend

Un Nominal 3-phase supply voltage

R T1-T2 Resistance between terminals T1 and T2

11-14 R1 output relay connections

Relay status: black color = energized.

NOTE: The temperature control relay can take up to 6 PTC (positive temperature coefficient) probes wired in series between terminals T1 and T2.