



### Main

Range of product	Zelio Relay
Product or component type	Plug-in relay
Device short name	RHK
Contacts type and composition	4 C/O
Contact operation	Standard Latching
[Uc] control circuit voltage	110 V AC, 50 Hz
[Ithe] conventional enclosed thermal current	5 A at $\leq 40$ °C
Status LED	Without
Control type	Manual control
Coil interference suppression	Without

### Complementary

[Ui] rated insulation voltage	250 V
Test levels	Level A group mounting
Operating position	Any position
Minimum switching capacity	150 mVA / 1 V 150 mVA at 10 mA
Contact bounce time	$\leq 10$ ms
Voltage drop	$\leq 100$ V for 3 A at 24 V
Average resistance	30 mOhm at 20 °C
Average coil consumption in VA	6 (inrush) on coil 1 1.3 (holding) on coil 2 2.5 (inrush) on coil 2 3.5 (holding) on coil 1
Control circuit voltage limits	0.8...1.1 Uc conforming to IEC 60255
Drop-out voltage threshold	0.15...0.5 Uc
Cos phi	0.6 (inrush) 0.7 (holding)
Mechanical durability	10000000 cycles
Operating rate	$\leq 2$ cyc/mn
Operating time	1...3 ms for energisation/de-energisation 0.5...6 ms for de-energisation/energisation

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

5...17 ms between energisation of coil and closing of NO contact at 20 °C  
8...16 ms between energisation of trip coil and closing of NC contact at 20 °C

Minimum pulse duration	50 ms
CAD overall width	33 mm
CAD overall height	43 mm
CAD overall depth	90 mm
Terminals description ISO n°1	(B1-B2)CO (41-42-44)OC (21-22-24)OC (31-32-34)OC (A1-A2)CO (11-12-14)OC
Product weight	0.14 kg

## Environment

Standards	NF C 45-250 BS 4794 IEC 255 VDE 0435
Product certifications	USSR BV UR CSA EDF ASE
Protective treatment	TC
Dielectric strength	2500 V
Ambient air temperature for operation	-5...40 °C conforming to IEC 60255
Ambient air temperature for storage	-40...70 °C
Vibration resistance	6 gn (f = 10...55 Hz) conforming to IEC 60068-2-6 6 gn (f = 10...55 Hz) conforming to NF C 20-616
Shock resistance	30 gn for 11 ms conforming to NF C 20-608

## Contractual warranty

Warranty period	18 months
-----------------	-----------