XKZA15100

potentiometer -10000 Ohm - for XKB XKD XKM



Main Product or component Controllers separate parts Accessory / separate Control accessories part category Product specific Medium hoisting applications Heavy hoisting applications Light hoisting applications application XKB Product compatibility XKD XKM Potentiometer Accessory / separate part type Condition of use For standard applications Ohmic value 10000 Ohm

15 mm

Complementary

Complementary		
Standards	UTE 93-265	
Potentiometer characteristic	Linear function Continuous rotational operation	
Operating angle	360 °	
Mechanical durability	3000000 cycles	
Centre tap	Wired out to terminal	
Centre tap dead zone	2 ° +/- 1 %	
Power dissipation in W	3 W 185 °F (85 °C)	
Connections - terminals	Flying leads from soldered standard tags	
Net Weight	0.13 lb(US) (0.06 kg)	

Size

Environment

Mounting mode	By the body
---------------	-------------

Ordering and shipping details

Category	22474 - PUSHBUTTON,CRANE JOYSTICKS	
Discount Schedule	1	
GTIN	00785901850038	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.14 lb(US) (0.06 kg)	
Returnability	No	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.73 in (4.4 cm)	
Package 1 width	2.44 in (6.2 cm)	
Package 1 Length	2.13 in (5.4 cm)	
Unit Type of Package 2	S01	
Number of Units in Package 2	24	
Package 2 Weight	3.66 lb(US) (1.66 kg)	
Package 2 Height	5.91 in (15 cm)	

Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	
Warranty	18 months