## Product data sheet Characteristics

## XVMC21

base unit with cover XVM -  $\varnothing$  45 mm - white - screw terminals - IP40



IVIAIII		
Range of product	Harmony XVM	:
Product or component type	Base unit with cover	
Kit composition	Base unit Cover	,
Component name	XVM	
Indicator bank base type	Base without buzzer	

## Complementary

Mounting diameter	45 mm	
Housing colour	White	
Connections - terminals	Screw terminals: 1 x 0.3251 x 1.5 mm <sup>2</sup>	
Marking	CE	
Product weight	0.055 kg	

#### **Environment**

Liviloriiicit		
Standards	EN/IEC 60947-1	
	EN/IEC 60947-5-1	
Product certifications	CCC	
Ambient air temperature for storage	-2570 °C	
Ambient air temperature for operation	-1050 °C	
Electrical shock protection class	Class I aluminium tube mounting conforming to IEC 60947-1	
	Class I aluminium tube mounting conforming to IEC 60947-5-1	
	Class I aluminium tube mounting conforming to IEC 61140	
IP degree of protection	IP40 in any position except vertical position conforming to IEC 60529	
	IP42 in vertical position conforming to IEC 60529	
Protective treatment	TC	

#### Contractual warranty

Warranty period	18 months


# Product data sheet Dimensions Drawings

## XVMC21

## **Customer Assembled Tower Light**

#### **Dimensions**

Below drawing shows a tower light with 3 illuminated stages. Select the number of stages according to the product characteristics in order to get b dimension.




- (1) Cover (included with base unit)
- (2) Illuminated unit, to be ordered separately
- (1) Cover (inc(2) Illuminated(3) Base unit
- (4) Fixing base XVMZ0•/Z0•T, to be ordered separately

Number of illuminated units (ref. 2)	b in mm	b in in.
1	127	5.00
2	192	7.56
3	257	10.12
4	322	12.68
5	387	15.24

## XVMC21

## **Customer Assembled Tower Light**

## Wiring Diagram



Indicator bank with buzzer (4 illuminated units max.):

- 4: 4th illuminated unit
- 3: 3rd illuminated unit
- 2: 2nd illuminated unit
- 1: 1st illuminated unit
- N: Common
- B: Buzzer

Indicator bank without buzzer:

- 5: 5th illuminated unit
- 4: 4th illuminated unit
- 3: 3rd illuminated unit
- 2: 2nd illuminated unit
- 1: 1st illuminated unit
- N: Common

Maximum capacity for wiring through support tube:

- 6 wires x 1 mm<sup>2</sup>/16 AWG,
- 5 wires x 1.5 mm<sup>2</sup>/14 AWG