Product data sheet Characteristics

XT112S1PAL2

capacitive sensor - XT1 - cylindrical M12 - stainless steel - Sn 2mm - cable 2m



Main

Range of product	OsiSense XT
Sensor type	Capacitive proximity sensor
Product specific application	Detection of insulated or conductive materials
Sensor name	XT1
Sensor design	Cylindrical M12
Size	50 mm
Body type	Fixed
Detector flush mounting acceptance	Flush mountable
Material	Stainless steel
Enclosure material	Stainless steel 303
Type of output signal	Discrete
Wiring technique	3-wire
[Sn] nominal sensing distance	0.08 in (2 mm)
Discrete output function	1 NO
Output circuit type	DC
Discrete output type	PNP
Electrical connection	Cable
Cable length	6.56 ft (2 m)
[Us] rated supply voltage	24 V DC reverse polarity protection
Maximum delay response	5 ms
IP degree of protection	IP67 IEC 60529 IP67 IEC 60947-5-2

Complementary

Complementary	
ISO thread	M12 x 1
Detection face	Frontal
[Sa] assured operating distance	0.000.06 in (01.44 mm)
Adjustment zone	0.020.20 in (0.55 mm)
Differential travel	< 0.2 x Sr
Repeat accuracy	< 0.1 x Sr
Wire insulation material	PVC
Status LED	Output state indication 1 LED yellow)
Supply voltage limits	1230 V DC
Maximum residual current	0.1 mA open state
Protection type	Short-circuit protection
Switching frequency	<= 300 Hz
Maximum voltage drop	<2 V closed)
Current consumption	< 15 mA
Maximum delay first up	30 ms
Maximum delay recovery	5 ms
Maximum switching current	200 mA
Marking	CE
Setting-up	Sensitivity by potentiometer
Threaded length	1.46 in (37 mm)
-	

Length	1.97 in (50 mm)
Net Weight	0.15 lb(US) (0.07 kg)
Environment	
Standards	EN/IEC 60947-5-2
Product certifications	CETLus
Ambient air temperature for operation	-13158 °F (-2570 °C)
Vibration resistance	10 gn 1 mm 1055 Hz)IEC 60068-2-6
Shock resistance	30 gn 11 ms IEC 60068-2-27
Resistance to electrostatic discharge	4 KV contact IEC 61000-4-2
Resistance to electrostatic discharge	8 kV air IEC 61000-4-2
Resistance to electromagnetic fields	2.74 V/m (3 V/m) IEC 61000-4-3
Resistance to fast transients	2 kV IEC 61000-4-4
Ordering and shipping details	
Category	22490 - SENSORS-ULTRASONIC (XX5,6)
Discount Schedule	DS2
GTIN	00785901481805
Nbr. of units in pkg.	1
Package weight(Lbs)	0.15 lb(US) (0.07 kg)
Returnability	No
Country of origin	DE
Packing Units	
Package 1 Height	0.120 dm
Package 1 width	1.500 dm
Package 1 Length	2.100 dm
· · · · · · · · · · · · · · · · · · ·	
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to
	MANAY D65/Marnings on gov
REACh Regulation	www.P65Warnings.ca.gov
REACh Regulation EU RoHS Directive	REACh Declaration

18 months


Contractual warranty

Warranty

Product data sheet **Dimensions Drawings**

XT112S1PAL2

Dimensions





- Adjustment potentiometer LED


Product data sheet Mounting and Clearance

XT112S1PAL2

Setting-up


Minimum Mounting Distances (mm)

Side by side




e(1) 0

Face to face



e(2) 4.4


Facing a metal object



e(3) 4

o(o) ≥


Mounted in support



Fixing nut tightening torque: 10 N.m

Adjustment

Sensitivity Adjustment



- (1) Adjustment potentiometer
- (2) Screwdriver (included with sensor)


Product data sheet Connections and Schema

XT112S1PAL2

Wiring Diagram

Pre-cabled

3-wire DC, PNP NO Output, Pre-cabled



(BU) Blue

(BN) Brown

(BK) Black